

Huebsch®

Huebsch


Commercial Homestyle
Frontload Washer, Dryer
and Stack Washer/Dryer



A Classic Laundry Solution




Commercial Homestyle Frontload Washer, Dryer and Stack Washer/Dryer Specifications



Frontload Washer (FTZA0/FTZA1)[†]



Dryer (FEZ17/FGZ17)[†]



Stack Washer/Dryer (LTZA9A/LTZA7A)

Washer

Model	FTZA0/FTZA1
Width - in (mm)	26 7/8" (683)
Depth - in (mm)	28" (711)
Height* - in (mm)	41 3/8" (1054)
Speeds	6
Cycles	5
	<ul style="list-style-type: none"> • Regular • Permanent Press • Delicate • Rinse and Spin • Spin Only
Water Temperatures	4
	<ul style="list-style-type: none"> • Hot/Cold • Warm/Warm • Warm/Cold • Cold/Cold
Features	
Stainless Steel Washtub - cu. ft.	2.84
Water Pressure - psi (bar)	Fill 20 - 120 (1.4/8.3)
Wash/Tumble	41, 50 RPM
Distribution/Pump	80 RPM
Spin Speeds	500, 650, 1000 RPM
Activation	Push-to-Start
Dispenser	Detergent, Liquid Bleach, Liquid Softener
Motor, HP	Variable-spd., 3/4 HP
Color	White
Electrical Specs.	120/60/1 • 15 amp
Net Weight - lb (kg)	240 (109)
Shipping Weight - lb (kg)	260 (118)
Agency Approvals	cULus
* Heights may vary slightly depending on leveling adjustments.	
Motor: 3/4 HP reversing, permanently lubricated with a built-in electronic protector.	
Electrical Requirements: Grounded 3-wire, 120V, 60 Hz AC, 15 amp circuit separately fused.	

Key Washer Features

- Exclusive inner and outer stainless steel tubs
- Extra-large 2.84 cu. ft. capacity
- Frontmount supply dispenser
- Automatic supply injection**
 - ~ Simplifies connection to solution dispenser
 - ~ Eliminates spills
 - ~ Solution enters from hose ports and is diluted with water for entry into the washtub



Key Dryer Features

- Extra-large 7.0 cu. ft. capacity
- Secured, upfront lint filter



** FTZA1 Only

[†] Meets all A.D.A. (Americans with Disabilities Act) guidelines for handicap accessibility.

Stack Washer/Dryer

Models	LTZA7/LTZA9
Width - in (mm)	26 7/8" (683)
Depth - in (mm)	28" (711)
Height - in (mm)	75 1/4" (1908)
Net Weight - lb (kg)	Elec.: 350 (159) Gas: 355 (161)
Shipping Weight - lb (kg)	Elec.: 380 (172) Gas: 385 (175)
Agency Approvals	Elec.: cCSA _{US} Gas: CSA, CSA Flame
Due to continuous product improvements, design and specifications are subject to change without notice. The quality management systems at all Alliance Laundry Systems manufacturing facilities are registered as ISO 9001:2000 compliant.	

Dryer

Model	FEZ17/FGZ17
Width - in (mm)	26 7/8" (683)
Depth - in (mm)	28" (711)
Height* - in (mm)	41 1/2" (1054)
Cylinder Volume	7.0 cu. ft.
Cycles	6
Auto	Regular/Delicate <ul style="list-style-type: none"> • More Dry • Less Dry Permanent Press/Knits <ul style="list-style-type: none"> • More Dry • Less Dry Time <ul style="list-style-type: none"> • More Dry • Less Dry
Features	
Cylinder Interior	Galvanized Steel
Door Opening	180° Side Swing
Lint Filter	Secured
Color	White
Energy Input	Elec.: 5350W Gas: 22,500 Btu
Temperatures	3
	<ul style="list-style-type: none"> • Delicate • No Heat • Regular/Perm Press
Net Weight - lb (kg)	Elec.: 150 (68) Gas: 155 (70)
Shipping Weight - lb (kg)	Elec.: 160 (73) Gas: 165 (75)
Agency Approvals	Elec.: cCSA _{US} Gas: CSA Flame
* Heights may vary slightly depending on leveling adjustments.	
Motor: 1/3 HP, permanently lubricated with a built-in electronic protector.	
Electrical Requirements: (Elec.) 3 wire system (neutral conductor grounded), 120/240V, 60 Hz AC, 30 amp circuit separately fused. (Gas) 2 wire plus grounded (earth) wire system, 120V, 60 Hz AC, 15 amp circuit separately fused.	

©Copyright 2007 Alliance Laundry Systems LLC

AH07-203

Alliance Laundry Systems, Shepard Street, Ripon, WI 54971 Telephone: 1-800-553-5120

www.huebsch.com