

Huebsch®

Huebsch

Commercial Homestyle Topload Washer



A Classic Laundry Solution



Commercial Homestyle Topload Washer Specifications



Control Panel Features

- Seven cycle selections
- Variable rotary water level control
- Four wash/rinse temperatures

Key Product Features

- **Automatic Balancing System (ABS)**
with rear self-leveling legs maximizes smooth and quiet operation on all floor types. High-speed extract of 710 RPM maximizes moisture removal for fast drying and lower dryer energy use.
- **Commercial quality transmission**
is of the highest quality with results proven in our rugged commercial models.
- **Large porcelain washtub**
provides resistance to chipping and scratching.
- **Extra-large lid opening**
for easy loading and unloading.
- **Front serviceability**
allows simple removal of front panel or control hood on both washer and dryer. This provides easy access for servicing from installed position.



Attractive Control Panel

Commercial homestyle topload washers have attractive styling to match electric or gas dryer.



| | |
|-----------------------------------|--|
| Model | LWZ02 |
| Speeds | 1 |
| Cycles | 7 |
| Regular | Heavy, Normal, Light |
| Permanent Press | Normal, Light |
| Delicate | Normal, Light |
| Water Temperatures | 4 <ul style="list-style-type: none"> • Hot/Cold • Warm/Cold • Cold/Cold |
| Features | |
| Water Levels | Variable Rotary |
| Agitator | Curved Vane |
| Basket Volume - cu. ft. | 3.3 |
| Agitation Speed | 67 RPM |
| Spin Speed | 710 RPM |
| Activation | Pull-to-Start |
| Top and Lid Finish | Tuff Guard |
| Tub | Blue Porcelain |
| Dispenser | Bleach |
| Color | White |
| Self-Adjusting Rear Leveling Legs | Yes |
| Dimensions | |
| Width - in (mm) | 25 5/8" (651) |
| Depth - in (mm) | 28" (711) |
| Height* - in (mm) | 43" (1092) |
| Work Surface Height* - in (mm) | 36" (914) |
| Approx. Weight - lb (kg) | 180 (82) |
| Agency Approvals | cCSAus |

* Heights may vary slightly depending on leveling adjustments.

Motor: 1/2 HP reversing, permanently lubricated with a built-in automatic thermal overload protector.

Electrical Requirements: Grounded 3-wire, 120V, 60 Hz AC, 15 amp circuit separately fused.

Warranty: At Huebsch, we're so confident that our quality washers and dryers are built to last, we offer a THREE-year warranty** on the entire machine. The washer transmission assembly is under warranty for FIVE years.**

** Parts only, labor not included.
See Huebsch Warranty Bond for specifics.



Due to continuous product improvements, design and specifications are subject to change without notice. The quality management systems at all Alliance Laundry Systems manufacturing facilities are registered as ISO 9001:2000 compliant.

©Copyright 2007 Alliance Laundry Systems LLC