

Huebsch®

Huebsch

Commercial Homestyle Frontload Washer



A Classic Laundry Solution



Commercial Homestyle Frontload Washer Specifications



Control Panel Features

- Five cycle selections
- Four wash/rinse temperatures

Key Product Features

- Exclusive inner and outer stainless steel washtub
Lifetime warranty.
- Extra-large capacity **2.84 cu. ft.**
- Superior wash system
Reversing wash action with two wash speeds and three spin speeds. Exclusive 4,912 perforated washtub holes. Three large tub baffles to maximize clothes turn.
- Large door opening with see-through glass
The door handle is located at the 11:00 position, for easy opening. The door swings 180° to accommodate user friendly loading.
- Frontmount supply dispenser
Automatically adds detergent, liquid bleach and liquid softener.
- High-speed extract
Huebsch frontloading washer features a 1,000 RPM spin speed for maximum water removal from clothes. This means faster drying and lower dryer energy use.
- Attractive control panel
Commercial homestyle frontload washers have attractive styling to match electric or gas dryers.
- Energy efficient
Our frontload washer uses only 13.9 gallons of water, reducing total water consumption compared to a topload washer. It also uses less hot water, averaging 1.74 gallons of hot water per load.



Model	LTZA0
Speeds	6
Cycles	5
	<ul style="list-style-type: none"> • Regular • Rinse and Spin • Perm Press • Spin Only • Delicate
Water Temperatures	4
	<ul style="list-style-type: none"> • Hot/Cold • Warm/Warm • Warm/Cold • Cold/Cold
Features	
Stainless Steel Washtub	2.84 cu. ft.
Water Pressure - psi (bar)	Fill 20 – 120 (1.4/8.3)
Wash/Tumble	41, 50 RPM
Distribution/Pump	90 RPM
Spin Speeds	500, 650, 1000 RPM
Activation	Push-to-Start
Dispenser	Detergent, Liquid Bleach, Liquid Softener
Motor HP	Variable speed induction, 3/4 HP
Top Finish	Tuff Guard
Color	White
Dimensions	
Width - in (mm)	26 7/8" (682)
Depth - in (mm)	28" (711)
Height* - in (mm)	43" (1092)
Work Surface Height* - in (mm)	36" (910)
Approx. Weight - lb (kg)	230 (105)
Agency Approvals	cUL _{us}

* Heights may vary slightly depending on leveling adjustments.

Motor: 3/4 HP reversing, permanently lubricated with a built-in electronic protector.

Electrical Requirements: Grounded 3-wire, 120V, 60 Hz AC, 15 amp circuit separately fused.

Warranty: At Huebsch, we're so confident that our quality washers and dryers are built to last, we offer a **THREE-year warranty**** on the entire machine. The washer transmission assembly is under warranty for **FIVE years.****

** Parts only, labor not included.
See Huebsch Warranty Bond for specifics.



Due to continuous product improvements, design and specifications are subject to change without notice. The quality management systems at all Alliance Laundry Systems manufacturing facilities are registered as ISO 9001:2000 compliant.

©Copyright 2007 Alliance Laundry Systems LLC