

Huebsch

Huebsch

Flatwork Finishers

8" (200 mm)

13" (325 mm)

20" (500 mm)



Serving the Laundry Industry For Over 90 Years



Flatwork Finisher Specifications

Key Product Features

- Huebsch now offers a full range of heated cylinder flatwork finishers that are simple to operate, will save you in labor and energy costs, and their smart design is a space saver as well!

- These new finishers are built to meet all the needs of hotels, nursing homes, hospitals, and on premises laundries. They are designed to boost the efficiency and productivity of each laundry operation.



- All models are equipped with a frequency-controlled motor, suspended roll, Nomex ironing belts, finger guards, a safety handle in case of power failure, easy access to all components, and an optimized exhaust system.

- All Huebsch finishers are constructed of heavy duty steel frames and thick polished steel cylinders, and are backed by a one year warranty.

Models	UD08F055	UD13F063	UD13F078	UD20F075	UD20F098	UD20F126
Roll Diameter - in (mm)	8" (200)	13" (325)	13" (325)	20" (500)	20" (500)	20" (500)
Finishing Width - in (mm)	55" (1400)	63" (1600)	78" (2000)	75" (1900)	98" (2500)	126" (3200)
Ironing Speed - ft/m (m/m)	3-15 (1-4.5)	3-30 (1-9)	3-30 (1-9)	3-30 (1-9)	3-30 (1-9)	3-30 (1-9)
Overall Dimensions* L" x D" x H" - in (mm)	74" x 17.5" x 43.7" (1880 x 445 x 1110)	86" x 26" x 43.8" (2192 x 661 x 1113)	100.1" x 26" x 43.8" (2542 x 661 x 1113)	117.1" x 42.2" x 46.1" (2975 x 1072 x 1171)	140.7" x 42.2" x 46.1" (3574 x 1072 x 1171)	168.3" x 42.2" x 46.1" (4275 x 1072 x 1171)
Roll Motor - HP (kW)	.33 (.25)	.33 (.25)	.33 (.25)	.5 (.37)	.5 (.37)	.5 (.37)
Roll Exhaust Motor - HP (kW)	1 x .12 (.09)	2 x .16** (2 x .12**)	2 x .16 (2 x .12)	2 x .34*** (2 x .25***)	2 x .34 (2 x .25)	2 x .34 (2 x .25)
Roll Exhaust Duct - in (mm)	1 x 3.25" (83)	2 x 4*** (2 x 98**)	2 x 4" (2 x 98)	2 x 6**** (2 x 150****)	2 x 6" (2 x 150)	2 x 6" (2 x 150)
Gas Heating						
Maximum Gas Input - Btu (kW)	N/A	76,792 (23)	102,340 (30)	136,453 (40)	187,623 (55)	235,495 (69)
Gas Inlet - in (mm)	N/A	3/4" (14)	3/4" (14)	1" (22)	1" (22)	1" (22)
Electrical Requirements • Circuit Breaker	N/A N/A N/A	120/60/1 • 15 230/50/3 • 6 400/50/3 • 6	120/60/1 • 15 230/50/3 • 6 400/50/3 • 6	120/60/1 • 15 230/50/3 • 6 400/50/3 • 6	120/60/1 • 15 230/50/3 • 6 400/50/3 • 6	120/60/1 • 15 230/50/3 • 6 400/50/3 • 6
Electric Heating						
Capacity Resistances - HP (kW)	14 (10.5)	21 (16)	27 (20)	42 (31.5)	54 (40.5)	72 (54)
Electrical Requirements • Circuit Breaker	208-240/60/3 • 40 230/50/3 • 40 400/50/3 • 25	208-240/60/3 • 50 230/50/3 • 50 400/50/3 • 32	208-240/60/3 • 63 230/50/3 • 63 400/50/3 • 40	208-240/60/3 • 100 230/50/3 • 100 400/50/3 • 63	208-240/60/3 • 125 230/50/3 • 125 400/50/3 • 63	208-240/60/3 • 163 230/50/3 • 163 400/50/3 • 100
Steam Heating						
Steam Inlet - in (mm)	N/A	N/A	N/A	3/4" (19.5)	3/4" (19.5)	3/4" (19.5)
Condensate Return - in (mm)	N/A	N/A	N/A	1/2" (12.7)	1/2" (12.7)	1/2" (12.7)
Hourly Consumption - lb/hr (kg/hr)	N/A	N/A	N/A	110 (50)	147 (67)	187 (85)
Min.-Max. Steam Pressure - Psi (bar)	N/A	N/A	N/A	145 (10)	145 (10)	145 (10)
Electrical Requirements • Circuit Breaker	N/A N/A N/A	N/A N/A N/A	N/A N/A N/A	120/60/1 • 15 230/50/3 • 4 400/50/3 • 4	120/60/1 • 15 230/50/3 • 4 400/50/3 • 4	120/60/1 • 15 230/50/3 • 4 400/50/3 • 4
Shipping Weight - lb (kg)	418 (190)	1320 (599)	1474 (669)	2167 (984)	2796 (1269)	3421 (1553)
Approvals	ETL, CE	CSA, ETL, CE	CSA, ETL, CE	CSA, ETL, CE	CSA, ETL, CE	CSA, ETL, CE

* Removal of trays will allow 32" door access on all models.

** One motor on electric models.

*** One motor on steam models.

Due to continuous product improvements, design and specifications subject to change without notice.

© Copyright 2004 Alliance Laundry Systems LLC