

Huebsch®

Huebsch

**HC20-80 lb A-Micro
Coin-Operated
Washer-Extractors**



A Classic Laundry Solution





Today's coin laundry needs are ever-changing, but your need for reliability, durability and energy efficiency remains constant. And now more than ever, you need equipment that is going to meet the changing needs of a diverse customer base. Huebsch A-Micro washer-extractors give you virtually unlimited cycle flexibility, but more importantly, they give your customer the opportunity to customize their own cycles, and the price adjusts automatically as the user selects various options.

Unmatched Warranty

At Huebsch, we're so confident that our quality washer-extractors are built to last, we offer a **THREE**-year warranty* on the entire machine. The frame, cylinder, shaft, bearings and seals are warrantied for **FIVE** years.*

3 year limited warranty*

* Parts only, labor not included.
See Huebsch Warranty Bond for specifics.

User-friendly and Flexible

For ease of use, the **A-Micro** control provides customers with six preset cycles and simple push-button operation. The status LEDs show users how the cycle is progressing. The main display shows vend price and time remaining. If necessary, the preset cycles can be easily reprogrammed by the owner to adjust to individual preferences and/or market needs.



Unlimited Revenue Generation

With the **A-Micro**, each of the six preset cycles can be programmed with a different vend price. Since hot water costs you more to provide, you can charge more for a hot wash cycle and less for a warm or cold cycle.



Customers with special wash requirements can further tailor their cycles with the simple push of the **extra wash and rinse keys**. The premium vends charged for extra features add to the store's profit potential. The machine automatically increases the vend price according to the options selected. This fantastic feature allows you to set wash prices for your store at a competitive level and customers who want an even "better" cycle, have the ability to build the cycle they really want, and you have the ability to generate additional revenue, and profit!

And that's not all. The **A-Micro** also has a **time-of-day pricing** capability that allows the store owner to pre-program the machines to offer promotional pricing during a selected time period on certain days of the week.

Energy Efficient

The **six preset cycles** are among our most efficient ever. The preset cycles on the **A-Micro** can **reduce overall water** usage per cycle by as much as **45%-55%** compared to older fixed-cycle models. These water savings add up month after month, and this feature alone will improve the bottom line profit of any laundry.



Optional 140 G-Force

Combine the A-Micro's energy efficient preset cycles with our optional super-fast **140 G-Force final extract speed****, and you have a real solution to rising energy prices. On a typical 30 lb washer, the 140 G-Force spin speed can remove an extra **1/2 gallon** of water from the load. By choosing washers with this higher spin speed, you can move customers through your store faster, and cut your gas usage by as much as **15%**. An up-front investment in washers with this capability will pay dividends for years to come in the way of **lower utility costs**.

** This feature is standard on our 80 lb models.

Convenience

The bigger the door, the easier the loading and unloading. Our **large stainless steel doors** open wide and seal tight.





The easy-to-use **automatic supply dispenser** allows customers to add detergents, softeners, etc. when the machine is started. The three compartments are clearly marked and identified with easy-to-follow instructions.



Quality That Lasts

The superior quality of Huebsch washer-extractors starts with our **strong industrial frames** that weigh almost as much as most competitor's complete machines. The structural steel is the same rugged material used in the construction of bridges and skyscrapers. All-welded construction is used with no riveted or bolted connections.

The simple design of our **direct V-belt drive system** eliminates high maintenance nuisance problems such as clutches, jackshafts and transmissions. Count on low service costs, high efficiency and long life.



Huebsch's **heavy-duty bearings** ensure long-term trouble-free performance. Two double-lip seals provide four sealing surfaces, which isolate the bearings from the wash load for absolute protection.

While **high quality internal components** ensure years of reliable service, rugged exterior panels form the **protective shell** of Huebsch washer-extractors. The components and panels used in Huebsch equipment are the result of demanding in-house testing to make certain they stand up to the rough demands of a commercial laundry.

Made In The USA



Huebsch washer-extractors are manufactured in Ripon, Wisconsin, USA and are sold and serviced by top quality distributors worldwide.

HC20-80 lb A-Micro Coin-Operated Washer-Extractor Specifications

HC Models		HC20	HC25	HC30	HC40	HC60	HC80
Capacity - lb (kg)		20 (9)	25 (11.3)	30 (13.6)	40 (18)	60 (27)	80 (36)
Overall Width - in (mm)		26" (660)	26" (660)	29" (737)	30 5/8" (778)	34 1/16" (865)	41 1/2" (1054)
Overall Depth* - in (mm)		29 13/16" (757)	33 13/16" (859)	34 13/16" (884)	40" (1016)	42 15/16" (1091)	52" (1321)
Overall Height - in (mm)		42 7/8" (1089)	44 7/8" (1140)	45 7/8" (1165)	47 1/4" (1200)	50 13/16" (1291)	56 7/8" (1444)
Cylinder Diameter - in (mm)		21" (533)	21" (533)	24" (610)	26 1/4" (667)	30" (762)	36" (916)
Cylinder Depth - in (mm)		13 3/4" (349)	18 3/4" (457)	16" (406)	20 1/4" (514)	22" (559)	22" (559)
Cylinder Volume - cu. ft. (liters)		2.76 (78.1)	3.76 (106)	4.19 (118)	6.34 (180)	9.0 (255)	12.4 (354)
Door Opening Size - in (mm)		11 5/8" (295)	11 5/8" (295)	14 11/32" (364)	16 1/4" (413)	16 1/4" (413)	18 1/2" (470)
Door Bottom to Floor - in (mm)		14 3/8" (365)	14 3/8" (365)	14" (356)	14 1/2" (368)	15" (381)	17 3/4" (451)
Distribution Speed (RPM)		N/A	N/A	N/A	N/A	N/A	63
Wash Speed - RPM	2-speed	57	57	49	51	44	N/A
	V-speed	52	N/A	52	46	46	40
Extract Speed - RPM	2-speed	528	529	464	491	469	N/A
	V-speed	686	N/A	686	613	574	524
G-Force Factor	2-speed	83.1	N/A	73.3	89.8	93.8	N/A
	V-speed	140	N/A	140	140	140	40/85/140
Water Inlet Connection - in (mm)		3/4" (19)	3/4" (19)	3/4" (19)	3/4" (19)	3/4" (19)	3/4" (19)
Steam Inlet Connection - in (mm)		1/2" (13)	1/2" (13)	1/2" (13)	1/2" (13)	1/2" (13)	1/2" (13)
Drain Connection Size - in (mm)		2" (52)	2" (52)	2" (52)	3" (76)	3" (76)	3" (76)
Drain Height To Floor - in (mm)		4 1/2" (114)	4 1/2" (114)	4" (100)	4 3/4" (121)	5" (127)	5 3/4" (146)
Motor hp (kw) Wash	2-speed	.15 (.11)	.25 (.19)	.24 (.18)	.40 (.30)	.55 (.41)	N/A
	V-speed	N/A	N/A	N/A	N/A	N/A	N/A
Motor hp Extract	2-speed	.74 (.55)	1.4 (1.04)	1.34 (1)	1.8 (1.3)	2.7 (2.01)	N/A
	V-speed	1 (.75)	N/A	1 (.75)	2.3 (1.7)	2.9 (2.2)	5 (3.73)
Voltage/Hz/Phase • Circuit Breaker - FLA	B	120/60/1 • 20-16	N/A	N/A	N/A	N/A	N/A
	C	380-415/50/3 • 15-4	380-415/50/3 • 15-4	380-415/50/3 • 15-4	380-415/50/3 • 15-5	380-415/50/3 • 15-4	N/A
	D	220-240/50/3 • 15-4	220-240/50/3 • 15-6	220-240/50/3 • 15-6	220-240/50/3 • 15-8	220-240/50/3 • 20-7	N/A
	E	220-240/50/1 • 20-10	220-240/50/1 • 20-10	220-240/50/1 • 20-10	N/A	N/A	N/A
	J	200/50/3 • 15-3	200/50/3 • 15-5	200/50/3 • 15-5	200/50/3 • 20-8	200/50/3 • 20-8	N/A
	O**	208-240/60/3 • 15-5	208-240/60/3 • 15-6	208-240/60/3 • 15-7	208-240/60/3 • 20-7	208-248/60/3 • 20-10	N/A
	P	N/A	N/A	N/A	380-415/50-60/3 • 15-3	380-415/50-60/3 • 15-5	380-415/50-60/3 • 15-4
	Q**	200-240/50/60/3 • 15-4	N/A	200-240/50/60/3 • 15-5	200-240/50/60/3 • 15-4	200-240/50/60/3 • 15-5	200-240/50/60/3 • 15-7
	X	N/A	N/A	N/A	N/A	200-240/50-60/1-3 • 15-9	N/A
	Y	208-240/60/1 • 15-10	208-240/60/1 • 20-10	208-240/60/1 • 20-10	208-240/60/1 • 30-14	N/A	N/A
Shipping Dimensions Approx. - in (mm)	H	51" (1295)	53 1/2" (1359)	53 1/2" (1359)	56 1/2" (1422)	58 1/2" (1486)	62 1/2" (1588)
	W	29" (737)	29" (737)	30 1/2" (774)	32" (813)	36" (914)	48" (1219)
	D	32 1/2" (826)	36 1/4" (921)	37 1/2" (953)	41" (1041)	44 1/2" (1130)	56" (1422)
Net Weight - lb (kg)		353 (160)	427 (193)	496 (225)	686 (311)	811 (368)	1346 (610)
Shipping Weight - lb (kg)		373 (169)	448 (203)	519 (235)	710 (322)	838 (380)	1420 (644)
Export Shipping Weight - lb (kg)		461 (209)	536 (243)	600 (272)	810 (367)	947 (430)	1545 (701)
Agency Approvals		ETL, ELTc CE,	ETL, ELTc CE,	ETL, ELTc CE,	ETL, ELTc CE,	ETL, ELTc CE,	ETL, ELTc CE,

* Overall depth includes drain pipe and door handle.

** Standard domestic voltage 208-240/60/3. Circuit breaker and amp draw data shown is for standard voltage models without auxiliary heat. Consult factory for other configurations. Manufacturer strongly recommends using a circuit breaker instead of fuses. Use 3-pole circuit breakers for 3-phase machines.

*** Agency approvals may vary depending on configuration. Consult factory for details. Steam connection requires 1/2" N.P.T.

Due to continuous product improvements, design and specifications subject to change without notice. The quality management systems at Alliance Laundry Systems manufacturing facilities are registered as ISO 9001:2000 compliant.

©Copyright 2007 Alliance Laundry Systems LLC

Printed in the U.S.A.



Printed on paper manufactured with virgin pulp from certified sources and a minimum of 10% post-consumer recovered fiber.

AH07-212

Alliance Laundry Systems, Shepard Street, Ripon, WI 54971 Telephone: 1-800-553-5120

www.huebsch.com