



The PT110 is a twisted pair transmitter for computer graphics video signals. It converts a computer graphics signal into a twisted pair signal which will be converted back to a computer graphics video signal when used in conjunction with the Kramer TP-120 twisted pair receiver (or other compatible Kramer receiver).

DESCRIPTION

- Resolution: Up to UXGA
- HDTV Compatible.
- Twisted Pair Output - RJ-45.
- System Range - Up to 100 meters (320'). Greater distances possible depending on resolution and cable.
- Cable - UTP (unshielded twisted pair) such as CAT5.
- Power Connect™ System Only one unit in a system, the transmitter or receiver, needs to be connected to a power source. All the system units must have Power Connect to use this feature.
- Ultra-compact - Part of the Kramer PicoTOOLSTM family of extremely compact, high quality and cost effective solutions.

SPECIFICATIONS

INPUTS:	1 VGA/XGA.
OUTPUTS:	1 RJ45 Line out.
MAX. OUTPUT LEVEL:	1.4Vpp.
BANDWIDTH (- 3DB):	Resolution: Up to UXGA
S/N RATIO:	80dB.
COUPLING:	AC.
POWER SOURCE:	12 VDC 60mA.
DIMENSIONS:	6cm x 6.5cm x 2.5cm (2.36" x 2.56 x 1", W, D, H).
WEIGHT:	0.14kg (0.31lbs) approx.
ACCESSORIES:	Power supply.

