



FC - 2

**SWITCHERS, MATRIX
SWITCHERS &
CONTROLLERS**

USB / RS-485 / RS-422 CONVERTER



The Kramer FC-2 is an adjustment-free, Plug and Play bi-directional USB to RS-485 or USB to RS-422 converter that incorporates the USB, RS-485, and RS-422 video and presentation industry interfaces. The machine can operate, using high quality cables for a range of up to 1200 meters (over 3,900 feet). The machine should be installed close to the USB source/acceptor. The FC-2 is housed in a Kramer PicoTOOLS® enclosure and uses the power provided by the USB port. The FC-2 is housed in a Kramer PicoTOOLS® enclosure and uses the power provided by the USB port.

DESCRIPTION

SPECIFICATIONS

- INTERFACE:** LINK (yellow) LED lights when the FC-2 is ready for use; TX (green) LED lights when data is transmitted from the USB port to the RS422/485 device; RX (red) LED lights when data is transmitted from the RS422/485 device to USB port.
- LEDS:** LINK (yellow) LED lights when the FC-2 is ready for use; TX (green) LED lights when data is transmitted from the USB port to the RS422/485 device; RX (red) LED lights when data is transmitted from the RS422/485 device to USB port.
- DIMENSIONS:** 6cm x 6.5cm x 2.5cm (2.36" x 2.56" x 1", W, D, H).
- WEIGHT:** 0.115kg. (0.25 lbs.) approx.
- ACCESSORIES:** USB Cable, Windows® 98/ME/2000/XP compatible software driver.

