
MUSICAL FIDELITY

X-A50 Power Amplifier

 Print This Page

OVERVIEW

50 watt monobloc power amplifier

FEATURES & BENEFITS

Two pairs of high current bipolar power transistors per unit	Very high peak current delivery gives excellent load driving ability coupled to solid bass control
---	--

Loop out facility	Allows easy 'daisy-chaining' of X-A50s for bi or tri-amping or home cinema use with existing setup
--------------------------	--

Compact monobloc construction	Complete physical separation of left and right channels for faultless soundstaging and imaging properties - ideal for surround sound use. Each unit may be placed very close to its speaker minimising the loudspeaker cable lengths - improves sound quality, particularly bass control
--------------------------------------	--

SPECIFICATIONS

Output power 50 Watts RMS into 8Ohms

100 Watts RMS into 4Ohms

THD < 0.04% 20Hz-20kHz unweighted
< 0.01% 20Hz-20kHz 'A' weighted
< 0.008% 20Hz-20kHz @ 1W unweighted

Frequency response +/- 0.2dB 20Hz-20kHz

S/N ratio greater than 102dB unweighted
greater than 114dB 'A' weighted

Power consumption 120W

Power requirements 100/115/230V 50/60Hz AC (factory preset
for country)

Dimensions (mm) 110 x 110 x 330 approx. (W x H x D)
width and height include feet, depth includes
terminals
