MUSICAL FIDELITY

A3.2 CD Player



Print This Page

OVERVIEW

FEATURES & BENEFITS

Upsampling.	This gives greatly improved sound due to digital noise and other artefacts being moved out of band.
	Allows complete circuits to operate ideally, giving truly extraordinary results.
Very low jitter.	Low clock errors mean more harmonic accuracy and dynamic range.

SPECIFICATIONS

DAC architecture	24 bit Delta-Sigma (Bitstream) Dual differential 8x oversampling
Disc mechanism	Sony
Upsampling	96kHz
Frequency response	10Hz to 20kHz +0 / -0.2 dB
Signal / noise ratio	> 115dB 'A' weighted
Total harmonic	< 0.006% 10Hz to 20kHz

distortion	
Total correlated jitter	< 170 pS
Channel separation	> 100dB 20Hz to 20kHz
Linearity	< 0.2dB down to -90dB
Audio output at digital 0dB level	2.14VRMS at 1kHz nominal
Analog output	One pair RCA connectors
Analog output impedance	50 Ohms
Digital outputs	One optical (Toslink) One S/PDIF (RCA connector).
Power requirements	100 / 115 / 230V AC 50 / 60Hz (factory preset) 15 Watts
	440mm, 17.3 inches wide. 102mm, 4 inches high including feet. 375mm, 14.8 inches deep including terminals.
Weight	6kg, 13.2lbs unit only, un-boxed. 8kg, 17.6lbs in shipping carton.
	Remote control handset (universal type). Two batteries (SUM-4, AAA, LR03). IEC type mains lead.