

## Tri-Vista 21 DAC

Print This Page



## **OVERVIEW**

The Tri-Vista 21 is part of a limited edition of 1300 pieces which will not be repeated and offer amazing value-formoney.

## **FEATURES & BENEFITS**

Improved version of the digital stage of the Tri-Vista SACD player.	State-of-the-art sound as good as any at any price. Extracts the maximum from your discs.
Full multi-stage choke regulation.	Extremely clean power supply lines and immunity from mains born interference which is particularly critical with CD players.
Upsampling at 96kHz and 192kHz.	·
Massive output stage using milspec 5703 tubes. Exactly the same configuration as used in the Tri-Vista SACD player.	High current low impedance output will drive any combination of preamp and cable up to about 35 feet in length. Sound quality is incredible.

## **SPECIFICATIONS**

Sampling frequencies  Data types 16, 20, 24 bit word lengths  Inputs RCA 75 Ohms, S/PDIF TOSLINK optical  Outputs RCA left and right analog audio, RCA digital loop out  Output impedence 50 Ohms  Frequency response 10Hz to 20kHz ± 0.0dB  Signal / Noise 114dB "A"- weighted  Total harmonic distortion 135pS  Channel separation < 109dB 20Hz to 20kHz  Linearity < 0.2dB down to -100dB  Audio output at digital 0dB level  Power Requirement 100 / 115 / 230 Volts AC 50 / 60Hz (factory pre-set for country), 30 Watts  Dimensions 440mm, 17.3 inches wide 105mm, 4.13 inches high (including feet) 375mm, 14.8 inches deep (including terminals)  Weight 13.15kg, 29lbs unit only, unboxed 15.2kg, 33.5lbs in shipping carton  Standard Accessories	DAC architecture	24-bit Delta-Sigma (Bitstream) Dual differential 8 times oversampling, 96/192kHz switchable
Inputs RCA 75 Ohms, S/PDIF TOSLINK optical  Outputs RCA left and right analog audio, RCA digital loop out  Output impedence 50 Ohms  Frequency response 10Hz to 20kHz ± 0.0dB  Signal / Noise 114dB "A"- weighted  Total harmonic distortion < 0.0025% 10Hz to 20kHz  Channel separation < 109dB 20Hz to 20kHz  Linearity < 0.2dB down to -100dB  Audio output at digital 0dB level  Power Requirement 100 / 115 / 230 Volts AC 50 / 60Hz (factory pre-set for country), 30 Watts  Dimensions 440mm, 17.3 inches wide 105mm, 4.13 inches high (including feet) 375mm, 14.8 inches deep (including terminals)  Weight 13.15kg, 29lbs unit only, unboxed 15.2kg, 33.5lbs in shipping carton  Standard IEC type mains lead		8 to 108kHz
Outputs RCA left and right analog audio, RCA digital loop out  Output impedence 50 Ohms  Frequency response 10Hz to 20kHz ± 0.0dB  Signal / Noise 114dB "A"- weighted  Total harmonic distortion 40.0025% 10Hz to 20kHz  Channel separation < 109dB 20Hz to 20kHz  Linearity < 0.2dB down to -100dB  Audio output at digital 0dB level Power Requirement 100 / 115 / 230 Volts AC 50 / 60Hz (factory pre-set for country), 30 Watts  Dimensions 440mm, 17.3 inches wide 105mm, 4.13 inches high (including feet) 375mm, 14.8 inches deep (including terminals)  Weight 13.15kg, 29lbs unit only, unboxed 15.2kg, 33.5lbs in shipping carton  Standard IEC type mains lead	Data types	16, 20, 24 bit word lengths
Output impedence 50 Ohms  Frequency response 10Hz to 20kHz ± 0.0dB  Signal / Noise 114dB "A"- weighted  Total harmonic distortion < 0.0025% 10Hz to 20kHz  Total correlated jitter 135pS  Channel separation < 109dB 20Hz to 20kHz  Linearity < 0.2dB down to -100dB  Audio output at digital 0dB level 2.17 Volts RMS at 1kHz nominal (factory pre-set for country), 30 Watts  Dimensions 440mm, 17.3 inches wide 105mm, 4.13 inches high (including feet) 375mm, 14.8 inches deep (including terminals)  Weight 13.15kg, 29lbs unit only, unboxed 15.2kg, 33.5lbs in shipping carton  Standard IEC type mains lead	Inputs	
Frequency response 10Hz to 20kHz ± 0.0dB  Signal / Noise 114dB "A"- weighted  Total harmonic distortion	Outputs	
Signal / Noise 114dB "A"- weighted  Total harmonic distortion < 0.0025% 10Hz to 20kHz  Total correlated jitter 135pS  Channel separation < 109dB 20Hz to 20kHz  Linearity < 0.2dB down to -100dB  Audio output at digital 0dB level 2.17 Volts RMS at 1kHz nominal 2.17 Volts RMS at 1kHz nominal 400 / 115 / 230 Volts AC 50 / 60Hz (factory pre-set for country), 30 Watts  Dimensions 440mm, 17.3 inches wide 105mm, 4.13 inches high (including feet) 375mm, 14.8 inches deep (including terminals)  Weight 13.15kg, 29lbs unit only, unboxed 15.2kg, 33.5lbs in shipping carton  Standard IEC type mains lead	Output impedence	50 Ohms
Total harmonic distortion < 0.0025% 10Hz to 20kHz  Total correlated jitter 135pS  Channel separation < 109dB 20Hz to 20kHz  Linearity < 0.2dB down to -100dB  Audio output at digital 0dB level 2.17 Volts RMS at 1kHz nominal 2.17 Volts RMS at 1kHz nominal 30 Volts AC 50 / 60Hz (factory pre-set for country), 30 Watts  Dimensions 440mm, 17.3 inches wide 105mm, 4.13 inches high (including feet) 375mm, 14.8 inches deep (including terminals)  Weight 13.15kg, 29lbs unit only, unboxed 15.2kg, 33.5lbs in shipping carton  Standard IEC type mains lead	Frequency response	10Hz to 20kHz ± 0.0dB
Total correlated jitter 135pS  Channel separation < 109dB 20Hz to 20kHz  Linearity < 0.2dB down to -100dB  Audio output at digital 0dB level 2.17 Volts RMS at 1kHz nominal 2.17 Volts RMS at 1kHz nominal 3.15 / 230 Volts AC 50 / 60Hz (factory pre-set for country), 30 Watts  Dimensions 440mm, 17.3 inches wide 105mm, 4.13 inches high (including feet) 375mm, 14.8 inches deep (including terminals)  Weight 13.15kg, 29lbs unit only, unboxed 15.2kg, 33.5lbs in shipping carton  Standard IEC type mains lead	Signal / Noise	114dB "A"- weighted
Channel separation < 109dB 20Hz to 20kHz  Linearity < 0.2dB down to -100dB  Audio output at digital 0dB level  Power Requirement 100 / 115 / 230 Volts AC 50 / 60Hz (factory pre-set for country), 30 Watts  Dimensions 440mm, 17.3 inches wide 105mm, 4.13 inches high (including feet) 375mm, 14.8 inches deep (including terminals)  Weight 13.15kg, 29lbs unit only, unboxed 15.2kg, 33.5lbs in shipping carton  Standard IEC type mains lead		< 0.0025% 10Hz to 20kHz
Linearity < 0.2dB down to -100dB  Audio output at digital 0dB level  Power Requirement 100 / 115 / 230 Volts AC 50 / 60Hz (factory pre-set for country), 30 Watts  Dimensions 440mm, 17.3 inches wide 105mm, 4.13 inches high (including feet) 375mm, 14.8 inches deep (including terminals)  Weight 13.15kg, 29lbs unit only, unboxed 15.2kg, 33.5lbs in shipping carton  Standard IEC type mains lead	Total correlated jitter	135pS
Audio output at digital 0dB level  Power Requirement 100 / 115 / 230 Volts AC 50 / 60Hz (factory pre-set for country), 30 Watts  Dimensions 440mm, 17.3 inches wide 105mm, 4.13 inches high (including feet) 375mm, 14.8 inches deep (including terminals)  Weight 13.15kg, 29lbs unit only, unboxed 15.2kg, 33.5lbs in shipping carton  Standard IEC type mains lead	Channel separation	< 109dB 20Hz to 20kHz
Power Requirement 100 / 115 / 230 Volts AC 50 / 60Hz (factory pre-set for country), 30 Watts  Dimensions 440mm, 17.3 inches wide 105mm, 4.13 inches high (including feet) 375mm, 14.8 inches deep (including terminals)  Weight 13.15kg, 29lbs unit only, unboxed 15.2kg, 33.5lbs in shipping carton  Standard IEC type mains lead	Linearity	< 0.2dB down to -100dB
(factory pre-set for country), 30 Watts  Dimensions 440mm, 17.3 inches wide 105mm, 4.13 inches high (including feet) 375mm, 14.8 inches deep (including terminals)  Weight 13.15kg, 29lbs unit only, unboxed 15.2kg, 33.5lbs in shipping carton  Standard IEC type mains lead		2.17 Volts RMS at 1kHz nominal
105mm, 4.13 inches high (including feet) 375mm, 14.8 inches deep (including terminals)  Weight 13.15kg, 29lbs unit only, unboxed 15.2kg, 33.5lbs in shipping carton  Standard IEC type mains lead	Power Requirement	
15.2kg, 33.5lbs in shipping carton  Standard IEC type mains lead	Dimensions	105mm, 4.13 inches high (including feet) 375mm, 14.8 inches deep (including
	Weight	
		IEC type mains lead