

OLDAKER TEST LEADS & ACCESSORIES

Call 888.295.9516

Fax 888.295.9517

STANDARD LENGTH ON THESE
LEADS IS 3 FOOT. OTHER LENGTHS
AVAILABLE UPON REQUEST.

**DUAL STACKABLE
TO DUAL STACKABLE**



CABLE DESCRIPTION >>> **RG/58** cable has a center conductor of (19 x 007) tinned copper stranding .195" O.D. Insulation, dielectric is 116P nom, Cap 29.5 PF/Ft. Maximum operating voltage 1900 - 50 ohms, temp. Rating -55c to +90c. Color black..
ZIP CORD 65/36 copper stranding, Heavy duty heater cord. Color black..

RG/174 cable has a center conductor of (7 x 34) tinned copper stranding .105" O.D. PVC Insulation, dielectric is 116P nom, Cap 30.0 PF/Ft. Maximum operating voltage 1500 - 50 ohms. Temp rating -100c to +300c. Color black..

PART NUMBERS

DUAL PLUGS TO
DUAL PLUGS

USING
RG/58 CABLE

506-1

DUAL PLUGS TO
DUAL PLUGS

USING
ZIP CORD

506

DUAL PLUGS TO
DUAL PLUGS

USING
RG/174 CABLE

506-13