

OLDAKER TEST LEADS & ACCESSORIES

Call 888.295.9516

Fax 888.295.9517


FerriShield, INC.
Interference Control Components

**RFI / EMI
SUPPRESSORS**




Part No.	A	B	C	D	IMPEDANCE IN OHMS
CS28B1937	1.182	0.78	1.188	0.425	117@100MHz

CABLE SNAP : Ferrite assembly in fully enclosed nylon case; This part fits .425" (10.8mm) diameter wires and cables. After closing around wire and clasping shut, assembly may be left hanging freely in position. May also be mounted with a flat-head screw through the .120" (3.0mm) diameter hole in the bottom by temporarily removing lower half. Other sizes available upon request.




Part No.	A	B	C	D	E	F	IMPEDANCE IN OHMS
SS28B2031	.700	1.255	.675	.230	.187	.768	200@100MHz

SLEEVE SNAP : Box-shaped ferrite assembly in enclosed nylon case fits .230" (5.8mm) diameter cable. Simply clamp around cable, plastic tabs at entry/exit ports apply pressure to cable surface to maintain mounting position. Options include foam adhesive pad on bottom. Other sizes available upon request.



Part No.	A	B	C	D	E	F	IMPEDANCE IN OHMS
SS28B2037	.790	1.450	.770	.350	.200	.885	154@100MHz
SS28B2032	1.155	1.450	1.125	.500	.200	1.230	230@100MHz

SLEEVE SNAP : Box-shaped ferrite assembly in enclosed nylon case fits .350" (8.8mm) & .500" (12.7mm) diameter cable. End ports are surrounded with flexible spring flutes to grip cable. Special mounting options include foam adhesive pad on bottom. Other sizes available upon request.



Part No.	A	B	C	D	COLOR	IMPEDANCE IN OHMS
IL28B0642G	.780	.780	.780	.316	GRAY	100@100MHz

INTERNAL LOCKING SNAP : This secure internal locking system cannot be reopened after snapping closed into position. Ensures that suppressor cannot be removed. Grip-lock tabs at entry/exit ports prevent longitudinal slippage. Fits .316" (8.0mm) cable. Color, computer gray. Other sizes & colors available upon request.