

OLDAKER TEST LEADS & ACCESSORIES

Call 888.295.9516

Fax 888.295.9517

STANDARD LENGTH ON THESE LEADS IS 3 FOOT, OTHER LENGTHS AVAILABLE UPON REQUEST.

MALE BNC TO MALE BNC



CABLE DESCRIPTION >>> **RG/58** cable has a center conductor of (19 x 007) tinned copper stranding .195" O.D. Insulation, dielectric is 116P nom, Cap 29.5 PF/Ft. Maximum operating voltage 1900 - 50 ohms, temp. Rating -55c to +90c. Color black
RG/59 cable has a center conductor of 22 ga. copper stranding .242" O.D. Insulation, dielectric is 146P nom, Cap 21 PF/Ft. Maximum operating voltage 2300 - 75 ohms, temp. Rating -40c to +80c. Color black
RG/174 cable has a center conductor of (7 x 34) tinned copper stranding .105" O.D. PVC Insulation, dielectric is 116P nom, Cap 30.0 PF/Ft. Maximum operating voltage 1500 - 50 ohms. Temp rating -100c to +300c. Color black..

PART NUMBERS

USING
RG/58 CABLE

541-2

USING
RG/59 CABLE

541-3

USING
RG/174 CABLE

541-4