MUSICAL FIDELITY

A3²⁴ DAC

Print This Page

OVERVIEW

FEATURES & BENEFITS

Exactly the same circuit as the Nu- Vista 3D, but without nuvistors	Truly incredible sound available from almost any CD player
Full multi-stage choke regulation	Extremely clean power supply lines and immunity from mains borne interference, which is particularly critical with CD players.
Upsampling at 96kHz and 192kHz	Allows optimisation of matching CD transport
	Will drive any combination of preamp and cable up to about 20 feet in length

SPECIFICATIONS

DAC architecture	24 bit Delta-Sigma (Bitstream) 8x oversampling, 96/192kHz switchable
Sampling frequencies	8 - 108kHz
Inputs	RCA 750hms TOSLINK optical

Outputs	RCA left and right analogue audio RCA digital loop out
Frequency response	10Hz - 22kHz ± 0.0dB
S/N ratio	>103dB unweighted >113dB 'A' weighted
THD	<0.005% 10Hz - 22kHz
Linearity	<0.1dB to -100dB
Power requirements	100/115/230V AC 50/60Hz (Factory preset)
Power consumption	10 Watts
Dimensions (mm)	440 x 90 x 375 (W x H x D) Height and width include feet. Depth includes terminals.
Weight	10kg (unboxed)
Standard accessories	IEC type mains lead.