

| Atmosphere Specifications | | | | | | | | | | | | |
|---------------------------|---|--------|------------------------------------|-------------------|----------------|----------------|-----------------------------|------------------------------------|-----------|------------------|-----------------|--------------------|
| | | Model | Description | Dimensions | Cut Out | Mounting Depth | Woofers | Tweeter | Power (W) | Impedance (Ohms) | Efficiency (dB) | Frequency Response |
| Single Point Stereo |  | SP-A6S | 6.5" DVC round single-point stereo | 9.75" | 8.375" | 3.875" | 6.5" injection molded cone | Dual 14mm neodymium PEI-dome | 60 | 8/8 | 92 | 55Hz-20kHz |
| In - Ceiling |  | SP-A5C | 5.25" round 2-way | 8.75" | 7.25" | 3.5" | 5.25" injection molded cone | 20mm neodymium mylar dome | 80 | 8 | 88 | 55Hz-20kHz |
| |  | SP-A6C | 6.5" round 2-way | 9.75" | 8.375" | 3.875" | 6.5" injection molded cone | 20mm neodymium mylar dome | 100 | 8 | 89 | 50Hz-20kHz |
| |  | SP-A8C | 8" round 2-way | 11.25" | 9.75" | 4" | 8" injection molded cone | 25mm neodymium mylar dome | 120 | 8 | 90 | 40Hz-20kHz |
| In - Wall |  | SP-A6W | 6.5" wall 2-way | 8.25" x 12.25" | 6.75" x 10.75" | 3.75" | 6.5" injection molded cone | 20mm pivoting neodymium mylar dome | 100 | 8 | 89 | 50Hz-20kHz |
| |  | SP-A8W | 8" wall 2-way | 10.625" x 16.375" | 9.25" x 15" | 3.875" | 8" injection molded cone | 25mm pivoting neodymium mylar dome | 120 | 8 | 90 | 40Hz-20kHz |