


BOX SPEAKERS



BS-1030B

BS-1030W

MUSIC/PAGING SPEAKERS

- Compact speaker for indoor/outdoor music and voice paging distribution
- Weather-resistant (IEC IP-X4 rating)
- Two-way, bass-reflex design
- 4.72" cone woofer and 1" dome tweeter
- Durable ABS resin UV-resistant paintable enclosure
- Frequency response: 80 Hz to 20 kHz
- Sensitivity: 90 dB SPL (1 W, 1 m)
- Continuous Power Handling: 90 W (8 ohms)
- Built-in multi-tap 70.7/100 V transformer (30 W max.) with direct 8 ohm mode
- Paintable steel mesh grille
- Available in black (BS-1030B) and white (BS-1030W)
- Horizontal or vertical mounting with rotatable logo badge
- Mounting bracket included
- Five year warranty



F-160G

F-160GM

F-160W

F-160WM

2-WAY SPEAKER

- Two-way, ported bass-reflex design
- 5.25" woofer and 1" dome tweeter
- Optimized for maximum efficiency with a flat frequency response when mounted in a half- or quarter-space environment
- Polypropylene enclosure available in white (F-160W, F-160WM models) or dark gray (F-160G, F-160GM)
- Frequency Response: 100 to 20k Hz
- Sensitivity: 91 dB SPL (1 W, 1 m)
- Continuous Power Handling: 150 W (8 ohms)
- Built-in multi-tap 70.7/100 V transformer (30 W max.) (F-160GM / F-160WM)
- Overload protection circuitry
- Horizontal or vertical mounting with rotatable logo badge
- Optional wall and ceiling-mount brackets
- Five year warranty



F-10B

F-10W

TRIANGULAR DESIGNER SPEAKER

- Sealed triangular enclosure mounts into corners
- 4" full-range cone speaker
- Acoustically damped cabinet
- Frequency Response: 100 to 18k Hz
- Sensitivity: 88 dB SPL (1 W, 1 m)
- Continuous Power Handling: 45 W (8 ohms)
- Optional multi-tap transformer, model TM-11 (10 W max.)
- Available in black (F-10B) or white (F-10W)
- Five year warranty



F-240G

F-240GM

F-240W

F-240WM

2-WAY SPEAKER

- Two-way, ported bass-reflex design
- Optimized for maximum efficiency with a flat frequency response when mounted in a half- or quarter-space environment
- Polypropylene enclosure available in white (F-240W, F-240WM models) or dark gray (F-240G, F-240GM)
- 6.5" woofer and 1" titanium dome tweeter
- Frequency Response: 65 to 20k Hz
- Sensitivity: 92 dB SPL (1 W, 1 m)
- Continuous Power Handling: 150 W (8 ohms)
- Built-in multi-tap 70.7/100 V transformer (30 W max.) (F-240GM / F-240WM)
- Overload protection circuitry
- Horizontal or vertical mounting with rotatable logo badge
- Optional wall and ceiling-mount brackets
- Five year warranty



F-505G

F-505W

TWO-WAY SPEAKER

- Two-way, ported bass-reflex design
- 8" woofer and HF compression driver
- Uniform directivity horn with controlled dispersion coverage pattern (60°H x 40°V)
- Frequency Response: 80 to 20k Hz
- Sensitivity: 93 dB SPL (1 W, 1 m)
- Continuous Power Handling: 240 W (8 ohms)
- Polypropylene enclosure in white (F-505W) or dark gray (F-505G)
- Built-in overload protection circuitry
- Input panel with push terminals and 1/4" phone jacks
- Optional mounting brackets
- Five year warranty



F-605G

F-605W

TWO-WAY SPEAKER

- Two-way, ported bass-reflex design
- 12" woofer and HF compression driver
- Uniform directivity horn with controlled dispersion coverage pattern (60°H x 40°V)
- Polypropylene enclosure available in white (F-605W) or dark gray (F-605G)
- Frequency Response: 80 to 20k Hz
- Sensitivity: 98 dB SPL (1 W, 1 m)
- Continuous Power Handling: 360 W (8 ohms)
- Overload protection circuitry
- Input panel with push terminals and 1/4" phone jacks
- Optional mounting brackets
- Five year warranty

