



MID LINE ARRAY SPEAKERS - NEW!

SR-A12L

SR-A12S

MID-SIZE LINE ARRAY SPEAKERS

- Designed for wide bandwidth response
- Compact and powerful 2-way modular speaker units used in multiple configurations as required to deliver greater output power with a more extended frequency response
- High-performance driver units
- Each Type A Series speaker module contains a 30cm (12") low frequency unit and a high-frequency horn attached to two compression drivers for greater output
- Wavefront control throat function to obtain the best possible performance from the high frequency drivers
- Two speaker configurations designed for specific sound coverage, each having a different taper
- 5-degree taper for effectively transmitting sound over distance
- 15-degree taper optimized for excellent short range coverage
- Simple maintenance and servicing for permanent installations
- All driver replacement is possible from the speaker's rear, a simple and speedy procedure
- SR-A12L Long-throw enclosure (15°V x 90°H)
- SR-A12S Short-throw enclosure (5°V x 90°H)
- Dual compression drivers and 12" low frequency driver
- Power handling: 450 W (LF), 180 W (HF)
- Weather-resistant versions available
- Optional mounting hardware
- Five year warranty



SR-A18B

SUBWOOFER

- Designed for use in conjunction with SR-A Series mid-size line array speakers
- Heavy-duty 18" low frequency
- Continuous power handling: 720 W
- Five year warranty



OPTIONAL SR-A SERIES MOUNTING OPTIONS

SR-RF12 Rigging Frame



SR-TP12 Tilt Joint Plate



SLIM LINE ARRAY SPEAKERS - NEW!

SR-S4L

SR-S4S

SLIM-SIZE LINE ARRAY SPEAKERS

- Slim compact design ideal for speech applications
- Low visual profile fits into demanding settings
- Highly controlled coverage yields improved intelligibility
- Multiple drivers (8 LF, 24 HF) for high sensitivity and power handling
- In-line driver arrangement for superior vertical coverage control
- All drivers share the same horizontal axis for best horizontal dispersion
- Horizontal coverage remains broad through speech range - 100 deg.
- High power handling: 600 W cont. (200 W, 24 hr. pink noise)
- SR-S4L Long-throw (0°V x 90°H)
- SR-S4S Short-throw (10°V x 90°H)
- (8) 4" cone drivers and (24) 1" balanced dome tweeters
- Full-range with built-in crossover or biamp
- Power handling: 600 W cont.
- High sensitivity: up to 99 dB, 1 watt @ 1 meter (500 to 5,000 Hz)
- Weather-resistant versions available
- Optional mounting hardware and 70.7 V transformer
- Five year warranty



OPTIONAL SR-S SERIES MOUNTING OPTIONS

SR-EP4 Extension Plate



SR-FS4 Floor Stand



SR-FB4 Rigging Bar



SR-SA4 Stand Adapter



SR-TB4 Wall Tilt Bracket



SR-WB4 Wall Mount Bracket



SR-PP4 Rubber Protector

