



CM CATV CL2  
E197429  
E222991  
E222992



Style 1354  
80° C 300V  
E195812



## Series-6 Coaxial Drop Cable

High-Grade RG6/U UL-Rated Coaxial Cable  
Suitable for Digital HDTV Applications, CATV and  
Digital Satellite Installations  
Fully Sweep-Tested to 2250MHz  
AWG18 Solid Copper Center  
Aluminum-Polypropylene Foil Shield with  
Overlap Bonded to Dielectric Insulator  
60% Tinned-Copper or Aluminum Braid Shield  
Flame Retardant Lead-Free PVC Jacket  
Foot-Marked PVC Jacket  
Inhibitor additive protects cable from UV damage  
0.180" (4.57mm) nom. OD Gas-Foamed Dielectric  
0.275" (7.00mm) nom. OD PVC Jacket  
Nominal Impedance 75 ±3 Ω  
Nominal Capacitance 16.2pF/ft  
Velocity of Propagation 82%  
Nom. Atten. -6.30dB@1GHz, -9.8dB@2250MHz  
Struct. Return Loss (SRL) 20dB min@5-2250MHz  
UL Listed CM, CATV, CL2 E197429  
Supplied in Wooden Spools or Pull-Out Boxes



- 200-932BK** RG6/U UL Black – Reel
- 200-932GY** RG6/U UL Grey – Reel
- 200-932IV** RG6/U UL Ivory – Reel
- 200-932WH** RG6/U UL White – Reel
- 200-933BK** RG6/U UL Black – Pull Box
- 200-933GY** RG6/U UL Grey – Pull Box
- 200-933IV** RG6/U UL Ivory – Pull Box
- 200-933WH** RG6/U UL White – Pull Box



- 200-934BK** RG6/U UL Messenger/Ground Black – Reel
- 200-934WH** RG6/U UL Messenger/Ground White – Reel
- 200-935BK** RG6/U UL Messenger/Ground Black – Reel
- 200-935WH** RG6/U UL Messenger/Ground White – Reel



- 200-936BK** RG6/U Quad UL Black – Reel
- 200-936WH** RG6/U Quad UL White – Reel



- 200-938BK** RG6/U-Dual UL Black – Reel
- 200-938WH** RG6/U-Dual UL White – Reel



- 200-939BK** RG6/U-Dual UL Messenger/Ground Black – Reel
- 200-939WH** RG6/U-Dual UL Messenger/Ground White – Reel

- 200-932BK** 1000' RG6 UL Black – Reel
- 200-932GY** 1000' RG6 UL Grey – Reel
- 200-932IV** 1000' RG6 UL Ivory – Reel
- 200-932WH** 1000' RG6 UL White – Reel
- 200-933BK** 1000' RG6 UL Black – Pull-Box
- 200-933GY** 1000' RG6 UL Grey – Pull-Box
- 200-933IV** 1000' RG6 UL Ivory – Pull-Box
- 200-933WH** 1000' RG6 UL White – Pull-Box
- 200-934BK** 1000' RG6 UL Black – Reel  
AWG17 Copper-Steel  
Messenger/Ground
- 200-934WH** 1000' RG6 UL White – Reel  
AWG17 Copper-Steel  
Messenger/Ground
- 200-935BK** 1000' RG6 UL Black – Reel  
AWG17 Copper-Steel  
Messenger/Ground
- 200-935WH** 1000' RG6 UL White – Reel  
AWG17 Copper-Steel  
Messenger/Ground
- 200-936BK** 1000' RG6-Quad UL Black – Reel  
60% + 40% Braid Coverage
- 200-936WH** 1000' RG6-Quad UL White – Reel  
60% + 40% Braid Coverage
- 200-938BK** 1000' RG6-Dual UL Black – Reel
- 200-938WH** 1000' RG6-Dual UL White – Reel
- 200-939BK** 500' RG6-Dual UL Black – Reel  
AWG17 Copper-Steel  
Messenger/Ground
- 200-939WH** 500' RG6-Dual UL White – Reel  
AWG17 Copper-Steel  
Messenger/Ground

