











Ordering Instructions: Complete the form by filling in each block with the appropriate bold letter or number that corresponds to the choice in each menu item. The product must have a combination of 13 letters/numbers. Example: FNPB52A002M2M

Fiber Optic Node Pigtail Cable

F | **NP** | **I**
 Fill out remaining spaces >>>>

Fiber	Type	Fiber Count	Singlemode Multimode	Connector	Polish	Cable Total Length	Meters, Feet or Inches	Cable Furcation (Breakout) Length	Meters, Feet or Inches
F Fiber	NP Node Pigtail	A 2-Ct. OFNR Node Cable B 2-Ct. OFNP Node Cable C 4-Ct. OFNR Node Cable D 4-Ct. OFNP Node Cable E 6-Ct. OFNR Node Cable F 6-Ct. OFNP Node Cable G 8-Ct. OFNR Node Cable H 8-Ct. OFNP Node Cable I 10-Ct. OFNR Node Cable J 10-Ct. OFNP Node Cable K 12-Ct. OFNR Node Cable L 12-Ct. OFNP Node Cable M 2-Ct. Armored OSP Node Cable N 4-Ct. Armored OSP Node Cable O 6-Ct. Armored OSP Node Cable P 8-Ct. Armored OSP Node Cable Q 10-Ct. Armored OSP Node Cable R 12-Ct. Armored OSP Node Cable S 2-Ct. Tight Buffer OSP Node Cable T 4-Ct. Tight Buffer OSP Node Cable U 6-Ct. Tight Buffer OSP Node Cable V 8-Ct. Tight Buffer OSP Node Cable W 10-Ct. Tight Buffer OSP Node Cable Y 12-Ct. Tight Buffer OSP Node Cable	5 Singlemode 9/125 7 Multimode 50/125 8 Multimode 62.5/125	1 ST  2 SC  3 FC  4 MTRJ  5 LC  6 MU  7 E2000  8 DIN  9 MPO  0 D4 	A APC (Angle) P PC U UPC (Ultra) M Male (MT), for MTRJ connector only F Female (MT), for MTRJ connector only	001 1 002 2 003 3 <i>through</i> 999 999	M Meters F Feet I Inches	1 1 2 2 3 3 4 4 5 5 6 6 7 7 8 8 9 9 0 10	M Meters F Feet I Inches

Specifications

- Node Pigtail Cable Based on Customer Options
- High-Performance Fiber Cable for Use in Fiber Optic Nodes
- Choose by fiber count, mode, type of connector, polish, cable length and cable furcation length
- Precision Manufactured
- Flame Retardant PVC Jacket
- 100% Factory Tested and Certified
- Excellent Insertion and Return Loss Characteristics
- Compliant with TIA/EIA-568B.3

