

ComPoint accessories

ISSP

Now!



ComPoint Speaker

The ComPoint Speaker is a Decora®-style in-wall speaker for use with the ComPoint intercom system. It installs beside a ComPoint keypad in a double-gang wall box. The ISSP allows ComPoint to be used as a stand-alone system. The high-quality driver in the ISSP is ideally matched to the keypad amplifier. Its moisture-resistant design makes it suitable for use in bathrooms and kitchens. 4w max. **Wall plate not included.**
3" W x 5.125" H x 3" D (7.6 x 13.0 x 7.6 cm)

Order #

2300-526374

Shipping Weight
8 oz (227g)
Min. Advertised Price
\$40⁰⁰

ISDR1

Now!



ComPoint Door Strike Release Module

Surface-mount module connects between the hub and a door station to provide relay contacts for a third-party door strike release or other device. 110 punch-down connector for CAT-5 cable. Screw terminals for access to common, NC and NO relay contacts. Relay rated for 1 A @ 12 VDC.
3" W x 1.875" H x 1" D (7.6 x 4.8 x 2.5 cm)

Order #

2300-525445

Shipping Weight
4.8 oz (136kg)
Min. Advertised Price
\$90⁰⁰

ISPS

Now!



ComPoint Power Supply

15VDC 3.5A. Autosensing 100V-240VAC, detachable power cord, compact size.
4.56" W x 1.93" H x 1.33" D (115.8 x 49 x 33.8 mm)

Order #

2300-526282

Shipping Weight
1 lbs. (.5kg)
Min. Advertised Price
\$70⁰⁰

Advanced Programming Cable



Advanced programming cable for UNO-S1, KP4, KP6, KPL keypads, ComPoint components (ISK1, ISK2, ISK3, ISH1), and iBridge Dock. Female DB-9 connection (PC end) and flat device pin connection (device end). 72" L (182.9 cm)

Order #

2500-521065

Shipping Weight
1 lbs.(0.45 kg)