

## R-Series Amplifiers

### R235LS



The Russound R235LS is a two-channel power amplifier with automatic local source switching capability that enables localized speaker override for a connected peripheral, such as a TV or PC. The Bridgeable power setting combines channel power for 100 watts into a single 8-ohm load, rated. 35 watts per channel RMS @ 8 Ohms.  
8.625" W x 10"D x 2.375"H (22 x 25.4 x 6 cm)




#### Order #

2800-521874

Shipping Weight  
**9.5 lbs (3.8kg)**  
Min. Advertised Price  
**\$299.00**

## Amplifiers Accessories

### LFP-1.2



Low Frequency Protection Module. Protects amplifiers from sub-sonic frequencies. Color-coded detachable 14-gauge snap connectors  
3.75" W x 1.5" H x 2.5" D (9.6 x 3.81 x 6.4 cm)

#### Order #

9500-520938

Shipping Weight  
**6oz (.2kg)**  
Min. Advertised Price  
**\$69.00**

### AW164CL3



4 conductor, 16 gauge speaker cable, unshielded, 26/30 strands bare copper, .024 nominal PVC jacket, temp. rating 75° C, UL Type CL3, YELLOW JACKET. 500 foot pull-box only.

#### Order #

9000-460067

Call  
for  
Pricing

### AW162CL3



2 conductor, 16 gauge speaker cable, unshielded, 26/30 strands bare copper, .024 nominal PVC jacket, temp. rating 75° C, UL type CL3, LIGHT BLUE JACKET. 1000 foot pull-box only.

#### Order #

9000-119316

Call  
for  
Pricing

### AW164C5



4 pair twisted, 24 gauge, CAT-5E cable, solid copper, PVC jacket, telephone/data grade/ISDN. Zipcord with 4 conductor, 16 gauge speaker cable. 500 foot spool. PINK jacket.

#### Order #

9000-121838

Call  
for  
Pricing