



INTERIOR DESIGN SPEAKERS

H Series

H-1

INTERIOR DESIGN SPEAKERS

- Sleek, stylish appearance blends well with modern architecture for background/foreground music and paging systems
- Wide variety of applications including houses of worship, hotels, museums, offices, restaurants, retail stores and residential spaces
- Minimum reflection design reduces sound wave reflections typical of conventional bracket-mounted "box" type speakers
- Loudspeaker components rotate internally to allow flexible aiming
- Two-way, sealed enclosure
- 3" x 2" cone woofer with neodymium magnet and 1" balanced-dome tweeter, ferrofluid-cooled
- Built-in passive crossover with optimized filter slopes
- Frequency Response: 120 to 20k Hz
- Coverage Angle: 120° H x 100° V
- Sensitivity: 85 dB SPL (1 W, 1 m)
- Continuous Power Handling: 90 W (4 ohms)
- Built-in 70.7/100 V multi-tap transformer (12 W max.) with 4 and 16 ohm modes
- Overload protection circuitry
- Paintable grille
- Removable terminal block with loop-through terminations
- Mounting hardware included
- Optional equalization with 900 Series module, model E-04R (DSP parameters also available)
- Five year warranty



H-2

H-2WP

INTERIOR DESIGN SPEAKERS

- Sleek, stylish appearance blends well with modern architecture for background and foreground music and paging systems
- Wide variety of applications including houses of worship, hotels, museums, offices, restaurants, retail stores and residential spaces
- Weather-proof version available, model H-2WP
- Minimum reflection design reduces sound wave reflections typical of conventional bracket-mounted "box" type speakers
- Loudspeaker components rotate internally to allow flexible aiming
- Two-way, sealed enclosure
- 4" cone woofer with neodymium magnet and 1" balanced-dome tweeter, ferrofluid-cooled
- Built-in passive crossover with optimized filter slopes
- Frequency Response: 100 to 20k Hz
- Coverage Angle: 100° H x 60° V
- Sensitivity: 88 dB SPL (1 W, 1 m)
- Continuous Power Handling: 120 W (4 ohms)
- Built-in 70.7/100 V multi-tap transformer (12 W max.) with 4 and 16 ohm modes
- Overload protection circuitry
- Paintable grille
- Removable terminal block with loop-through terminations
- Mounting hardware included
- Optional system equalization with 900 Series module, model E-05R (DSP parameters also available)
- Five year warranty



H-3

H-3WP

WIDE-DISPERSION WALL-MOUNT SPEAKER

- Special appearance blends well with modern architecture for background/foreground music and paging systems
- Wide variety of applications including hotels, houses of worship, museums, offices, residential spaces, restaurants, and retail stores
- Wide coverage area: 140° horizontal dispersion
- Weather-resistant version available, model H-3WP
- Minimum reflection design reduces sound wave reflections typical of conventional bracket-mounted "box" type speaker
- Two-way, sealed enclosure
- Dual 4" woofers with neodymium magnets and 1" dome tweeter
- Built-in crossover with optimized filter slopes
- Frequency Response: 100 to 20k Hz
- Coverage Angle: 140° H x 70° V
- Sensitivity: 89 dB SPL (1 W, 1 m)
- Continuous Power Handling: 150 W (8 ohms)
- Built-in 70.7/100 V multi-tap transformer (30 W max.) with 8 and 16 ohm modes
- Overload protection circuitry
- Paintable grille
- Removable terminal block with loop-through terminations
- Mounting hardware included
- Optional equalization with 900 Series module, model E-06R (DSP parameters also available)
- Five year warranty

