



WEATHER-RESISTANT SPEAKERS

F-505WP

F-505WP-L

WEATHER-RESISTANT TWO-WAY SPEAKER

- Weather-resistant construction for outdoor or humid indoor applications
- Two-way, ported bass-reflex design
- 8" woofer and HF compression driver
- Uniform directivity horn with controlled dispersion coverage pattern (60°H x 40°V)
- Durable polypropylene enclosure
- Frequency Response: 80 to 20k Hz
- Sensitivity: 93 dB SPL (1 W, 1 m)
- Continuous Power Handling: 240 W (8 ohms - F-505WP-L)
- Built-in multi-tap 70.7/100 V transformer (60 W max.) (F-505WP)
- Overload protection circuitry
- Optional wall and ceiling-mount brackets
- Five year warranty



F-605WP

F-605WP-L

WEATHER-RESISTANT TWO-WAY SPEAKER

- Weather-resistant construction for outdoor or humid indoor applications
- Two-way, ported bass-reflex design
- 12" woofer and HF compression driver
- Uniform directivity horn with controlled dispersion coverage pattern (60°H x 40°V)
- Durable polypropylene enclosure
- Frequency Response: 80 to 20k Hz
- Sensitivity: 98 dB SPL (1 W, 1 m)
- Continuous Power Handling: 360 W (8 ohms - F-605WP-L)
- Built-in multi-tap 70.7/100 V transformer (120 W max.) (F-605WP)
- Overload protection circuitry
- Optional wall and ceiling-mount brackets
- Five year warranty



BS-20W

WEATHER-RESISTANT TWO-WAY SPEAKER

- Two-way sealed enclosure
- 5.2" treated cone woofer and CD horn (90°H x 30°V) with piezo driver
- Frequency Response: 100 to 20k Hz
- Sensitivity: 94 dB SPL (1 W, 1 m)
- Built-in 70.7/100 V transformer (20 W max.)
- Mounting bracket included
- Five year warranty



F-160WP

WEATHER-RESISTANT TWO-WAY SPEAKER

- Weather-resistant construction for outdoor or humid indoor applications
- Two-way, ported bass-reflex design
- 5.25" woofer and 1" dome tweeter
- Optimized for maximum efficiency with a flat frequency response when mounted in a half- or quarter-space environment
- Polypropylene dark gray enclosure
- Frequency Response: 100 to 20k Hz
- Sensitivity: 91 dB SPL (1 W, 1 m)
- Built-in multi-tap 70.7/100 V transformer (30 W max.)
- Optional mounting bracket
- Five year warranty



PORTABLE SOUND SYSTEMS

SL-122

TWO-WAY STAGE SPEAKER

- Compact and lightweight
- 12" woofer and CD horn (90°H x 40°V) with piezo driver
- Frequency Response: 70 to 20k Hz
- Sensitivity: 95 dB SPL (1 W, 1 m)
- Continuous Power Handling: 240 W (8 ohms)
- Two paralleled 1/4" phone jacks
- Rugged stackable enclosure with durable textured vinyl coating and protective steel mesh grille
- Convenient carrying handle
- Built-in stand-mounting adapter (1 3/8" diameter)
- Five year warranty



SL-122M

TWO-WAY FLOOR MONITOR

- Compact and lightweight
- 12" woofer and CD horn (90°H x 40°V) with piezo driver
- Frequency Response: 70 to 20k Hz
- Sensitivity: 95 dB SPL (1 W, 1 m)
- Continuous Power Handling: 240 W (8 ohms)
- Two paralleled 1/4" phone jacks
- Rugged enclosure with durable textured vinyl coating and protective steel mesh grille
- Convenient carrying handle
- Five year warranty



SL-152

TWO-WAY STAGE SPEAKER

- Compact and lightweight
- 15" woofer and CD horn (90°H x 40°V) with piezo driver
- Frequency Response: 70 to 20k Hz
- Sensitivity: 98 dB SPL (1 W, 1 m)
- Continuous Power Handling: 240 W (8 ohms)
- Two paralleled 1/4" phone jacks
- Rugged stackable enclosure with durable textured vinyl coating and protective steel mesh grille
- Convenient carrying handle
- Built-in stand-mounting adapter (1 3/8" diameter)
- Five year warranty



SL-152M

TWO-WAY FLOOR MONITOR

- Compact and lightweight
- 15" woofer and CD horn (90°H x 40°V) with piezo driver
- Frequency Response: 70 to 20k Hz
- Sensitivity: 98 dB SPL (1 W, 1 m)
- Continuous Power Handling: 240 W (8 ohms)
- Two paralleled 1/4" phone jacks
- Rugged enclosure with durable textured vinyl coating and protective steel mesh grille
- Convenient carrying handle
- Five year warranty

