

Below Ground Tanks



300 Gallon Sphere



500 Gallon Sphere

Our 300 and 500 gallon spheres are designed to be used as a holding tank or pump tank. Unlike our ribbed septic tanks, these tanks may remain in the ground when empty. These tanks are furnished with manhole covers and include a molded-in elevated pump stand on the bottom of the tank.

Below Ground Spherical Pump Tanks

Gallon Capacity	Diameter	Height	Height To Inlet	Height To Outlet	Manhole Diameter	Part No.
300 Sphere	54"	51"	44"	42"	1-20"	41319
500 Sphere	64"	64"	56"	53"	1-20"	40785

Below Ground Cistern Tanks

Our below-ground cisterns feature the same rugged, ribbed design found in our septic tanks and are lightweight for ease of transport and installation.

Gallon Capacity	Length	Width	Height	Manhole Diameter	Part No.
325 Cistern	—	54" Dia.	51"	1-20"	41321
550 Cistern	—	64" Dia.	64"	1-20"	40856
600 Cistern	101"	51"	42"	1-20"	41328
1200 Cistern	102"	60"	58"	2-20"	41329
1400 Cistern	116"	55"	66"	2-20"	41893
1700 Cistern	133"	55"	66"	2-20"	41330



325 Gallon Cistern



550 Gallon Cistern



600 Gallon Cistern



1200 Gallon Cistern



1700 Gallon Cistern

Polyethylene water storage tanks are ideal for instances when drinking water must be hauled in or if a well does not meet consumption needs. NORWESCO tanks are manufactured using resins that meet FDA specifications to ensure safe storage of potable water. Where applicable, NORWESCO's **water storage tanks and below ground cisterns** have been certified under ANSI/NSF™ Standard 61. The 325 and 550 gallon spheres may remain in the ground when empty. These tanks include a molded-in elevated pump stand on the bottom of the tank. The ribbed tanks (600 gallon and larger) need to be kept ¼ full at all times.

Above Ground Tanks



Vertical

Our selection of **above-ground vertical tanks** feature tie down slots, built-in graduated gallonage indicators, offset fill-well and self-vented, sash-proof lids. An installed bulkhead fitting is standard on the above-ground vertical tank. Fittings are available in a full range of sizes to help adapt the tank to suit specific applications. Please refer to page 5 for accessory items.

Vertical Tanks

Gallon Capacity	Diameter	Height	Outlet/Drain Specification	Fill Opening	Part No.
25 Vertical	18"	29"	¾"	5"	41867
50 Vertical	18"	53"	¾"	5"	41865
65 Vertical	23"	42"	1¼"	8"	45192
75 Vertical	23"	50"	1¼"	8"	41863
100 Vertical	28"	43"	1¼"	8"	41861
105 Vertical	23"	63"	2"	8"	40803
150 Vertical	30"	56"	1¼"	8"	41859
165 Vertical	31"	55"	2"	16"	40281
200 Vertical	30"	72"	2"	8"	41856
210 Vertical	32"	69"	2"	16"	47401
250 Vertical	30"	89"	2"	8"	41854
300 Vertical	36"	78"	2"	16"	40213
500 Vertical	48"	72"	2"	16"	40148
550 Vertical	67"	42"	2"	16"	40023
1000 Vertical	64"	79"	2"	16"	40152
1100 Vertical	87"	51"	2"	16"	40070
1350 Vertical**	71"	87"	2"	16"	40861
1550 Vertical	87"	65"	2"	16"	40235
2100 Vertical**	87"	87"	2"	16"	40178
2500 Vertical	95"	89"	2"	16"	40051
3000 Vertical	95"	107"	2"	16"	40754
5000 Vertical	102"	152"	3"/2"	16"	40164
6100 Vertical**	120"	139"	3"/2"	16"	40659
6500 Vertical**	120"	150"	3"/2"	16"	40224

** Limited availability. For availability details please visit our website at www.norwesco.com.

Above Ground Tanks (continued)

Horizontal Tanks

Gallon Capacity	Diameter	Length	Outlet/Drain Specification	Fill Opening	Part No.	Band Part No.
35 Horizontal	20"	29"	¾"	5"	45223	60520
55 Horizontal	23"	33"	¾"	5"	41873	61745
65 Horizontal	23"	43"	¾"	5"	45191	61745
125 Horizontal	32"	41"	2"	8"	40298	61744
225 Horizontal	38"	49"	2"	8"	40299	60478
325 Horizontal	38"	68"	2"	16"	40217	60478
525 Horizontal	49"	71"	2"	16"	40181	60057

Bands are optional, 2 per tank.

Pickup Tanks

Gallon Capacity	Top Width or Diameter	Bottom Width or Diameter	Overall Height	Outlet/Drain Specification	Fill Opening	Part No.
210 Pickup	60"/51"	48"/39"	28"	2"	8"	40300
325 Pickup	62"	49"	32"	2"	8"	40160
425 Pickup	65"	49"	37"	2"	8"	40102

Mini Bulk Tanks

Gallon Capacity	Diameter	Height	Outlet/Drain Specification	Fill Opening	Part No.
120 Mini Bulk	38"	29"	2"	5"	40318
220 Mini Bulk	42"	42"	2"	5"	40320

PCO Tanks

Gallon Capacity	Length	Width	Height	Outlet/Drain Specification	Fill Opening	Part No.
30 PCO	25"	19"	22"	—	5"	41254
50 PCO	38"	19"	20"	—	8"	40664
100 PCO	38"	30"	26"	—	8"	40668
150 PCO	48"	36"	26"	—	8"	40669
200 PCO	48"	36"	35"	—	8"	41413
300 PCO	69"	36"	37"	—	16"	41381

Specialty Water Tanks

Gallon Capacity	Length	Width	Height	Drain Specification	Fill Opening	Part No.
375 with Steel Frame**	62"	30"	60"	1¼"	16"	40480
300 Freestanding**	62"	29"	49"	1¼"	16"	41869
400 Freestanding**	62"	29"	65"	1¼"	16"	41247

** Limited availability. For availability details, please visit our website at www.norwesco.com.

Water Hauling Tanks (ABOVE GROUND USE ONLY)

Gallon Capacity	Length	Width	Height	Drain Specification	Fill Opening	Part No.
1250**	132"	80"	35"	2"	16"	40756
1500**	130"	81"	41"	2"	16"	41392

** Limited availability. For availability details, please visit our website at www.norwesco.com.

Elliptical Leg Tank

Gallon Capacity	Length	Width	Height	Drain Specification	Fill Opening	Part No.
3135**	151"	88"	76"	3"/2"	16"	40686

This tank requires full length support as well as 4 support bands. Band part number is 62097.

** Limited availability. For availability details, please visit our website at www.norwesco.com.



325 Gallon Horizontal



210 Gallon Pickup



Mini Bulk



PCO



375 Gallon with Frame

400 Gallon Freestanding



Water Hauling



Elliptical Leg