

# Image Kiosk™ 8560/8570

## Price Checker and Interactive Mini-Kiosk



### Overview

The Image Kiosk 8560 and 8570 are designed to give customers instant self-access to information they need. Offering a range of functionality including price checking, item information look-up, and loyalty program administration, Image Kiosks give you the ability to assist and communicate with your customers effectively and efficiently – all without requiring them to seek out an employee. In addition, the IK8570's capabilities can be leveraged to provide automated check-in and access control to secure areas.

Designed for ease of use, the Image Kiosk combines omnidirectional barcode scanning, an illuminated cone that highlights the scanning area and simple finger-touch navigation, ensuring intuitive operation even for first-time users – a key factor for the success of any self-service solution.

An industry-standard operating system, centralized remote management capabilities, an integrated suite of programming and application development tools, and the option of wireless connectivity simplify integration and maintenance – reducing your total cost of ownership.

Offering the power and performance of larger, more expensive kiosks, the Image Kiosk takes up less space and comes packed with more standard features than other devices in its class, delivering a full suite of kiosk capabilities in a small and extremely user-friendly package.

### Premium Features

- **Compact Design:** Small size reduces the amount of valuable space required for mounting.
- **Easy & Intuitive Barcode Scanning:** Reads barcodes omnidirectionally, delivering easy scanning regardless of how an item is presented.
- **Industry-Standard Platform:** Microsoft® Windows® CE 5.0 operating system provides a familiar interface for programmers, streamlining application development and deployment.
- **Powerful Integrated Software Tools:** Comprehensive suite of easy to use software tools and utilities enable simplified device configuration and application development.
- **Easy Peripheral Connectivity for Extended Capability:** USB port functionality enables adding peripherals, allowing you to expand the functionality of your Image Kiosk.
- **Built Right for Unattended Use:** Rugged solid-state design and a patented screen protector to guard against display damage provide maximum reliability and up-time – reducing total cost of ownership.
- **Integrated Magnetic Stripe Reader (IK8570 only):** Reads MSR Tracks 1, 2, and 3, enabling applications such as customer loyalty card administration and gift card balance retrieval.
- **Customer-Safe Scanning Technology:** Image scanning technology is completely safe to look into, eliminating the need for “laser warning” labels and erasing any concern over litigation from injury.

### Industry Standard Features

- **High-Performance Processor:** Intel® XScale® processor delivers faster performance across all applications, getting customers quick access to the information they need.
- **Versatile Connectivity:** Wireless LAN or Ethernet connectivity enables communication and deployment flexibility.
- **Large Color Display:** Vibrant color LCD is ideal for touchscreen applications and gives impact to the messages you want your customer to notice.

# Image Kiosk™ 8560/8570 Specifications

## System Architecture

<b>Processor:</b>	Intel XScale PXA255 200 Mhz
<b>Operating Platform:</b>	Microsoft Windows CE 5.0
<b>Memory:</b>	IK8560 Models: 32MB Flash ROM X 64MB SDRAM of on-board memory IK8570 Models: 64MB Flash ROM X 64MB SDRAM of on-board memory
<b>Development Environment:</b>	Image Kiosk .NET SDK for Visual Studio 2005. Setup supports C++, C#.NET, and VB.net development Image Kiosk SDK for eMbedded Visual C++. Setup supports C/C++ development
<b>Third Party Software:</b>	SOTI MobiControl (remote device management), PowerNet™ Terminal Emulation (TNVT, 3270, 5250), and ITScriptNet™
<b>Graphics Supported:</b>	BMP, CGM, DIB, EPS, MF, PCL, PCX, PLS, JPG, and TIF



## Data Inputs

<b>Imager/Scanner:</b>	5100 Standard Range (SR) with LED aimer decodes from 2.1 in. to 13.2 in. (5.3cm to 33.5cm) for 30 mil UPC
<b>Symbologies Supported:</b>	Codabar, Code 3 of 9, Code 11, Code 32 Pharmaceutical (PARAF), Code 93, Code 128, EAN with Add-On and EAN with Extended Coupon Code, EAN-13, Interleaved 2 or 5, Matrix 2 of 5, Plessey, PosiCode, GS1 DataBar, Straight 2 of 5 IATA, Straight 2 of 5 Industrial, Telepen, Trioptic Code, UCC/EAN-128, UPC and UPC-A, Aztec, Code 16K, Composite, Data Matrix, MaxiCode, OCR, PDF417, & QR Code
<b>Magnetic Stripe Reader:</b>	Track 1, 2, 3 (IK8570 only)

## Data Outputs

<b>Display Window:</b>	Resistive, transparent, pressure-sensitive touch screen
<b>LCD Size:</b>	5.7 in. (14.5 cm) 1/4 VGA
<b>LCD Active Area:</b>	4.45 x 3.3 in. (11.3 x 8.4 cm) (Active area)
<b>LCD Resolution:</b>	320 x 240 dot, 16 bit color
<b>Touch Pad Resolution:</b>	903 x 1238 ppi

## Communications

<b>RS-232:</b>	4800 to 115.2 Kbps
<b>RS-232 Pass-Through:</b>	Using Aux. Y cable with AC power adapter
<b>PC USB:</b>	AC power adapter required
<b>USB Hub Host:</b>	5V DC power pass-through, support for USB 1.1 for up to 10 devices
<b>Ethernet 100Base-TX/ 10Base-T:</b>	(IK8560EE, IK8570E, & IK8570EUE models) Cable not supplied
<b>WLAN:</b>	(IK8560CE, IK8560CEUE, IK8570E, & IK8570EUE models) IEEE 802.11b, DSSS Authentication Methodologies: Open communication, WEP (40 & 128 bit), WPA (PSK, TTLS PAP), LEAP, PEAP
<b>Beeper:</b>	Programmable

## Physical


<b>Dimensions:</b>	8.7"L x 7.3"W x 3.2"D (22.1 x 18.5 x 8.1 cm)
<b>Weight:</b>	2 lb. (.9 kg)
<b>Operating Temperature:</b>	0° to 40°C (32° to 104°F)
<b>Storage Temperature:</b>	0° to 40°C (32° to 104°F)

## Power Requirements

<b>Current Draw:</b>	IK8560EE: 860 mA @ 12VDC IK8560CE & IK8560CEUE: 800 mA @ 12VDC IK8570E & IK8570EUE: 870 mA @ 12VDC
<b>Source:</b>	120V (NA) or 230V (EU) AC adapter or powered host terminal port

## Approvals

<b>FCC-CE Radio Country:</b>	US/Canada, R&TTE, NOM
------------------------------	-----------------------

 Complies with EMC 89/336/EEC *Microsoft Windows CE is a registered trademark or trademarks of Microsoft Corporation in the United States and/or other countries.*

## Worldwide Offices

### NORTH AMERICA

Skaneateles Falls, NY  
Tel: +1 315 685 8945  
or, in North America:  
+1 800 582 4263  
napresales@handheld.com  
  
Carolinas  
Tel: +1 803 835 8000  
or, in North America:  
+1 800 582 4263  
napresales@handheld.com

### ASIA AND THE PACIFIC RIM

Hong Kong  
Tel: +852 2511 3050  
appresales@handheld.com  
  
Japan  
Tel: +813 5770 6312  
appresales@handheld.com  
  
Shanghai  
Tel: +86 21 6361 3818  
appresales@handheld.com  
  
Malaysia  
Tel: +603-6201 9020  
appresales@handheld.com

### LATIN AMERICA

Naples, Florida  
Tel: +1 239 263 7600  
lapresales@handheld.com  
  
Rio De Janeiro  
Tel: +55 21 2178 0500  
lapresales@handheld.com  
  
Mexico  
Tel: +52 55 5203 2100  
lapresales@handheld.com

### EUROPE, MIDDLE EAST, AND AFRICA

Europe  
Tel: +31 (0) 40 29 01 600  
eusales@handheld.com  
  
United Kingdom  
Tel: +44 (0) 1 925 240055  
eusales@handheld.com  
  
Italy  
Tel: +39 02 7254 6754  
Info.italy@handheld.com

France  
Tel: +33 (0) 1 41 158220  
Info.france@handheld.com  
  
Germany  
Tel: +49 (0) 7 477 151377  
Info.germany@handheld.com  
  
Spain  
Tel: +34 93 228 78 68  
Info.spain@handheld.com

Hand Held Products, Inc., ("Hand Held Products")® 1999-2007. All rights reserved. Printed in the U.S.A. Web Site Address: [www.handheld.com](http://www.handheld.com)  
Due to Hand Held Products' continuing product improvement programs, specifications and features herein are subject to change without notice.

