

DIGITAL MESSAGE REPEATERS



EV-20A

DIGITAL SOUND REPEATER W/USB


- Compact digital messaging ideal for kiosks and retail displays
- Built-in amplifier and speaker
- Record messages with built-in microphone or upload from computer via USB
- Motion sensor for automatic activation
- Accepts SmartMedia memory cards - 32Mb card included for over six minutes of CD-quality digital storage
- Optional mounting bracket
- CD-ROM tone library, software and USB cable included
- Five year warranty



S-20S

DIGITAL MESSAGE/TONE MODULE W/USB

- Digital audio storage module compatible with TOA 9000, 900, 700 and BG-M Series mixer/amplifiers
- USB interface for fast audio file transfer between PC and module
- Three minutes of CD quality digital storage — 50 to 20k Hz frequency response
- Versatile CD-ROM tone library included
- Accepts four audio files — 44.1 kHz, 16 bit PCM, monaural WAV format
- External activation for single or repeating playback
- Automatic priority overrides current playback
- Stop function immediately cancels playback
- Selectable repeat interval for each message
- Auto-mute function for priority over background music
- Adjustable level control
- CD-ROM tone library, software and USB cable included
- Five year warranty



EV-20R

DIGITAL MESSAGE REPEATER W/USB

- Rack-mount digital message repeater
- Three minutes of CD-quality digital storage
- Four selectable messages/tones
- 44.1kHz, 16 bit PCM, monaural, uncompressed WAV format
- USB interface for fast PC data transfer
- Upload messages from PC or record directly to unit
- Front panel mic/line input (switchable)
- Built-in amplifier (3 W/8 ohm) for direct speaker connection
- Balanced line input pass-through to balanced line output
- Headphone output with adjustable volume control
- Individual message activation via front panel and/or rear panel switch inputs
- Stop input terminal
- Adjustable broadcast delay time (0, 2 and 4 sec)
- Interval timer allows messages to be repeated at various time intervals (0,5,10, 30 seconds or 1,5,10, 30 minutes, 1 hour or continuous)
- Automatic muting of external source during message activation
- Busy output terminal for activating external equipment
- CD-ROM tone library, software and USB cable included
- External 24 VDC input
- Requires AC power supply, model AD-246
- Optional rack-mount kits, model MB-WT3 (one unit) and MB-WT4 (two units)
- Five year warranty



PM-20EV

DIGITAL PAGING MICROPHONE W/USB

- Adjustable unidirectional gooseneck paging microphone with three minutes of CD-quality digital storage
- Use as conventional paging microphone plus easily record and playback messages or tones
- Built-in monitor speaker
- Rehearsal function for pre-recording and auditioning messages before broadcasting
- Individual pre and post-announcement chime tones
- Adjustable broadcast delay time (0, 2 and 4 sec)
- Compression circuitry prevents distortion
- Adjustable mic, speaker and chime volume
- Line output with both 1/4" phone jack and removable terminal block
- Busy output terminal for activating external equipment
- Press-to-Talk and Latch activation modes
- External microphone input terminal
- Optional headset microphone, model WH-4000H
- CD-ROM tone library, software and USB cable included
- Requires AC power supply, model AD-246
- Five year warranty



Optional Mounting Hardware

Model	Accessory	
EV-20A	C-BC31	Wall/Ceiling-Mount Bracket, Black
EV-20R	MB-WT3	Rack-mount Kit for One EV-20R, Black (1RU)
	MB-WT4	Rack-mount Kit for Two EV-20R, Black (1RU)



C-BC31



MB-WT3



MB-WT4

