



# VIDEO SURVEILLANCE

## CCTV Video Surveillance Systems - NEW!

### COMBINATION DOME COLOR CAMERAS

- High speed pan/tilt: 360°/second
- 255 preset positions
- 1/4-inch CCD imager
- 480 TV lines of resolution
- Zoom: Up to 23x optical, 12x electronic
- Pelco "D", Bosch and Panasonic protocol compatible



#### C-CC514

##### INDOOR COMBINATION DOME CAMERA

- Tilt rotation range: +5° to -90°
- Three alarm inputs

#### C-CC564

##### ADVANCED INDOOR COMBINATION DOME CAMERA

- Wide dynamic range and day/night functions
- High sensitivity: 0.03 lux
- Tilt rotation range: +5° to -185°
- Auto-flip function
- Privacy masking
- Eight alarm inputs



#### C-CC714

##### OUTDOOR COMBINATION DOME CAMERA

- Tilt rotation range: +5° to -90°
- Built-in heater and fan
- Three alarm inputs



#### C-CC764

##### ADVANCED OUTDOOR COMBINATION DOME CAMERA

- Wide dynamic range and day/night functions
- High sensitivity: 0.03 lux
- Tilt rotation range: +5° to -185°
- Auto-flip function
- Privacy masking
- Built-in heater and fan
- Three alarm inputs

#### C-CV854D-3

##### VANDAL-PROOF MINI COLOR DOME CAMERA

- Diecast aluminum alloy and polycarbonate resin dome cover
- Indoor and outdoor (IP66)
- Day/Night mode
- 3.0 to 9.0mm varifocal lens in three axis
- Auto-iris
- 1/3-inch CCD, 500 TVL
- Backlight compensation
- 24 VAC or 12 VDC
- Optional heater, model C-A854H



#### C-CV202-3

##### C-CV202-F3

##### ECONOMY MINI INDOOR COLOR DOME CAMERA

- C-CV202-3: 2x 2.8 to 5.8mm varifocal auto-iris lens
- C-CV202-F3: built-in fixed focus, 3.0mm fixed-iris lens
- 1/4-inch CCD, 480 TVL
- Backlight compensation
- Monitor output
- 12 VDC



#### C-CV24-2

##### MINI INDOOR COLOR DOME CAMERA

- 2.0 to 4.0mm varifocal in three axis
- Wide camera lens angle setting
- Auto-iris
- 1/4-inch CCD, 480 TVL
- Backlight compensation
- 24 VAC or 12 VDC



#### C-CC364

##### WIDE DYNAMIC RANGE

##### COLOR CAMERA

- Wide dynamic range and day/night functions
- High sensitivity: 0.5 lux (color mode)/ 0.01 lux (b/w mode)
- 1/3-inch CCD imager
- 500 TV lines resolution
- Alarm input
- 24 VAC or 12 VDC
- CS lens compatible (available separately)
- Optional C-RU10 Remote Controller



#### C-CV102-CS

##### ECONOMY CS-MOUNT INDOOR COLOR CAMERA

- CS lens compatible (available separately)
- 1/4-inch CCD, 480 TVL
- Backlight compensation
- 12 VDC



#### C-CV14-CS

##### COMPACT INDOOR COLOR CAMERA

- CS lens compatible (available separately)
- Auto-iris
- 1/4-inch CCD, 480 TVL
- Backlight compensation
- 24 VAC or 12 VDC



#### C-CV14-2

##### INDOOR COLOR CAMERA

- 2.0 to 4.0mm varifocal
- Auto-iris
- 1/4-inch CCD, 480 TVL
- Backlight compensation
- 24 VAC or 12 VDC



#### C-CV44-3

##### OUTDOOR COLOR CAMERA

- Indoor and outdoor (IP66)
- 3.0 to 6.0mm varifocal
- Auto-iris
- 1/4-inch CCD, 480 TVL
- Backlight compensation
- 24 VAC or 12 VDC

