Coaxial Products

Coaxial CCTV-Cam Cable

RG59 Coaxial Cable with 2-Conductor Power-Limited Cable Suitable for CCTV Installations 20 AWG Solid Copper Center Conductor Gas Injected Polyethylene Dielectric Copper Braid Shield, 95% Coverage 2-Conductor 18 AWG Stranded Copper Flame Retardant PVC Insulation and Outer Jackets Impedance 75 Ohms UL Listed – NEC Type CM, CL3

200-915BK 500' RG59 Coaxial CCTV-Cam Cable, Black – Spool

200-915WH 500′ RG59 Coaxial CCTV-Cam Cable, White – Spool

BNC Connector Crimp Kit

75 Ohm BNC Crimp Kit Nickel-Plated Connector Bodies, Ferrules and Washers Delrin Dielectric Gold Plated Center Contacts Includes RG58/RG59P, RG59/RG6P and

200-123 75 Ohm BNC Male with 3 Ferrules200-124 75 Ohm BNC Female with 3 Ferrules

Thread Protectors

RG6/RG8X ferrules

Environmentally seals F-ports to F-connectors with coaxial cable Compresses to form seal when F-connectors are

tightened onto 3/8" threaded ports

200-958BK Thread Protector, 0.25" long **200-959BK** Thread Protector, 0.41" long

Compression Termination Tool

Professional Watertight Termination of Steren PermaSeal™ F, RCA, and BNC Connectors for Series 59, 6, 11 Coaxial Cables Smooth One-Cycle Full Ratchet Mechanism Ratchet Release Lever Rugged Hardened Carbon Steel Construction, Black-Oxide Finish Yellow/Black Rubberized Grip Handles for Reduced Fatigue Built-in Cable Cutter Includes interchangeable F, RCA, and BNC dies 2″ (W) x 9″ (H) x 1″ (D)

204-036 Universal Compression Tool **204-034** 3-Piece Die Set for 204-036

See Steren Catalog pg. A13 for more products in this category



200-915BK RG59 Camera Black **200-915WH** RG59 Camera White



200-123 BNC Female

200-124 BNC Male



200-958BK 0.25"



200-959BK 0.41"



204-036

F, BNC, RCA, RG59, RG6 Tool



204-034

F, BNC, RCA Die Set

