

D Telephony & Twisted Pair Products

Telephony & Twisted Pair Products

Structured Wiring Cables






Cable Solutions for Whole Home Voice-Video-Data
 Carries multiple services in one easy-to-install cable
 Saves installation time and money
 Eliminates multiple cable pulls
 Readies premises for future services
 18 AWG RG6/U-Quad Coax with
 Copper-Clad Steel Conductors
 20 AWG RG59 Coax with Solid Copper Conductors
 4-Pair 24 AWG CAT5E Networking Cable with
 Solid Copper Conductors
 16/4 or 18/2 Speaker/Power-Limited Circuit Cable with
 Stranded Copper Conductors
 Flame Retardant PVC Jackets
 Conforms to ANSI/SCTE 74 2003 and/or
 ANSI/TIA/EIA 568-B.2 standards
 UL Listed – NEC Type CM

- 300-669PR** 1000' 1xRG59 + 1xCAT5E 350MHz + 18/2 Speaker Cable, Bundled – Spool 0.512" (13mm) O.D.
- 300-770PR** 500' 1xCAT5E 350MHz + 16/4 Speaker Cable, Siamese – Spool CAT5E 0.217" (5.5mm) O.D., 16/4 Cable 0.295" (7.5mm) O.D.
- 300-771GY** 500' 1xCAT5E 350MHz + 2xRG6/U Quad Shield, Triamese – Spool CAT5E 0.217" (5.50mm) O.D., RG6/U-Quad 0.30" (7.62mm) O.D.
- 300-772RD** 500' 1xCAT5E 350MHz + 1xRG6/U Quad Shield, Siamese, Red – Spool
- 300-772WH** 500' 1xCAT5E 350MHz + 1xRG6/U Quad Shield, Siamese, White – Spool CAT5E 0.217" (5.50mm) O.D., RG6/U-Quad 0.30" (7.62mm) O.D.
- 300-773BL** 500' 2xCAT5E 350MHz + 1xRG6/U Quad Shield, Triamese – Spool CAT5E 0.217" (5.50mm) O.D., RG6/U-Quad 0.30" (7.62mm) O.D.
- 300-774BL** 500' 2xCAT5E 350MHz + 2xRG6/U Quad Shield, Bundled – Spool 0.669" (17mm) O.D.

Plenum Fast Media™ CAT6 Cable

Plenum-Rated Category-6 Unshielded
 Twisted Pair (UTP) Cable
 Ultra-High-Performance Data Communications Cable
 Suitable for 550MHz High-Speed Applications, Critical
 Network Applications, Gigabit Ethernet, Fast Ethernet,
 Broadband Audio and Video, 155Mbps ATM, and
 100Mbps TP-PMD/CDDI, NEXT, ELFEXT and
 RL Bandwidth Compliant
 4-Pair – Easily Identified Color-Striped Pairs
 PE pair separator minimizes pair motion
 23 AWG Solid Annealed Copper Conductors
 Virgin Polyolefin Insulation
 Flame Retardant Blue or Grey TFE Jacket
 100% Tested Wiring Sequence and Continuity
 Excellent Attenuation and Crosstalk Characteristics
 Impedance 100 Ohms ±5%
 DC Resistance 6.84 Ohms /100m max.
 Exceeds ANSI/TIA/EIA-568-B.2-1 standards
 UL/cUL 1685, CSA, ETL Listed – NEC Type CMP

- 300-796BL** 1000' Blue Plenum Fast Media™ CAT6 Cable – Reel in Box
- 300-796GY** 1000' Grey Plenum Fast Media™ CAT6 Cable – Reel in Box



300-669PR 1xRG59 + 1xCAT5E + 18/2 Speaker Cable, Purple

300-770PR 1xCAT5E + 16/4 Speaker Cable, Purple

300-771GY 1xCAT5E + 2xRG6/U Quad, Grey

300-772RD 1xCAT5E + 1xRG6/U Quad, Red

300-772WH 1xCAT5E + 1xRG6/U Quad, White

300-773BL 2xCAT5E + 1xRG6/U Quad, Blue

300-774BL 2xCAT5E + 2xRG6/U Quad, Blue



300-796BL Blue
300-796GY Grey