

B Satellite/CATV Drop Installation Materials

Satellite/CATV Drop Installation Materials

Grip-Clip™ Mounting Clips

Grip-Clip™ Cable Mounting Clips
 Automatically adjusts to coaxial wire size
 Provides strain relief without pinching or damage
 Prevents signal loss and protects installation
 Pre-loaded screws and integral automatic ratchet mechanism allow for easy, one-handed installation
 High-Impact Durable Polyethylene Construction
 UV Inhibitor™ protects from ultraviolet ray damage
 Various Sizes for Telecommunications Wire and Series 6 and 59 Coax, Single and Dual, with and without Messenger Wire

- 200-965BK** Ground Wire Grip-Clip™, Black
- 200-965GY** Ground Wire Grip-Clip™, Grey
- 200-965WH** Ground Wire Grip-Clip™, White

See Steren Catalog pg. B26 for more products in this category



- 200-965BK** Black
- 200-965GY** Grey
- 200-965WH** White

Feed-Through Bushings

Seals wall openings and protects cable
 Impact-Resistant ABS Plastic Construction
 UV Inhibitor™ protects bushing from ultraviolet ray damage

- 200-984BK** RG6 Black Bushing with Ground and Messenger Knockouts
- 200-984CL** RG6 Clear Bushing with Ground and Messenger Knockouts
- 200-984IV** RG6 Ivory Bushing with Ground and Messenger Knockouts
- 200-984WH** RG6 White Bushing with Ground and Messenger Knockouts
- 200-985BK** RG6-Dual Black Bushing with Ground and Messenger Knockouts
- 200-985CL** RG6-Dual Clear Bushing with Ground and Messenger Knockouts
- 200-985IV** RG6-Dual Ivory Bushing with Ground and Messenger Knockouts
- 200-985WH** RG6-Dual White Bushing with Ground and Messenger Knockouts

See Steren Catalog pg. B27 for more products in this category



- 200-984BK** RG6 KO Black
- 200-984CL** RG6 KO Clear
- 200-984IV** RG6 KO Ivory
- 200-984WH** RG6 KO White



- 200-985BK** RG6-Dual KO Black
- 200-985CL** RG6-Dual KO Clear
- 200-985IV** RG6-Dual KO Ivory
- 200-985WH** RG6-Dual KO White

Weather Boots

- 200-977BK** Tapered-Inner-Diameter Weather Boot
 Suitable for Series 6 and 59 Coaxial Cable
 Flexible Rubber Construction
 UV-Inhibitor™ Ultraviolet-Ray Resistant
 2 1/2" Long Boot – Tapered I.D.
 6 1/2-11mm

See Steren Catalog pg. B27 for more products in this category



- 200-977BK** 2 1/2"