



# Boiler Controls

McDonnell & Miller


## Low Water Cut-Offs – Electronic For Hot Water Boilers

**NOW WITH SELF-CLEANING PROBE!**

### RB-120 Low Water Cut-Offs



- For residential and (where codes allow) commercial applications
- Electro-mechanical operation
- Automatic reset feature resumes operation after a power outage when water is on probe
- No blow down required
- 6,000 ohms probe sensitivity
- Maximum ambient temperature 120°F (49°C)
- Maximum water temperature 250°F (121°C)
- Maximum water pressure 160 psi (11.2 kg/cm<sup>2</sup>)



Boiler Controls

### Electrical Ratings

| Voltage | Power Consumption | Load Switching   |
|---------|-------------------|------------------|
| 120 VAC | 15 VA             | 5.8 A at 120 VAC |

### Dimensions, in. (mm)

| A                                   | B                                   | C                                   | D                                  | E                                  | F        | G<br>NPT |
|-------------------------------------|-------------------------------------|-------------------------------------|------------------------------------|------------------------------------|----------|----------|
| 6 <sup>3</sup> / <sub>8</sub> (162) | 5 <sup>1</sup> / <sub>8</sub> (130) | 2 <sup>9</sup> / <sub>16</sub> (65) | 1 <sup>5</sup> / <sub>8</sub> (41) | 1 <sup>3</sup> / <sub>8</sub> (35) | 3/4 (20) | 7/8      |

### Ordering Information

| Model Number | Part Number | Description       | Weight lbs. (kg) |
|--------------|-------------|-------------------|------------------|
| RB-120       | 144675      | Low water cut-off | 3.8 (1.7)        |