

Thermowells Sanitary



Description

Designed specifically for sanitary requirements of the food and dairy industry. Winters Sanitary Thermowells allow for easy installation and replacement of bimetallic dial thermometers without draining the process.

Thermometers

| Specifications | |
|--------------------------------|---|
| Material: | 316 stainless steel |
| Connection: | 1 1/2" (40mm) or 2" (50mm) Tri-Clamp® |
| Thermometer Connection: | 1/2" NPT |
| Bore: | 0.260" (6.604mm) standard |
| Other: | Lengths to fit all standard Bi-Metal Thermometers |

| Product Codes | | | |
|---------------|---------|-----------------------|----------------|
| Stem Length | Code | Tri-Clamp® connection | U - Dimensions |
| 2 1/2" (63mm) | 15SANI2 | 1 1/2" (40mm) | 1.5" |
| 4" (100mm) | 15SANI4 | 1 1/2" (40mm) | 3" |
| 6" (150mm) | 15SANI6 | 1 1/2" (40mm) | 5" |
| 9" (225mm) | 15SANI9 | 1 1/2" (40mm) | 8" |
| Over 9" | 15SANIX | 1 1/2" (40mm) | - |
| 2 1/2" (63mm) | 2SANI2 | 2" (50mm) | 1.5" |
| 4" (100mm) | 2SANI4 | 2" (50mm) | 3" |
| 6" (150mm) | 2SANI6 | 2" (50mm) | 5" |
| 9" (225mm) | 2SANI9 | 2" (50mm) | 8" |
| Over 9" | 2SANIX | 2" (50mm) | - |

