

TWIN-CAT-2 Dual Spindle Heavy-Duty Rewind / Unwind Station

The world's easiest solution for wind-in / wind-out, label reversing & inspection applications.

Here's LABELMATE's Dual-Spindle Heavy Duty Unwinder / Rewinder, the **TWIN-CAT-2**. With two powerful motors and your choice of Core holders you have maximum versatility. Each spindle can rewind or unwind. You control the direction and torque on each Spindle independently. An External Halt Control allows you to STOP and START the **TWIN-CAT-2** with a Foot Switch, a Pre-set Label Counter or other external device.



- Unwind and Rewind labels on one machine. Ideal for “wind-in / wind-out” operations.
- Reverse the order of serialized labels.
- Conveniently rewind labels onto a different Core size. With two universal Adjustable Core Holders you can unwind from any diameter Core and rewind onto any diameter Core within the range of 1- to 4-inches! Great for production shops with varied jobs.
- Add the Label Inspection option to create a stand-alone Inspection Station.
- Then, add a Label Counter to create an all-in-one Inspection and Counting Station as shown at left.
- Wind small rolls of labels from larger ones.
- Set up an in-line slitting operation with a LABELMATE **S-100** or **S-200** Slitter at your printer output.
- Strip unwanted matrix from die-cut labels for easy disposal as you rewind them.
- All **TWIN-CAT-2** Models operate at speeds up to 30-inches per second.
- Each Spindle allows roll diameters up to 8.6” (220-mm).
- Worldwide, heavy-duty universal Power Supply included.

Please refer to the table below to Specify Your TWIN-CAT-2:

“**TWIN-CAT-2, [Core Holder Order Number] Upper Spindle, [Core Holder Order Number] Lower Spindle.**” Add Inspection and Counter Options if desired. Please see the information on the facing page.

You Must Also Order Two Core Holders From This List						
(2 Core Holders are required – Mix or Match)						
CORE HOLDER TYPE	CORE DIAMETER	MAXIMUM WIDTH	# OF FLANGES	ORDER NUMBER		
Coreless	NA	6” (152-mm)	2	SHAFT, TC-CL		
	Fin Style			1” (25.4-mm)	SHAFT, TC-1”	
		3” (76-mm)		10” (254-mm)	SHAFT, TC-W6	
Continuously Adjustable	1” to 4” (25- to 100-mm)	6” (152-mm)	1	ACH-TC2 Cannot mix.*		
	“Quick-Chuck” Quick-locking Core Chuck	1.5-inch (38.1-mm)		6.7” (170-mm)	TC-C1.5-170	
40-mm (1.57”)		6.7” (170-mm)	10.6” (270-mm)	TC-C1.5-270		
70-mm (2.76”)			2	TC-C40-170		
3” (76-mm)	8.5” (220-mm)	TC-C70-170				
	10.6” (270-mm)	TC-C76-170				
	4” (102-mm)	6.7” (170-mm)	1	TC-C76-220		
8.5” (220-mm)		TC-C76-270				
10.6” (270-mm)		TC-C100-170				
				TC-C100-220		
				TC-C100-270		
OPTIONAL: Dual Control Low-Torque Option for delicate label webs.				LTO-TC2		

*The ACH-TC2 cannot be mixed with any other type of Core Holder. The ACH-TC2 is not suitable for slitting applications.