

# Cart Dumping Systems



Model shown D6202 Baler/Compactor

## Features:

- Cylinder mounts and main hinge are 3/4" reinforced steel
- Moving parts are enclosed for operator safety
- Weather-proof
- Optional power supplies available

### Clearance Requirements:

- Versa-Kart 60 & 90 . . . . .109"
- Versa-Kart 35 . . . . .103"
- Poly-Kart 60 & 90 . . . . .115"
- One-Yard Tilt Truck . . . . .132"
- Half-Yard Tilt Truck . . . . .124"

## Hydraulic Lift

Model No.	Description	Dimensions						Capacity		Ship Weight lbs.
		Inches			mm			lbs.	kg	
		W	L	H	W	L	H			
D6201	Fixed Position Dumper	46"	36"	49"	1168	914	1245	1,200	544	800
D6202	Baler/Compactor Attached Dumper	46"	45"	49"	1168	1143	1245	1,000	454	850
D6203	Mobile Dumper	40"	60"	49"	1016	1524	1245	800	363	900

## Fixed Position Self-Contained Hydraulic Dumper (Standard Model)

Self-Contained Hydraulic Dumpers® streamline in-plant handling of waste and recyclables. The Standard Model is available with lockable casters and forklift brackets. A battery-powered version allows complete mobility with no reduction in efficiency or lifting capacity. One operator can unload up to 1,300 lbs. of scrap or waste in seconds. Operation is efficient, safe, and clean.

## Attached Mobile Dumper

Same construction as fixed position. Solid-steel throughout. Empties into containers, bailers, or compactors up to 57" high. Wheels for swinging door/baler application.

## Fully Mobile Dumper

Construction as described. Dumper is factory fitted with locking wheels for total mobility. Power Supply options meet special situations where power source is non-standard. Battery operated version available.

