





The E-242HD electric vehicle offers superior performance and durability.

Its powerful 6 hp motor excels at trailer towing, hauling 7000 lb. with the 6 mph speed option.

Low maintenance is guaranteed by a dependable automotive differential and larger self-adjusting drum brakes.

It's built to last with a 14-G diamond-plate body and a tubular steel frame.

Benefits

ENDURANCE. Powerful 6 hp motor for trailer towing.

RUGGEDNESS. Automotive ring gear differential, axle shafts on roller bearings. **DEPENDABILITY.** Larger self-adjusting drum brakes.

COMFORT. Bucket seat on slide adjusters.


STURDINESS. 14-G diamond-plate steel body, tubular frame.

DURABILITY. Optional bolt-on bumpers and rear wheel guards.

BATTERY EFFICIENCY. 24V accessory option to equalize cells, extend battery life.

ROUND-THE-CLOCK OPERATION. Optional lift-out battery box.





Technical specs	6	
Туре	24-volt Electric vehicle	G C
Capacity	*500 lb. (227 kg)	
Speed (Max)	10 mph (16 km/h)	
Motor	6 hp	
Controller	Electronic speed controller	A 0
Battery	Four 6V-220AH batteries	
Charger	25 amp, built-in automatic	
Transmission	Dual V-belt drive	
Drive axle	Differential with automotive ring gear	
Brakes	Dual self-adjusting mechanical drum brakes on rear, hand lever parking brake.	ASSIFIE
Steering	Handlebar	
Suspensions	Dual coil springs on front, dual coil springs and shock absorber on rear.	r(UI)
Seats	Bucket seat on slide adjusters	
Indicators	Battery status indicator	
Safeties	Optional reverse alarm, deadman seat switch	
Lights	Headlight, tail/brake light	
Accessories	Horn	
Wheels	4.8x8 LRB pneumatic tires	10
Unit Weight	800 lb. (364 kg)	
Options	 Bolt-on bumpers and rear wheel guards. Front suspension with dual shock absorbers. Reverse alarm. 4.5, 6, 8 mph differential ratios. Hitch. 24-volt accessories. 6V-244AH batteries. Digital battery status indicator, hour meter. 	0-00
Standard	Maintenance meter. Strobe light. Steering wheel. Convertible backrest for two passengers. MX maintenance kit with a toolbox and storage cabinets. Conforms to requirements for type E as stated in UL 583 and ANSI B56.8	www.motrec.com
Notes	*includes 200 lb. per passenger. Specifications and standard equipment are subject to change without notice.	