

STELLAR AGGRESSOR™

138-15 Mid-Size OTR



The Stellar Aggressor 138-15 MS (Mid-Size) OTR series, features a rugged, heavy duty 15' steel OTR service body with over 60 cubic feet of storage. The standard driver side rail folds down, for ease and safety of loading and unloading of tires, as well as sign boards for identification.

The 138-15 MS OTR can be equipped with either a model 4500 or 6000 hydraulic knuckleboom crane. These cranes are both operated by a standard fully proportional radio remote control.



All of the underbody tool compartments come standard with the exclusive Stellar slide top doors for unobstructive storage access. Stainless steel automotive style slam latches and hardware are standard on all tool compartments.

The left front storage compartment houses the 3/8" and 1/2" hose reels, along with the FLR (filter, lubricator and regulator) and a 12-volt trouble light reel.



The SHD-66DD direct-driven hydraulic-drive air compressor is mounted on the crane base. The model SHD-66DD direct drive hydraulic air compressor is a 4-cylinder, 2-stage compressor with a 100 cubic inch displacement and an output capacity of 46 CFM @ 175 PSI. The crane boom is stored in travel position in a unique crane saddle, which will ease wear and tear on the turntable bearing. The SHD-66DD carries a 2-year warranty because of these features.

Specifications	4500	6000
Crane Rating	45,000 foot/pounds	60,000 foot/pounds
Standard Boom Length	11 foot from CL of Crane 14 foot from CL of Truck	11 foot from CL of Crane 14 foot from CL of Truck
Boom Extension	Hydraulic 32 inches	Hydraulic 32 inches
Max. Horizontal Reach	14 foot-from CL of Crane 17 foot-from CL of Truck	14 foot-from CL of Crane 17 foot-from CL of Truck
Rotation	290 degree power (worm gear drive)	290 degree power (worm gear drive)
Lifting Capacities <i>(from CL of truck)</i>	7,500 lbs. @ 9 foot 5,600 lbs. @ 11 foot 4,100 lbs. @ 14 foot 3,200 lbs. @ 17 foot	10,000 lbs. @ 9 foot 7,500 lbs. @ 11 foot 5,450 lbs. @ 14 foot 4,250 lbs. @ 17 foot
Power Supply Required	PTO & Pump (5 gpm @ 2800 psi)	PTO & Pump (6 gpm @ 2850 psi)
Controls	Proportional Radio Control Standard	Proportional Radio Control Standard
Stowed Height <i>(above truck frame)</i>	71 inches	75 inches
Mounting Space Req.	32 inches	32 inches
Approx. Shipping Weight	2,400 lbs.	3,150 lbs.

