



FasTrak™ Super Duty 48/54

Features and Benefits

- Kawasaki Commercial V-twin engines
- Welded steel decks. NOT STAMPED!
- 20" drive tires, 13" caster tires
- Commercial hydrostatic transmissions for true zero turning radius maneuverability
- Commercial duty, serviceable deck spindles
- Heavy-duty, remote air cleaner for increased engine protection.
- Heavy-duty, 7-gauge, full-height rear bumper with built-in hitch provides protection for the engine and exhaust, retains the ease of maintenance.
- Toughest frame, front forks, and deck in the industry
- Wide stance, low center of gravity for unmatched stability on slopes
- Simplest maintenance in the industry
- 10-gallon fuel capacity with built-in sight line
- Seat springs and slide with arm rests come standard
- Silky-smooth SmoothTrak™ steering with patented automatic park brake system
- Optional, foldable certified ROPS and seat belt.
- 48" or 54" side-discharge/mulching decks
- 60" side-discharge/mulching decks coming soon!
- "Drive-straight" adjustment.
- Standard hour meter.

(Mower shown with optional ROPS)



Best warranty in the business

- Lifetime warranty on the leading edge of the deck
- Lifetime warranty on tractor frame
- A limited residential four-year warranty – parts and labor*
- A limited 2-year commercial warranty – parts and labor*

* See your local Hustler dealer for complete warranty details





The FasTrak™ Super Duty Specifications 48/54

(Mower shown with optional ROPS)



FasTrak™ Super Duty 48/54 Specifications

Engine

Model	23/48	25/54
Make	Kawasaki	Kawasaki
Horsepower	23	25
No. of Cylinders	2	2
Max. Torque	39.8 ft lbs @ 2400 rpm	41.2 ft lbs @ 2400 rpm

Starter 12-volt (.8 kw) (see engine manufacturer specs)

Ignition Electronic

Charging System 12-volt, 15-amp (see engine manufacturer specs)

Fuel Unleaded gasoline (see engine manufacturer specs)

Fuel Filter Replaceable, automotive-type

Air Cleaner Heavy-duty, remote mounted

Cooling Air cooled. Fly-wheel fan

Governor Mechanical

Traction Drive System

Type Dual hydrostatic. Commercial-duty Hydro-Gear ZT 2800. ZT transmissions feature relief valve, charge pump, spin-on oil filter, expansion tank, and steel cut gears. Hydraulic system operates on 20W50 motor oil.

Hydrostatic Drive V-belt drive from engine crankshaft

Ground Speed Infinitely variable: 0-8 mph (0-12.9 kph) forward, 0-5 mph (0-8 kph) reverse

Steering Twin-lever SmoothTrak™ steering provides independent control of each drive wheel. Speed, forward, reverse, brake, and turns are all controlled with hand-operated controls

Turning Radius True zero turning radius. Turns within its own length. Counter-rotating, independent drive wheels

Brakes

Service: Hydrostatic dynamic braking

Parking: Internal transmission mechanical brake. When steering levers are placed in neutral position, integral park brakes are automatically engaged

Mower Drive Single V-belt drive from engine with electric clutch. Spring tension idler for extended belt life

Tires

Front: 13 x 5 – 6, rib tread

Drive: 48 in: 20 x 10 – 10, turf tread

54 in: 20 x 12 – 10, turf tread

Capacities Fuel System: 10 US gal (37.85 l)

Dimensions

Height: 41.8 in (106.17 cm)

W/48 in Deck

Length: 74.42 in (189.02 cm)

Overall width: 51.77 in (131.50 cm) w/discharge chute up

Tire-to-tire width: 47 in (119.38 cm)

Weight: 835 lbs (378 kg)

W/54 in Deck

Length: 74.42 in (189.02 cm)

Overall width: 61.30 in (155.70 cm) w/discharge chute up

Tire-to-tire width: 51 in (129.54 cm)

Weight: 860 lbs (390 kg)

Safety Features Operator presence system connected to deck and drive clutches. Stabilizer rollers at rear of tractor

Seat Molded, cool-grey vinyl seat with adjustable armrests. Fore and aft sliding adjustment. Seat-pan suspension springs standard.

Construction Mainframe is 1.5 in x 1.5 in x .188 in (3.8 cm x 3.8 cm x .48 cm) square steel tubing. Front caster wheels mounted with roller bearings on each wheel. Front caster forks are .375 in (.95 cm) steel

Deck Lift Foot-operated deck height adjustment. Pin for setting height, detent for transport position

Controls Hand-operated choke, throttle, ignition switch, electric mower clutch. Integrated parking brakes

Indicators Engine warning light (low oil pressure)

Cup Holder Two cup holders molded into the left side fuel tank. Accommodates nearly any cup size.

Decks 48" and 54" Side-Discharge Decks

Type Free-floating mower using three blades with center blade to the front. Mower is suspended at the corners. Includes 4 deck-mounted rollers to improve flotation in rolling and uneven terrain

Deck Lift Raise and lower deck from driver's seat with simple foot-operated deck height adjustment. Pin for setting height, transport position. Change cutting heights, hop curbs and trailer more easily

Construction .125 in (.317 cm) welded steel. Solid 1 in x .375 (2.55 cm x .95 cm) steel bars reinforce impact areas on trim edges. Commercial-style box-section reinforced front edge. Reinforcements welded onto spindle mount areas. Molded rubber discharge chute.

Cutting Heights Foot-operated deck height adjustment. Pin for setting height, detent for transport position. Height adjustment in .25 in increments from 1.5 in to 4.5 in (3.81 cm to 11.43 cm)

Mowing Blades Heavy-duty, heat-treated, high-lift Fusion™ blades

48 in: 16.5 in x 2.5 in x .20 in

54 in: 18.5 in x 2.5 in x .20 in

Blade Tip Speed

48 in: 18,306 fpm (at 3500 RPM engine speed)

54 in: 18,464 fpm

Blade Drive V-belt drive to all three spindles. Spring tension idler pulleys-Spindles Aluminum casting with steel shafts and sealed ball bearings

Flotation Suspended mower floats on four spring-assisted chains. 4 anti-scalp wheels are standard

Width of Cut

48 in: 47.1 in (119.63 cm)

54 in: 53.1 in (134.87 cm)

Trim Capacity (left side)

48 in: 0.5 in (1.27 cm)

54 in: 2.5 in (6.35 cm)

Accessories

Flex Forks™ Shock-absorbing front caster forks for a smooth ride and smoother cut

Mulch Kit Recycles clippings under deck allowing clippings to be cut and recut, then discharged down into the grass. Reduces handling of clippings, improves appearance, and recycles nutrients back to the soil

Catcher Commercial-duty, 6.5 bushel, rear-mounted, two-bag catcher

ROPS Certified, 2-post, foldable ROPS

Stripe Kit Make your lawn look like Yankee stadium

Personalized Bumper Have your name laser-cut into the rear bumper of your mower. Ask your dealer for details.

Snow Blower 48" two-stage blower utilizes the deck-lift to raise and lower. The blower is powered by deck belt and features a rotating chute adjustable from the seat and a heavy-duty gear box

Snow Blade 56" wide, 3-position angling, heavy-duty, reversible, replaceable cutting edge

Gator™ Blades Patented mulching blade design

Wavy Blades Improved performance for mulching

Jack Kit Mounts to unit and can be carried onboard at all times

Other Accessories Light Kit, Tire Chains, Steering Lever Extension Kit, Weight/Utility Box

Specifications subject to change without notice.



For more information : www.hustlerturf.com **HUSTLER**

HUSTLER TURF EQUIPMENT • HESSTON, KANSAS 67062 • 1-800-395-4757