

Mini FasTrak™ 36/42 Specifications

EI	ıg	Ш	1	e
_		_		1

	··j···-							
	Model	OHV Honda	Kohler	Kohler				
Ξ	Horsepower	16	15	17				
	No. of Cylinders	2	1	1				
	Displacement	32.3 cu in (530 cc)	29.1 cu in (477 cc)	32.6 cu in (535 cc)				
Ξ	Compression Ratio	8.3:1	8.5:1	8.5:1				
	Max.Torque	26.9 ft lbs @ 2500 rpm	27.0 ft lbs @ 2200 rpm	30.8 ft lbs @ 2200 rpm				
	Models Available	16/36, 16/42	15/36	17/42				



Electrical System 12 volt, 15 amp regulated

Ignition Electronic

Fuel Capacity 6 US gal (22.71 L)

Transmission Dual hydrostatic, Hydro-Gear EZT Forward Speeds 0-7 mph (0-11.26 kph), infinitely variable Reverse Speeds 0-3.5 mph (0-5.63 kph), infinitely variable

Steering Patented Twin-lever, SmoothTrak™ steering provides independent control of each drive wheel. Speed, forward, reverse, brake, and true zero-degree-radius turns are all controlled with hand-operated controls (Patent # 6729115B2-FT)

Brakes

Service Hydrostatic dynamic braking

Parking Sprocket and cog. Patent-pending integral park brake system (when steering levers are placed in off position, park brakes are automatically engaged)

Seat Molded vinyl seat, deluxe high back. Optional armrests.

Accessories

Mulch Kit Recycles clippings under deck allowing clippings to be cut and recut, then discharged down into the grass. Reduces handling of clippings, improves appearance, and recycles nutrients back to the soil. Rear and side-mounted catching systems, hour meter

Specifications subject to change without notice.

Engine Model	OHV Honda	OHV Honda	Kohler	Kohler
Horsepower/Deck	16 hp/36	16 hp/42	15 hp/36	17 hp/42
Tires				
Front Casters	11 x 4 - 5, rib tread			
Rear Drive	18 x 8.50 - 8, turf tread	18 x 9.50 - 8, turf tread	18 x 8.50 — 8, turf tread	18 x 9.50 - 8, turf tread
Mower	36 in side-discharge	42 in side-discharge	36 in side-discharge	42 in side-discharge
Width	36 in (111.76 cm)	42 in (132.08 cm)	36 in (111.76 cm)	42 in (132.08 cm)
Blades	1, 20.5 in x 2.5 in x .20 in	2, 20.5 in x 2.5 in x .20 in	1, 20.5 in x 2.5 in x .20 in	2, 20.5 in x 2.5 in x .20 in
	1, 13.75 in x 2.5 in x .20 in		1, 13.75 in x 2.5 in x .20 in	
Blade Tip Speed	18,200 fpm	18,200 fpm	18,200 fpm	18,200 fpm
Cut Height	1.5 in to 4 in, .25 in increments	1.5 in to 4 in, .25 in increments	1.5 in to 4 in, .25 in increments	1.5 in to 4 in, .25 in increments
	(3.81 cm to 10.16 cm, .64 cm)			
Dimensions				
Height	38 in (96.52 cm)	37.3 in (94.74 cm)	37.3 in (94.74 cm)	37.3 in (94.74 cm)
Length	72.5 in (184.15cm)	74 in (187.96 cm)	74 in (187.96 cm)	74 in (187.96 cm)
Width Overall	35.9 in (91.19 cm) w/chute up	41.6 in (105.66 cm) w/chute up	41.6 in (105.66 cm) w/chute up	41.6 in (105.66 cm) w/chute up
Tire-to-tire width	35.5 in (90.17cm)	37.75 in (95.89 cm)	37.75 in (95.89 cm)	37.75 in (95.89 cm)
Net Weight	552 lbs (250.33 kg)	572 lbs (259.4 kg)	552 lbs (250.33 kg)	572 lbs (259.4 kg)

