

# FasTrak™ SuperDuty 36/42

A real pro for home or contractors!

## Best warranty in the business

- Limited residential four-year warranty – parts and labor!
- Limited commercial two-year warranty – parts and labor!
- Lifetime warranty on the tractor frame
- Lifetime warranty on the leading edge of the deck



## FasTrak™ SuperDuty 36/42 Features

- A true, commercial-duty unit in a compact package.
- The latest technology in hydrostatic transmissions! – Commercial-duty ZT 2800 transmissions feature the same rotating group as Hydro-Gear pump & motor combinations. ZT transmissions feature steel cut gears, relief valve, charge pump, and spin-on oil filter.
- Decks incorporate XR-7™ FreeFlow™ technology offering the highest quality of cut and finished appearance on the market. In either side-discharge or mulch, these new decks will produce an immaculate lawn
- SmoothTrak™ steering with patented automatic park brake system
- Wide stance, low center of gravity for excellent stability on slopes
- Fusion™ blades stay sharper longer!
- Molded rubber discharge chute standard
- Remote, heavy-duty air cleaner standard

**HUSTLER®** 

# FasTrak™ SuperDuty 36/42 Specifications



## Engine

Model	Kawasaki Kai	Kawasaki Kai
Horsepower	17	19
No. of Cylinders	2	2
Displacement	35.7 cu in (585 cc)	35.7 cu in (585 cc)
Compression Ratio	8.5:1	8.5:1
Max. Torque	36.2 ft lbs @ 2000 rpm	36.6 ft lbs @ 2000 rpm

**Starter** 12-volt, solenoid shift positive engagement

**Ignition** Electronic

**Charging System** 12-volt, 15-amp

**Fuel** Unleaded gasoline with 87 or higher octane

**Fuel Filter** Replaceable, automotive-type

**Air Filter** Heavy-duty air cleaner to extend the service interval for excessive, dirty applications and improved performance

**Cooling** Air cooled. Fly-wheel fan

**Governor** Mechanical

## Traction Drive System

**Type** Dual hydrostatic. Hydro-Gear ZT2800 commercial-duty pump/motor combination. Hydrostatic system operates on 20W50 motor oil.

**Transmission Drive** V-belt drive from engine crankshaft  
**Filter** Spin-on type

**Ground Speed** Infinitely variable: 0-8 mph (0-12.87 kph) forward, 0-6 mph (0-9.66 kph) reverse

**Steering** Twin-lever, SmoothTrak™ steering provides independent control of each drive wheel. Speed, forward, reverse, brake, and true zero-degree-radius turns are all controlled with hand-operated controls

**Turning Radius** True zero radius. Turns within its own length. Counter-rotating, independent drive wheels

## Brakes

**Service** Hydrostatic dynamic braking

**Parking** Sprocket and cog. When steering levers are placed in neutral position, integral park brakes are automatically engaged

**Mower Drive** Single V-belt drive from engine with electric clutch. Spring tension idler for extended belt life.

## Tires

**Front Casters** 13 x 5.0 – 6, rib tread

**Drive** 20 x 8.0 – 10, turf tread on 36 in model  
20 x 10.0 – 10, turf tread on 42 in model

**Fuel Capacity** 6 US gal (22.71 l) Site line in fuel tanks

**Seat** Molded vinyl seat with armrest. Fore and aft adjustment. Standard seat spring

## Dimensions

**Height** 40 in (101.6 cm)

## W/36 in Deck

**Length:** 74 in (187.96 cm)

**Overall width:** 36 in (96.5 cm) w/discharge chute up

**Tire-to-tire width:** 35 in (88.9 cm)

**Weight:** 650 lbs (294.84 kg)

## W/42 in Deck

**Length:** 78 in (198.12 cm)

**Overall width:** 42 in (106.7 cm) w/discharge chute up

**Tire-to-tire width:** 38 in (96.5 cm)

**Weight:** 675 lbs (306.17 kg)

**Deck Lift** Foot-operated deck height adjustment.

Pin for setting height, detent for transport position

**Safety Features** Operator presence system connected to deck and drive clutches. Stabilizer rollers at rear of tractor

## Construction

**Mainframe** is 1.5 in x 1.5 in x .188 in

(3.8 cm x 3.8 cm x .32 cm) rectangular steel tubing

**Drive motors** mounted to .120 in (.45 cm) welded steel

**Front caster wheels** mounted with roller bearings on each wheel

**Front caster forks** are .375 in (.95 cm) steel

**Controls** Hand-operated choke/throttle, ignition switch, electric mower clutch. Integrated parking brakes

**Indicators** Hour meter, engine warning light

**Cutting Heights** 1.5 in to 4 in (3.81 cm to 10.16 cm) in .25 in increments

**Cup Holder** Cup holder molded into the left side fuel tank. Holds nearly any cup size including Big Gulp™

## Decks

36", and 42" side-discharge decks

**Type** Free-floating mower using two blades. Mower is suspended at the corners. Includes deck-mounted rollers to improve flotation in rolling and uneven terrain. FreeFlow™ XR-7™ deck technology for minimized buildup of material under the deck and improved flow for awesome discharge pattern

**Deck Lift** Raise and lower deck from driver's seat with simple foot-operated deck height adjustment. Pin

for setting height, transport position. Change cutting heights, hop curbs and trailer more easily.

**Construction** 7 ga, .179 in (.45 cm) welded steel with 11 ga, .125 in doubler welded onto spindle mount areas. Solid 1.5 in x .5 in (3.81 cm x 1.27 cm) steel bars reinforce impact areas on trim edges. Steel deck housing is 4 in (10.16 cm) deep which allows high-capacity mowing.

**Cutting Heights** Foot-operated deck height adjustment. Pin for setting height, detent for transport position. Height adjustment in .25 in increments from 1 in to 5 in (2.55 cm to 12.7 cm).

**Mowing Blades** Heavy-duty, heat-treated, high-lift steel Fusion™ blades feature an exclusive electro-fusion technology that creates an ultra-hard layer at the blade's cutting edge. This means the blade remains sharp and continues to give a clean cut far longer than any blade you've ever used before.

36 in: 1-13.75 in x 2.5 in x .20 in and

1-20.5 in x 2.5 in x .20 in

42 in: 2-20.5 in x 2.5 in x .20 in

**Blade Tip Speed** 36 in: 18,600 fpm  
42 in: 18,400 fpm

**Blade Drive** V-belt drive to spindles. Spring idler tension pulleys.

**Spindles** Machine aluminum housing, 1 in (2.5 cm) diameter high carbon steel shafts & sealed ball bearings.

**Flotation** Suspended mower floats on spring-assisted chains. 2 anti-scalp wheels are standard.

**Width of Cut** 36 in: 33.5 in (85.09 cm)  
42 in: 40.25 in (102.24 cm)

**Trim Capacity (left side)** 36 in: .5 in (1.27 cm)  
42 in: 2.25 in (5.75 cm)

## Accessories

**Mulch Kit** Recycles clippings under deck allowing clippings to be cut and recut, then discharged down into the grass.

**Flex Forks™** Shock-absorbing front caster forks for a smooth cut and an even smoother ride.

**Steering Lever Extension Kit, Hitch Kit**

*Specifications subject to change without notice.*



For more information : [www.hustlerturf.com](http://www.hustlerturf.com) **HUSTLER**  
HUSTLER TURF EQUIPMENT • HESSTON, KANSAS 67062 • 1-800-395-4757