

The Stellar Road Raptor TS 904 is the ideal service vehicle for truck stop road service. The TS 904 design has a unique combination of aluminum and fiberglass to make up the service body. The inner structure aluminum frame fastens to the truck chassis by stainless steel fasteners. The use of aluminum versus steel reduces the total weight of the vehicle by approximately 160 lbs. This allows for a larger payload, greater fuel efficiency and better overall performance of the truck. The body gives you a sleek, more aesthetic appearance through the rounded automotive wheel well design. All hardware on the truck is



constructed of stainless steel. The use of aluminum in the frame and the use of stainless steel hardware makes this body virtually corrosion proof.

The TS 904 features the Stellar air starter pack, a 20 hp Koehler gas engine w/elec. start, 600 amp DC startall, 30' cables, 25 CFM at 100 PSI air compressor. Package includes protective back gate and a 30-gallon air receiver which is mounted under the rear of the truck.



The Stellar Model EDL-54 hydraulic cylinder powered liftgate can lift loads up to 1,300-pounds. For those applications where a liftgate is not desired, an attractive steel pickup style tailgate is available with a rear step bumper and body-mounted hand grab rails.

The driver side compartment is designed to accept numerous shelving and storage options. The TS 904 can also be set up to have the left side as your primary working side. Shown is the 3 shelf/tray package 40-gallon diesel fuel pumping system w/meter and fuel hose.

Designed & Manufactured in the USA

Service



Stellar Air/Starter Pack

The TS 904 Tire Service Truck features a Stellar Air/Starter Pack. The starter pack includes the following features:

- Stellar Model 600 amp DC Start-All with 12-volt nominal, 600 amp cranking capacity; 24-volt nominal, 250 amp cranking capacity.
- Two sets of 30-foot long welding cable with 500 amp clamps.
- 20 HP 4-cycle cast iron Kohler gasoline-powered engine with low oil shutdown.
- Stellar model SUH-43A air-cooled compressor. producing 25 CFM @ 100 psi.
- 30-gallon capacity truck-mounted air receiver.
- 1/2" hose reel with 50-foot of 1/2" hose.
- 3/8" hose reel with 30-foot of 3/8" hose.
- Combination air filter, lubricator, and air regulator plumbed with the air hose reels.

904 Service Body Features

- The entire inner structure of the 904 is constructed of aluminum. Which makes the body virtually corrosionproof.
- The exterior is constructed of fiberglass with one solid gel coat color impregnated into the fiberglass to provide a long lasting, durable finish.
- The 904 can carry ten 11.00 x 24.5 truck tires in the load bed.
- The front compartments can be fitted with three (3)
 adjustable shelves. Durable plastic parts bins designed
 to fit the shelves are available to provide an organized
 storage system to store patches, valve stems, and other
 consumable service items.
- The 904 loadbed is a full 49.5-inches wide and features ribbed aluminum side walls and floor for added strength and durability.
- The 904 utilizes four (4) tool compartments to give you 56 cubic feet of tool storage. That's approximately 25 cubic feet more storage than competitive models!

Direct Hydraulic Liftgate Features

- Electric-hydraulic liftgate with 1300-pound capacity.
- Side loading rail and tire stop.
- Hydraulic lift cylinder.
- 27-inch loading platform raises on an arc to prevent bumping of the rear body.
- Maintenance-free, oil-impregnated bronze bushings.









190 State Street Garner, Iowa 50438 1-800-321-3741 Fax: 641-923-2812

E-mail: sales@tiretruck.com www.tiretruck.com Designed & Manufactured in the U.S.A.

*Specifications may change without notification. Copyright © 2003 Stellar Industries, Inc.