


## FLINTFAST™ #12 FASTENERS

### Product Information



**Description:** FlintFast Fasteners from CertainTeed are engineered to provide top quality performance with commercial roofing systems and designed to increase strength and improve application efficiency. Fasteners are used in roofing applications for the attachment of roofing insulation (FlintBoard™) and base sheets.

**Uses:** Exclusive tapered wedge entry and sharp drill point for fast, strong application in steel and wood substrates. FlintFast #12 Fasteners are not for use in concrete decks. Available in lengths from 1-5/8" to 8".

### Technical Data

13 single lead threads per inch

Typical pullout in 22 ga. steel deck: 450 lbs.

Standard #3 Phillips Truss Head

Back-out resistance

EPX™ epoxy coating exceeds FM4470 corrosion standards

Approvals: Factory Mutual, Miami-Dade



### Product Application

Eye protection must be worn. Install using 2500 RPM variable speed drill. Do not over or under drive.

Steel decks: penetrate 3/4" minimum

Wood decks: penetrate 1" minimum

### Packaging

| Screw Length | Pieces per Pail | Pails per Pallet | Approx. Weight per Pallet (lbs.) |
|--------------|-----------------|------------------|----------------------------------|
| 1-5/8"       | 1000            | 80               | 912                              |
| 2-1/4"       | 1000            | 80               | 1,200                            |
| 2-7/8"       | 1000            | 80               | 1,480                            |
| 3-1/4"       | 1000            | 80               | 1,624                            |
| 3-3/4"       | 1000            | 80               | 2,000                            |
| 4-1/2"       | 1000            | 80               | 2,208                            |
| 5"           | 1000            | 80               | 2,424                            |
| 6"           | 1000            | 80               | 2,872                            |
| 7"           | 500             | 80               | 1,696                            |
| 8"           | 500             | 80               | 1,876                            |

Driver included in each pail