


# Technical Product Data

## FLINTFAST™#14 **HEAVY DUTY FASTENERS**

### **Product** Information





Uses: For tougher jobs, low profile head provides positive driving, while sharp drill point and exclusive tapered wedge entry allow fast, strong application. Available in lengths from 1-1/2" to 12".

#### Technical Data

13 single lead threads per inch

Typical pullout in 22 ga. steel deck: 550 lbs.

Typical pullout in structural concrete 1" embedment: 740 lbs.

Standard #3 Phillips Truss Head

Back-out resistance

EPX<sup>™</sup> epoxy coating exceeds FM4470 corrosion standards

Approvals: Factory Mutual, Miami-Dade





## **Product Application**

Eye protection must be worn. Install using 2500 RPM variable speed drill. Do not over or under drive.

Steel decks: penetrate 3/4" minimum

Wood decks: into or through deck 1" minimum Concrete decks: penetrate 1" minimum

#### **Packaging**

Screw Length	Pieces per Pail	Pails per Pallet	Approx. Weight per Pallet (lbs.)
1-1/2"	1000	80	1,032
2"	1000	80	1,240
2-1/2"	1000	80	1,552
3	1000	80	1,896
3-1/2"	1000	80	2,256
4"	1000	80	2,392
4-1/2"	1000	80	2,688
5"	1000	80	2,984
6, 7, 8, 9"	500	80	1,760; 2,308; 2,372; 2,628;
10, 11, 12"	500	80	3,040; 3,308; 3,472
Driver included in each pail			



www.certainteed.com

750 East Swedesford Rd. P.O. Box 860 Valley Forge, PA 19482 (610) 341-7000

Sales Support Group 800-233-8990

West Region 6400 Stevenson Blvd. Fremont, CA 94538 800-955-0811 510-438-0271 fax

South Region 5525 MacArthur Blvd. Suite 900 Irving, TX 75038 800-333-ROOF (7663) 419-499-4337 fax 972-580-5645 fax

**Lake Central Region** 11519 US Route 250 North Milan, OH 44846 800-432-9256

North Region Riverbridge Industrial Center 800 W. Front Street Chester, PA 19013 866-297-ROOF (7663) 610-874-6170 fax