TAKE A LOOK AT WHAT ABATEMENT TECHNOLOGIES HAS HATCHED UP FOR YOU NOW...

Introducing the NEW PRED600 MINI-PREDATOR®. The world's lightest and smallest portable air scrubber. Take a look at these MINI-PREDATOR features:

INCREDIBLY LIGHTWEIGHT AND COMPACT

Weighs just 34 lbs., including filters; about <u>10 pounds</u> <u>lighter</u> than any other PAS.

POWERFUL

Variable-speed airflow, rated at 200 to 600 cfm.

SPECIAL CABINET RESIN

Cabinets made from a high-density polyethylene resin that contains microbial growth and UV inhibitors. And, the Tefgard™ finish is easy to clean and decontaminate.

EFFECTIVE FILTRATION

Comes with two pre-filters and a <u>True 99.97% HEPA filter</u>. Vapor-Lock® carbon pre-filter is optional.

ECONOMICAL TO OPERATE

You save money because filters last longer and cost less.

SECURE STACKING

Multiple units nest securely together, to save space when stacked in a warehouse, a van, or on the job. They can even run when stacked.

LOW AMPERAGE DRAW

Up to five units can be safely daisy-chained on one 15amp circuit (total current draw <12amps)

SAFETY FIRST

ETL-certified to meet UL and CSA standards for electrical safety and flammability.

Order Now and Save

Take advantage of special introductory Mini-Predator pricing by ordering now. Call us today to learn more.







United States: 800.634.9091 Canada: 800.827.6443 www.abatement.com Phone 678.889.4200 Fax 678.889.4201

SPECIFICATIONS AND FEATURES OF THE MINI-PREDATOR

NET WEIGHT WITH FILTERS:

34 pounds

SHIPPING WEIGHT:

39 pounds

DIMENSIONS (LxWxH):

24"L x 18"W x 19 1/2"H

POWER SUPPLY REQUIREMENTS:

120 volts AC, 60Hz, 15 amps

NORMAL OPERATING AMPS:

2.0 amps or less (Daisy-chain up to 5 units on one 15Amp

circuit)

MOTORIZED IMPELLER:

185 watt motorized impeller with thermal overload protec-

tion, auto re-set, 60Hz, single phase

CIRCUIT BREAKER:

12 amp

OPERATIONAL SOUND LEVEL:

62 - 68 dBA, reading taken at 5 feet

CABINET MATERIAL:

UL94HP flame retardant resin with EPA-Registered micro-

bial inhibitor

TRANSPORTABILITY:

Sturdy 10" long, tubular carry handle

PRE-FILTER ACCESS:

Easy-operating hinged door secured by rotating latches

to protect against filter by-pass

FILTERS:

First Stage pre-filter - 1" coarse particulate pre-filter Second stage pre-filter - 2" pleated particulate pre-filter

Optional second stage pre-filter - 2" high capcaity carbon filter

True HEPA filter - Tested and certified to an efficiency of









United States: 800.634.9091 Canada: 800.827.6443 www.abatement.com Phone 678.889.4200 Fax 678.889.4201