

## FLINTLASTIC® FR CAP T SHEET

### MINERAL SURFACED, FIRE RESISTANT, SBS MODIFIED BITUMEN FIBER GLASS CAP SHEET

#### Product Information

**Product Use:** FLINTLASTIC FR Cap T Sheet is a fire rated, glass mat cap sheet used in two-ply or multi-layer modified bitumen fire rated roofing systems. It is designed for use as a cap sheet over inorganic and organic built-up roofing systems. It may also be used as a heavy-duty, venting type base sheet when installed mineral side down and either mechanically fastened or spot mopped over lightweight insulating concrete decks or existing smooth surfaced membranes. FLINTLASTIC FR Cap T Sheet is suitable for both new construction and reroofing membranes over a variety of substrates. It is surfaced with ceramic granules to provide a durable, heat reflective weathering surface when used as a cap sheet. FLINTLASTIC FR Cap T Sheet is reinforced with a tough fibrous glass fabric.

**Limitations:** FLINTLASTIC FR Cap T Sheet is intended for torch application. Rolls should be stored upright, off ground, completely protected from the weather. Roof decks shall be structurally sound, dry, smooth and meet or exceed minimum requirements of the deck manufacturer, local code and CertainTeed. Additional specifications and precautions are contained in the CertainTeed Commercial Roof Systems Specification Manual.

**Product Composition and Features:** FLINTLASTIC FR Cap T Sheet is reinforced with a durable, high quality fiber glass mat which receives a heavy coating of weathering grade rubberized asphalt. FLINTLASTIC FR Cap T Sheet is manufactured on state-of-the-art, dedicated roofing lines that were exclusively designed for the production of modified bitumen roofing membrane.

**Roll Size:** 39 $\frac{3}{8}$ " X 33' 11"

**Coverage\*:** One square

(\*When applied according to CertainTeed's specification)

**Approximate Weight:** 100 lbs. per roll

**Top Surface:** Ceramic Granules

**Back Surface:** Mineral Release Agent

**Applicable Standards:** FLINTLASTIC FR CAP T is approved by Underwriters Laboratories for use in various Class A, B, and C roof assemblies. Consult CertainTeed, UL, ICC, F.M., Miami-Dade, FBC, LA RR, or TDI for details. Meets ASTM D6163, Grade G, Type I.

#### Technical Data

**Modified Bitumen Coating:** Non-oxidized (flux) asphalt, blended with a compatible elastomeric styrene-butadiene-styrene polymer and selected inert fillers.

<u>Test Description</u>	<u>Test Method</u>	<u>Results*</u>
Softening Point:	ASTM D36	260°F
Tensile Strength:	ASTM D5147	
	@ 73.4 +/- 3.6°F MD/XD	65/40 lbs./in.
	@ 0 +/- 3.6°F MD/XD	110/90 lbs./in.
Elongation:	ASTM D5147	
	@ 73.4 +/- 3.6°F MD/XD	4%/4%
	@ 0 +/- 3.6°F MD/XD	4%/4%
Dimensional Stability:	ASTM D5147 MD/XD	0.1/0.1 Max
Low Temperature Flex:	ASTM D5147	Pass @ -20°F
Compound Stability:	ASTM D5147	250°F
Thickness:	ASTM D5147	4.0mm (140 mils)
Tear Strength:	ASTM D5147	
	@ 73.4 +/- 3.6°F MD/XD	120/95 lbs.

**\*NOTE: Published results are nominal production values confirmed by independent laboratory testing.**

## **Product Application**

FLINTLASTIC FR Cap T Sheet roof systems must be applied in accordance with installation procedures contained in the CertainTeed Commercial Roof Systems Specification Manual. The following information is intended for general information purposes only and is not all-inclusive.

**Preparation:** Substrates to receive a roof system shall be firmly attached, smooth, dry, clean and free of depressions and sharp projections. Substrates requiring priming shall be primed with asphalt primer such as FlintPrime™ and be allowed to completely dry. Substrates shall provide positive drainage. Roof insulation shall be tapered to drains.

**Installation:** Unless otherwise specified by CertainTeed, a CertainTeed approved base sheet shall be installed with 3" sidelaps and 4" endlaps, with endlaps diagonally staggered not less than 3 feet apart. The base sheet shall be mechanically fastened to nailable substrates, and torched to non-nailable or insulated substrates as specified in the CertainTeed Commercial Roof Systems Specification Manual. Over the base ply, torch one ply of FLINTLASTIC FR Cap T Sheet lapping 4¼" on sides and 6" on ends with endlaps diagonally staggered not less than 3 feet apart. Sides and endlaps shall be inspected to ensure a minimum 3/8" flow of modified compound has been achieved. Refer to the CertainTeed Commercial Roof Systems Specification Manual for additional specifications.

**Precautions:** Cold weather applications require special handling to prevent damage to the rolls and to ensure satisfactory installation. Do not apply roofing systems over improperly prepared substrates or substrates which contain moisture. Follow all safety recommendations relating to the use and maintenance of liquid propane gas torches and equipment. Refer to the CertainTeed Commercial Roof Systems Specification Manual for additional safety information.

**Maintenance:** CertainTeed Commercial Roof Systems do not require any additional maintenance beyond normal roof maintenance procedures. CertainTeed recommends regular roof maintenance and inspection to determine the condition of drains, flashings and other similar items, and to prolong the life expectancy of the roof system.

## **Warranties**

CertainTeed offers a number of different types of Roof Membrane Warranties designed to meet the building owner's specific requirements. Please contact your nearest CertainTeed office for additional information and requirements.

## **Technical Assistance and Services**

CertainTeed provides technical assistance in the design, selection, specification and application guidelines of FLINTLASTIC Roof Systems. Architectural and field representatives are available for consultation within each region.

For more information, contact CertainTeed's Customer Support at 800-233-8990, or the CertainTeed regional offices listed below.



[www.certainteed.com](http://www.certainteed.com)

750 East Swedesford Rd.  
P.O. Box 860  
Valley Forge, PA 19482  
(610) 341-7000

**Sales Support Group**  
800-233-8990

**West Region**  
6400 Stevenson Blvd.  
Fremont, CA 94538  
800-955-0811  
510-438-0271 fax

**South Region**  
5525 MacArthur Blvd.  
Suite 900  
Irving, TX 75038  
800-333-ROOF (7663)  
972-580-5645 fax

**Lake Central Region**  
11519 US Route 250 North  
Milan, OH 44846  
800-432-9256  
419-499-4337 fax

**North Region**  
Riverbridge  
Industrial Center  
800 W. Front Street  
Chester, PA 19013  
866-297-ROOF (7663)  
610-874-6170 fax