# Brass Craft<sub>®</sub>



# Brass Craft.

## A Safer, More Dependable Gas Connector

Combine the large diameter gas connector with a Safety+PLUS® large demand excess flow valve to provide a safer gas connection for your home and family. The patented Safety+PLUS large demand excess flow valve restricts gas flow to the appliance in the event of a gas line rupture or disconnection downstream of the valve. Gas flow is immediately restricted to a non-hazardous level (bypass flow) to avert the potential for a dangerous release of gas into the home. The valve will not reset until the gas line is properly repaired. Only once the line is repaired, the bypass flow pressurizes the gas line automatically resetting the valve to restore normal gas flow to the appliance.



### **Superior Corrosion Resistance**

BrassCraft's proprietary ProCoat coating resists corrosion from harsh household cleaning, plumbing repair and masonry products such as bleach, ammonia, solder flux and muriatic acid. ProCoat coating helps protect the stainless steel core from pinhole leaks and deterioration resulting from prolonged exposure to residue and vapors from these products. Approved for indoor and outdoor use, the ProCoat coating resists the harsh effects of UV rays and salt.



#### Greater Flexibility

Manufactured from high-tensile strength stainless steel with deeper corrugations, BrassCraft connectors are less susceptible to work hardening and provide greater flexibility.

#### 100% Leak Tested

Each gas connector is factory leak tested prior to coating application to provide 100% core protection.

#### Approved for Indoor/Outdoor Use

ProCoat coating resists the harsh effects of UV rays and salt (road and sea).

# CSSB

### **ProCoat® Large Diameter Gas Connectors** (List Price Ea.)

CONNECTORS	Part #	Description	24"	30"	36"	48"	60"	72"
	CSSB1412	7/8" O.D. (3/4" I.D.) 1" F.I.P. x 1" M.I.P.	63.62		74.51	96.31	118.66	
	CSSB21	7/8" O.D. (3/4" I.D.) 3/4" F.I.P. x 3/4" M.I.P.	55.32	61.83	64.80	83.74	103.18	115.19
	CSSB22	7/8" O.D. (3/4" I.D.) 3/4" F.I.P. x 3/4" F.I.P.	55.32	61.83	64.80	83.74	103.18	115.19
		Straight Length Capacity (BTU Per Hour)	290,900	270,500	255,900	215,000	197,400	173,900
		Approx. Carton Wt. Lbs.	11	12	13	8	9	10
		Carton Qty.	10	10	10	5	5	5











215 North Smith Avenue Corona, California 92880-1791 (951) 278-5140 FAX: (951) 278-5193 39600 Orchard Hill Place Novi, Michigan 48375-5331 (248) 305-6000 (248) 305-6011 35 Currah Road St. Thomas, Ontario N5P 3R2 (519) 633-0340 FAX: (519) 633-0777