

WATER SUPPLY STOPS

1/4 TURN G2 SureConnect™ STOP

Use:	¼-turn supply stop for potable water distribution systems.
Sizes:	See catalog for specific configurations.
Operating Pressure:	125 psi maximum
Operating Temperature:	40 - 150°F Maximum continuous use temperature: 115°F
<i>Note: Not intended for recirculating water systems that produce continuous use temperatures above 115°F. For those applications, use BrassCraft KT series ball stops.</i>	
Material Specifications:	<p>Body and brass components – Chrome Plated C36000 Brass</p> <p>Stem – Barrel - Santoprene</p> <p style="padding-left: 40px;">Shaft - Glass Filled Polypropylene</p> <p>Stem O-Ring - EPDM</p> <p>Retainer O-Ring – EPDM (straight valves)</p> <p>Retainer – Glass Filled Polyphthalamide (straight valves)</p> <p>Handle - Zinc Die Cast</p> <p>Handle Screw - Zinc Plated Steel</p> <p>Compression Sleeve – C36000 Brass</p> <p>SureConnect™ O-Ring – Viton</p> <p>SureConnect™ O-Ring – Nitrile</p> <p>SureConnect™ O-Ring Spacer – Nylon</p> <p>Housing – Glass Filled Nylon</p> <p>Housing Retainer – Glass Filled Nylon</p> <p>Anti-Rotation Disk – C36000 Brass</p> <p>Inner Spacer – C36000 Brass</p>
Designed and Manufactured In Accordance With:	<p>By IAPMO to ASME A112.18.1-2005</p> <p>By CSA to CSA-B125-05</p> <p>By CSA to NSF 61 Section 9</p>
Approvals/Listings:	<p>IAPMO File #0645</p> <p>CSA Approved – File #0204593</p>

This technical product data sheet and all information contained herein is the confidential and exclusive property of BrassCraft Manufacturing, and shall not be disclosed to others without the written consent of BrassCraft. This technical product data sheet must be returned to BrassCraft if requested.

Tech. Product Data Sheet Number	© BrassCraft Mfg.	Revision Level
800.47	Page 1 of 1	(A)

WATER CONNECTORS

1/4 Turn G2 SureConnect™ SPEEDI ONE PLUS

Use:	For use with potable hot & cold water. Sink riser, water closet and dishwasher installations. ¼-turn supply stop for potable water distribution systems.
Sizes:	A variety of end fittings with lengths from 16 to 72 inches. See catalog for specific combinations.
Operating Pressure:	125 psi maximum
Operating Temperature:	40 - 150°F Maximum continuous use temperature: 115°F
<i>Note: Not intended for recirculating water systems that produce continuous use temperatures above 115°F. For those applications, use BrassCraft KT series ball stops.</i>	
Material Specifications:	<p>Body and brass components – C36000 Brass Stem – Barrel - Santoprene Shaft - Glass Filled Polypropylene Stem O-Ring - EPDM Retainer O-Ring – EPDM (straight valves) Retainer – Glass Filled Polythalamide (straight valves) Handle - Zinc Die Cast Handle Screw - Zinc Plated Steel Compression Sleeve – C36000 Brass</p> <p>SureConnect™ O-Ring – Viton SureConnect™ O-Ring – Nitrile SureConnect™ O-Ring Spacer – Nylon Housing – Glass Filled Nylon Housing Retainer – Glass Filled Nylon Anti-Rotation Disk – C36000 Brass Inner Spacer – C36000 Brass</p> <p>Bell Escutcheon – Nick Chrome Plated Low Carbon Steel</p> <p>Speedi-Plumb PLUS™ Nut – C36000 or Polypropylene End Fitting – C36000 Brass Inner Core – PVC Washer – Nitrile</p>
Designed and Manufactured In Accordance With:	By IAPMO to ASME A112.18.1 By CSA to CSA-B125 By CSA to NSF 61 Section 9
Approvals/Listings:	IAPMO File #0645 CSA Approved – File #0204593

This technical product data sheet and all information contained herein is the confidential and exclusive property of BrassCraft Manufacturing, and shall not be disclosed to others without the written consent of BrassCraft. This technical product data sheet must be returned to BrassCraft if requested.

Tech. Product Data Sheet Number	© BrassCraft Mfg.	Revision Level
800.48	Page 1 of 1	(A)

WATER SUPPLY STUB-OUTS

1/4 TURN G2 SureConnect™ STUB-OUT - COPPER

Use:	For use with SureConnect™ Stops.
Sizes:	See Catalog for specific sizes and configurations
Operating Pressure:	N/A
Operating Temperature:	N/A
Material Specifications:	Copper Stub-out - C12200 Copper Plastic Cap Cap – Polyphthalamide O-Ring – EPDM Spacer – Glass Filled Nylon
Designed and Manufactured In Accordance With:	By CSA to ASME A112.18.1-2005, ASTM F1807 and ASTM F1960-05 By CSA to CSA-B1256.1-05 and B137.5 By CSA to NSF61 Section 9
Approvals/Listings:	CSA Approved File #150436

This technical product data sheet and all information contained herein is the confidential and exclusive property of BrassCraft Manufacturing, and shall not be disclosed to others without the written consent of BrassCraft. This technical product data sheet must be returned to BrassCraft if requested.

Tech. Product Data Sheet Number	© BrassCraft Mfg.	Revision Level
800.49	Page 1 of 1	(A)

WATER SUPPLY STUB-OUTS

1/4 TURN G2 SureConnect™ STUB-OUT - CPVC

Use:	For use with SureConnect™ Stops.
Sizes:	See Catalog for specific sizes and configurations
Operating Pressure:	N/A
Operating Temperature:	N/A
Material Specifications:	Stub-out – CPVC 23447-B Plastic Cap Cap – Polyphthalamide O-Ring – EPDM Spacer – Glass Filled Nylon
Designed and Manufactured In Accordance With:	By CSA to ASTM D2846/D2846M By CSA to CSA-B137.6-05 By CSA to NSF61 Section 9
Approvals/Listings:	CSA Approved File #150436

This technical product data sheet and all information contained herein is the confidential and exclusive property of BrassCraft Manufacturing, and shall not be disclosed to others without the written consent of BrassCraft. This technical product data sheet must be returned to BrassCraft if requested.

Tech. Product Data Sheet Number	© BrassCraft Mfg.	Revision Level
800.50	Page 1 of 1	(A)

WATER SUPPLY STOPS

1/4 TURN G2 SureConnect™ TEST CAP

Use:	For use with SureConnect™ Stops
Sizes:	N/A
Operating Pressure:	125 psi maximum
Operating Temperature:	40 - 150°F
Material Specifications:	<p>Cap - C36000 Brass</p> <p>SureConnect™ O-Ring – Viton</p> <p>SureConnect™ O-Ring – Nitrile</p> <p>SureConnect™ O-Ring Spacer – Nylon</p> <p>Housing – Glass Filled Nylon</p> <p>Housing Retainer – Glass Filled Nylon</p>
Designed and Manufactured In Accordance With:	By CSA to NSF61 Section 9
Approvals/Listings:	CSA Approved – File #0204593

This technical product data sheet and all information contained herein is the confidential and exclusive property of BrassCraft Manufacturing, and shall not be disclosed to others without the written consent of BrassCraft. This technical product data sheet must be returned to BrassCraft if requested.

Tech. Product Data Sheet Number	© BrassCraft Mfg.	Revision Level
800.51	Page 1 of 1	(A)

WATER SUPPLY STUB-OUTS

1/4 TURN G2 SureConnect™ STUB-OUT Engineered Plastic – PEX Crimp

Use:	For use with SureConnect™ Stops.
Sizes:	See Catalog for specific sizes and configurations
Operating Pressure:	N/A
Operating Temperature:	N/A
Material Specifications:	PEX Crimp Stub-out – Solvay Acudel 22000 BK937 Polyphenylsulfone Plastic Cap Cap – Polyphthalamide O-Ring – EPDM Spacer – Glass Filled Nylon
Designed and Manufactured In Accordance With:	By IAPMO to ASME A112.18.1-2005/CSA B125.1-05 By IAPMO to NSF61, 2007 Section 9
Approvals/Listings:	IAPMO File: #0645

This technical product data sheet and all information contained herein is the confidential and exclusive property of BrassCraft Manufacturing, and shall not be disclosed to others without the written consent of BrassCraft. This technical product data sheet must be returned to BrassCraft if requested.

Tech. Product Data Sheet Number	© BrassCraft Mfg.	Revision Level
800.52	Page 1 of 1	(A)

WATER SUPPLY STUB-OUTS

1/4 TURN G2 SureConnect™ STUB-OUT Engineered Plastic – Cold Expansion

Use:	For use with SureConnect™ Stops.
Sizes:	See Catalog for specific sizes and configurations
Operating Pressure:	N/A
Operating Temperature:	N/A
Material Specifications:	Cold Expansion Stub-out – Solvay Udel GF-120 Polysulfone Plastic Cap Cap – Polyphthalamide O-Ring – EPDM Spacer – Glass Filled Nylon
Designed and Manufactured In Accordance With:	By IAPMO to ASME A112.18.1-2005/CSA B1256.1-05 By IAPMO to NSF61, 2007 Section 9
Approvals/Listings:	IAPMO File: #0645

This technical product data sheet and all information contained herein is the confidential and exclusive property of BrassCraft Manufacturing, and shall not be disclosed to others without the written consent of BrassCraft. This technical product data sheet must be returned to BrassCraft if requested.

Tech. Product Data Sheet Number	© BrassCraft Mfg.	Revision Level
800.53	Page 1 of 1	(A)