NEC MultiSync® LCD195VX+/ Matrox Analog DualHead2Go Bundle

Dual 19" desktop LCDs / Analog graphics expansion module



Increase your productivity with the 19" NEC MultiSync LCD195VX+/Matrox DualHead2Go bundle (LCD195VX+BK-DA), an easy-to-implement solution that helps you get more done in less time. Combining two feature-rich LCD monitors and an analog graphics expansion module, this bundle delivers all of the benefits of a dual-display configuration in one simple solution.

matrox

DualHead2Go

Matrox DualHead2Go, the first in the Matrox series of GXMs (Graphics eXpansion Modules) is a palm-sized box which sits outside a notebook or desktop computer and offers dual display support to a system via external connectivity. Unlike with a new graphics card, this patent pending technology delivers multi-display capability without requiring users to open their computer and insert parts into it.







Bundle Features & Benefits

External graphics expansion module connectivity makes for an easy dual-display setup without the need for installing components into your computer

Dual-display configuration expands the desktop for increased productivity

Height-adjustable stand adds flexibility and comfort to your viewing preferences

Ambix dual-input technology allows for digital/analog compatibility with upgraded video cards and software as well as connection to two systems

Enhanced cable management helps prevent unattractive, space-consuming wire clutters

Rapid Response technology delivers virtually uninterrupted, undistorted viewing of high-speed, full-motion video

Model	MultiSync LCD195VX+
Display Viewable Image Size Pixel Pitch Pixels Per Inch Brightness (typical) Contrast Ratio (typical) Viewing Angle (typical) Response Time (typical) Display Colors	19" 0.294mm 86 @ native resolution 270 cd/m² 600:1 170° Vert., 170° Hor. (85U/85D/85L/85R) (CR > 5) Rapid Response (5ms) More than 16 million
Inputs	DVI-D and VGA 15 pin D-sub
Resolutions Supported	720 x 400 @ 70 Hz 640 x 480 @ 60-75 Hz 800 x 600 @ 56-75 Hz 832 x 624 @ 75 Hz 1024 x 768 @ 60-75 Hz 1152 x 864 @ 70-75 Hz 1152 x 870 @ 75 Hz 1280 x 960 @ 60-75 Hz 1280 x 1024 @ 60-75 Hz
Native Resolution	1280 x 1024 @ 60 Hz
Additional Features	Thin-frame (bezel), height-adjustable stand, tilt, No Touch Auto Adjust, cable management, touchscreen-compatible, AccuColor color control, digital smoothing, digital controls, DDC/CI, NaViSet software, Plug and Play (VESA DDC 1/2B), VESA DPMS power management, OSD user controls, ISO 13406-2 Class II, Windows Vista-certified
Power Consumption (typical) On Power Savings Mode	37W 2W
Dimensions (W x H x D) Net (with stand) Net (without stand)	16 x 15.2-17.2 x 9.4 in. / 405.5 x 385.8-435.8 x 240mm 16 x 13.6 x 2.6 in. / 405.5 x 345.5 x 66.5mm
Weight Net (with stand) Net (without stand)	13.2 lbs. /6 kg 11 lbs. /5 kg
Limited Warranty	3 years parts and labor, including backlight
Technical Support	M - F (7am - 7pm CST)

