





# Refrigeration Fan Motors, Single Phase, PSC

Open Air Over, Resilient Ring & Thru-Bolt Mount

**Applications:** Replacement motor for refrigeration equipment.

- Features:**
- Open end bracket
  - Ball Bearings
  - Automatic reset thermal protector
  - BX connector included in frame (except on Catalog # X262)
  - Catalog # X263 and X264 have 12" cord and molded plug
  - UL Recognized and CSA Certified
  - **Capacitor included (except on Catalog # X262 and X426)**



HP	RPM	VOLTS	FRAME	CAT. NO.	MODEL NO.	LIST PRICE	MULT. SYMB.	F.L. AMPS	APPROX. WGT. LBS.	FRAME LENGTH	SHAFT DIM.	FOOT NOTES
1/6	1625	208-230	48Y	X269 *	48A17O147	\$187	F1	1.2	11	5.00	1/2 x 1 1/2	15
1/4	1625	208-230	48Y	X270 *	48A17O149	\$201	F1	1.9	12	5.69	1/2 x 2 1/2	16
	1075	208-230	48Y	X263	48A11O11041	\$161	F1	2.0	11	4.25	1/2 X 3 3/4	16
	1075	208-230	48Y	X262 *	48A11D245	\$169	F1	1.8	12	7.25	1/2 x 1 5/8	67,69,82
	1075	460	48Y	X264 *	48A11O11040	\$164	F1	0.8	11	4.50	1/2 X 3 3/4	d, 16
1/3	1625	208-230	48YZ	X230 *	48A17O136	\$168	F1	1.8	15	5.69	1/2 x 3 1/2	15
	1075	208-230	48YZ	X268 *	48A11O1239	\$206	F1	3.0	14	5.69	1/2 x 2 1/2	15
3/4	1075	460	48YZ	X426 *	48A11O1375	\$251	F1	2.2	19	6.38	5/8 X 4 1/2 w/key	67,69

\* Stock Model

# Refrigeration Fan Motors, Three Phase

Open Air Over, Shaft Up & Horizontal Rigid Base Mount

**Applications:** Replacement motor for refrigeration equipment.

- Features:**
- Enclosed shaft end bracket, vented frame
  - Continuous duty, air over
  - Automatic reset thermal protector
  - Shaft slinger
  - Threaded lead exit
  - 60°C ambient
  - Nameplated 60/50 hertz  
190/380 volts, at next lower HP
  - Double sealed ball bearings
  - Flat and keyway on shaft
  - Patented VCD, Voltage Change Device
  - Ball Bearings
  - UL Recognized and CSA Certified



HP	RPM	VOLTS	FRAME	CAT. NO.	MODEL NO.	LIST PRICE	MULT. SYMB.	F.L. AMPS	APPROX. WGT. LBS.	FRAME LENGTH	SHAFT DIM.	FOOT NOTES
1/2	850	208-230/460	56HZ	X529 *	56T8O5531	\$480	F1	2.9-3.0/1.5	39	9.62	5/8 X 5	VC,5
1	850	208-230/460	56HZ	X528 *	56T8O5306	\$539	F1	5.1-5.3/2.65	46	10.62	5/8 X 5	VC,5
	850	208-230/460	56Y	X507 *	56T8O5302	\$524	F1	5.3-5.3/2.6	46	12.00	5/8 X 5	VC
1 1/2	1140	208-230/460	56HZ	X523 *	56T11O5306	\$440	F1	5.45-5.4/2.7	38	11.00	5/8 X 5	VC,5
	850	208-230/460	56HZ	X531 *	56T8O15504	\$586	F1	7.0-7.0/3.5	48	11.50	5/8 X 5	VC,5
2	1140	208-230/460	56HZ	X525 *	56T11O5310	\$476	F1	7.2-6.8/3.4	40	12.00	5/8 X 5	VC,5


\* Stock Model

**Footnotes:**

- d Will become build-up item when current stock is gone
- VC Voltage Change Device feature for quick voltage changes
- 5 56H, 143T, AND 145T Combination Base with 12 mounting holes
- 15 Fixed CW Rotation, viewing opposite shaft (or lead end) of motor
- 16 Fixed CCW Rotation, viewing opposite shaft (or lead end) of motor
- 67 Capacitor not included, see Accessory Section
- 69 50°C Ambient
- 82 Welded Rigid Base

# Unit Heater, Single Phase, PSC

Totally Enclosed Air Over, Resilient Base



**Applications:** Replacement motors for unit heaters. Air over motors need to be mounted within the airstream for proper cooling.

- Features:**
- Totally enclosed
  - Direct drive, air over
  - Ball Bearings
  - Horizontal or vertical mount
  - Weather resistant reversing plug
  - BX connector mounted in frame
  - 1" Extended thru-bolts
  - 48Y Frame has non-standard BA dimension
  - Automatic reset thermal protection
  - UL Recognized and CSA Certified
  - **Capacitor included**

HP	RPM	VOLTS	FRAME	CAT. NO.	MODEL NO.	LIST PRICE	MULT. SYMB.	F.L. AMPS	APPROX. WGT. LBS.	FRAME LENGTH	SHAFT DIM.	FOOT NOTES
<b>1/6</b>	1625	115	48Y	X305 *	48A17T2001	\$153	F1	2.0	13	4 3/4	1/2 x 2 3/4	
	1625	115	48Y	X301 *	48A17T72	\$136	F1	2.0	13	5 1/4	1/2 x 2 3/4	
	1075	115	48Y	X306 *	48A11T2005	\$158	F1	3.0	13	4 3/4	1/2 x 2 3/4	
	1075	115	48Y	X302 *	48A11T199	\$141	F1	3.0	12	4 3/4	1/2 x 2 3/4	
<b>1/4</b>	1075	115	48Y	X307 *	48A11T2006	\$166	F1	4.1	15	4 3/4	1/2 x 2 3/4	
	1075	115	48Y	X303 *	48A11T198	\$149	F1	4.1	14	4 3/4	1/2 x 2 3/4	
<b>1/3</b>	1075	115	48Y	X304 *	48A11T201	\$166	F1	6.5	21	6	1/2 x 2 3/4	
	1075	115	48Y	X308 *	48A11T2007	\$183	F1	6.5	20	6	1/2 x 2 3/4	

\* Stock Model

HVAC

# Water Circulator Replacement Motors, Single Phase

Drip-proof, Resilient Ring Mount



**Applications:** Direct replacements for Taco hot water circulators.

- Features:**
- Economical split phase design
  - Quiet sleeve bearing construction
  - 48Z frame with 1/2" diameter shaft, 1" long without flat
  - 1.40 Service Factor
  - Fixed CCW rotation, viewed opposite shaft end
  - Ball Bearings
  - UL Recognized and CSA Certified

HP	RPM	VOLTS	FRAME	OVER LOAD	CAT. NO.	MODEL NO.	LIST PRICE	MULT. SYMB.	SERVICE FACTOR	F.L. AMPS	APPROX. WGT. LBS.	"C" DIM.	FOOT NOTES
<b>1/12</b>	1800	115	48YZ	AUTO	X700*	48S17D2102	\$108	F1	1.4	2.7	10	7.22	
<b>1/8</b>	1800	115	48Y	AUTO	X701*	48S17D1084	\$117	F1	1.4	3.0	11	8.84	

\* Stock Model