

6.4" SMARTPAD LCD VIDEO TOUCHPANEL

The SPLCD64V combines video display with the convenience and simple operation of a self-contained touchpanel controller. Its 640 x 480 resolution, with 64K color, provides outstanding graphics and a remarkable video image, which may be displayed full screen, or as picture-in-picture.

- Touchpanel controller with video display
- Fully customizable display graphics
- Video image may be displayed full-screen, or PiP mode
- Stand-alone device can output IR and/or RS232 commands
- Internal pre-programmed IR code library, as well as capability to learn IR commands
- Built-in IR receiver
- SPLCDPS1 Power Supply required (p38)
- Front panel IR learning eye
- Integrated Macronizer executes long macros without errors

Order: SPLCD64VW



Speaks Dragon

6.4" SMARTPAD LCD GRAPHIC TOUCHPANEL

- Stand-alone device can output IR and/or RS232 commands
- Fully customizable display graphics
- XDT Station feedback, and XMUSIC song title navigation
- Internal pre-programmed IR code library, as well as capability to learn IR commands
- Built-in IR code library
- Built-in IR receiver
- SPLCDPS1 Power Supply required (p38)
- Front panel IR learning eye
- Fully compatible with the MRC88/MRAUDIO8X8 Controllers with bi-directional status indication

Order: SPLCD64GW



Speaks Dragon

3.9" SMARTPAD LCD GRAPHIC TOUCHPANEL

- Stand-alone device can output IR and/or RS232 commands
- Fully customizable display graphics
- XDT Station feedback, and XMUSIC song title navigation
- Internal pre-programmed IR code library, as well as capability to learn IR commands
- Built-in IR code library
- Built-in IR receiver
- SPLCDPS1 Power Supply required (p38)
- Front panel IR learning eye
- Fully compatible with the MRC88/MRAUDIO8X8 Controllers

with bi-directional status indication

Order: SPLCD39GW



Speaks Dragon

RACK MOUNT FOR SPLCD39

For applications requiring 19" rack mounting of SPLCD39

Order: CSPLCD39RMP

RACK MOUNT FOR SPLCD64

For applications requiring 19" rack mounting of SPLCD64

Order: CSPLCD64RMP

DESKTOP MOUNT FOR SPLCD39

For applications requiring desktop mounting of SPLCD39

Order White: DTMLCD39W

Order Black: DTMLCD39B



DESKTOP MOUNT FOR SPLCD64

For applications requiring desktop mounting of SPLCD64

Order White: DTMLCD64W

Order Black: DTMLCD64B



SMARTPAD LCD CONNECTING BLOCK

- Allows integration of SPLCD SmartPad LCD™ Controllers into an existing IR network
 - 12 VDC Regulated output for standard Xantech IR Receivers
 - 16 VDC output for SPLCD Touchpanel Controllers
 - 10 amplified IR emitter ports
 - Requires SPLCDPS1 or SPLCDPS4 Power Supply
- Order: SPLCDCB100**



SMARTPAD LCD POWER SUPPLY

- Steady, regulated, 16V DC, 800 mA power supply for a single SPLCD Touchpanel Controllers
 - Available in 120VAC-60 Hz or 240VAC-50 Hz
- Order: SPLCDPS1**

HIGH CURRENT SMARTPAD LCD POWER SUPPLY

- Steady, regulated, 16V DC, 3.12A power supply for multiple Touchpanel Controllers
 - Available in 120VAC-60 Hz or 240VAC-50 Hz
 - Powers up to four SPLCD SmartPad LCD™ Controllers
- Order: SPLCDPS4**

RS422 TO RS232 MODULE

- Connects to the Serial I/O port on SPLCD Controllers
 - Converts RS422 from SPLCD to RS232 output to control a RS232 device
 - Converts RS232 from a control device to RS422 to control a SPLCD
 - Allows control from up to 4000 feet away via CAT5 cable
- Order: RS422232**



RS232 EXPANSION MODULE

- RS232 Serial Port Extender/ Hub
- Order: XOVP14**