

REGAL-BELOIT SpinMaster® AC Adjustable Speed Drives

Volts/Hertz Constant Torque, Micro Inverter

Applications: Constant torque or constant horsepower applications. Typical applications include conveyors, packaging machinery, machine tool, printing equipment, and specialty equipment.

- Features:**
- Current limit to 180% with frequency foldback
 - Adjustable carrier frequency
 - Independent accel and decel adjustment
 - Adjustable DC injection braking
 - Programmable inputs
 - Fixed boost for high starting torque
 - UL Listed and UL Certified for Canada under File No. E197830
 - IP20 enclosure
 - Unlimited lead length with microMAX™, Black Max® or Blue Max®, AC motor
 - 2 year warranty



REGAL-BELOIT
SpinMaster®

AC DRIVES

Single Phase Input / Three Phase Output

HP / kW	INPUT VOLTAGE	INPUT AMPS	OUTPUT AMPS 230 VAC	CAT. NO.	LIST PRICE	MULT. SYMB.	APPROX. WGT. LBS.	HEIGHT	WIDTH	DEPTH	FOOT NOTES
								IN / MM	IN / MM	IN / MM	
.33 / .25	120	6.8	1.7	T201★	\$345	D3	1.5	5.75/146	3.66/93	3.26/83	
.5 / .37	120	9.2	2.4	T202★	\$375	D3	1.5	5.75/146	3.66/93	3.26/83	
1 / .75	120	16.6	4.2	T204★	\$498	D3	2.7	5.75/146	4.52/115	4.88/124	
1.5 / 1.1	120	24.0	6.0	T205★	\$565	D3	3.0	5.75/146	4.52/115	4.88/124	

★ Stock Model

Single Phase Input / Three Phase Output

HP / kW	INPUT VOLTAGE	INPUT AMPS	OUTPUT AMPS	CAT. NO.	LIST PRICE	MULT. SYMB.	APPROX. WGT. LBS.	HEIGHT	WIDTH	DEPTH	FOOT NOTES
								IN / MM	IN / MM	IN / MM	
.33 / .25	208/240	3.9/3.4	1.9/1.7	T211★	\$320	D3	2.0	5.75/146	3.66/93	3.26/83	d
.5 / .37	208/240	5.8/5.0	2.8/2.4	T212★	\$337	D3	2.0	5.75/146	3.66/93	3.26/83	
.75 / .55	208/240	6.9/6.0	3.7/3.2	T213	\$356	D3	2.6	5.75/146	3.66/93	3.63/92	
1 / .75	208/240	10.6/9.2	4.8/4.2	T214★	\$375	D3	3.6	5.75/146	3.66/93	3.63/92	
1.5 / 1.1	208/240	13.9/12.0	6.9/6.0	T215★	\$452	D3	4.0	5.75/146	4.52/115	4.88/124	
2 / 1.5	208/240	18.4/16.0	8.1/7.0	T216★	\$530	D3	4.1	5.75/146	4.52/115	4.88/124	
3 / 2.2	208/240	24.0/21.0	11.0/9.6	T217★	\$624	D3	4.9	5.75/146	4.52/115	5.53/140	

★ Stock Model

Three Phase Input / Three Phase Output

HP / kW	INPUT VOLTAGE	INPUT AMPS	OUTPUT AMPS	CAT. NO.	LIST PRICE	MULT. SYMB.	APPROX. WGT. LBS.	HEIGHT	WIDTH	DEPTH	FOOT NOTES
								IN / MM	IN / MM	IN / MM	
.5 / .37	208/240	3.1/2.7	2.8/2.4	T222★	\$320	D3	1.4	5.75/146	3.66/93	3.26/83	
1 / .75	208/240	5.8/5.1	4.8/4.2	T224★	\$355	D3	1.7	5.75/146	3.66/93	3.63/92	
1.5 / 1.1	208/240	8.0/6.9	6.9/6.0	T225★	\$422	D3	2.4	5.75/146	3.66/93	5.56/141	
2 / 1.5	208/240	9.1/7.9	8.1/7.0	T226★	\$481	D3	2.5	5.75/146	3.66/93	5.56/141	
3 / 2.2	208/240	12.4/10.8	11.0/9.6	T227★	\$533	D3	3	5.75/146	4.52/115	5.53/140	
5 / 3.7	208/240	19.6/17.1	17.5/15.2	T228★	\$680	D3	4.6	5.75/146	4.52/115	6.74/171	96
7.5 / 5.5	208/240	28.0/25.0	25.0/22.0	T229	\$939	D3	7.3	7.75/197	5.76/147	7.18/182	96
10 / 7.5	208/240	34.0/32.0	30.0/28.0	T220	\$1,167	D3	7.5	7.75/197	5.76/147	7.18/182	96
15 / 11	208/240	54.0/48.0	48.0/42.0	T221	\$1,720	D3	13.0	9.75/248	7.68/195	8.00/203	96
.5 / .37	480	1.4	1.1	T232★	\$427	D3	2.0	5.75/146	3.66/93	3.94/100	
1 / .75	480	2.5	2.1	T234★	\$457	D3	2.4	5.75/146	3.66/93	4.74/120	
1.5 / 1.1	480	3.6	3.0	T235★	\$496	D3	2.9	5.75/146	3.66/93	5.74/146	
2 / 1.5	480	4.0	3.4	T236★	\$529	D3	3.1	5.75/146	3.66/93	5.74/146	
3 / 2.2	480	5.4	4.8	T237★	\$581	D3	3.2	5.75/146	4.52/115	5.74/146	
5 / 3.7	480	8.8	7.8	T238★	\$695	D3	4.6	5.75/146	4.52/115	6.74/171	96
7.5 / 5.5	480	12.4	11	T239	\$903	D3	7.2	5.75/146	4.52/115	6.74/171	96
10 / 7.5	480	15.8	14	T230	\$1,167	D3	7.5	7.75/197	5.76/147	7.18/182	96
15 / 11	480	24.0	21	T231	\$1,272	D3	8.0	7.75/197	5.76/147	7.18/182	96

Footnotes:

- d Will become build-up item when current stock is gone
- 96 Drive has cooling fan

★ Stock Model

REGAL-BELOIT SpinMaster® Plus AC Adjustable Speed Drives

Volts/Hertz Constant Torque, Micro Inverter



REGAL-BELOIT
SpinMaster® plus

Applications: Constant torque or constant horsepower applications. Typical applications include conveyors, packaging machinery, machine tool, printing equipment, and specialty equipment.

- Features:**
- Current limit to 180% with frequency foldback
 - Adjustable carrier frequency
 - Independent accel and decel adjustment
 - RS-485 Communications
 - Adjustable DC injection braking
 - Programmable inputs
 - MODBUS protocol
 - Fixed boost for high starting torque
 - UL Listed and UL Certified for Canada under File No. E197830
 - IP20 enclosure
 - Unlimited lead length with microMAX™, Black Max® or Blue Max®, AC motor
 - 2 year warranty

Single or Three Phase Input / Three Phase Output

HP / kW	INPUT PHASE	INPUT VOLTAGE	INPUT AMPS	OUTPUT AMPS	CAT. NO.	LIST PRICE	MULT. SYMB.	APPROX. WGHT. LBS.	HEIGHT	WIDTH	DEPTH	FOOT NOTES
									IN / MM	IN / MM	IN / MM	
.25 / .20	1	208/240	3.6/3.2	1.6/1.4	T310★	\$507	D3	1.9	5.75/146	3.66/93	3.94/100	
	3		1.9/1.7									
.5 / .37	1	208/240	5.4/4.7	2.5/2.2	T312★	\$529	D3	1.9	5.75/146	3.66/93	3.94/100	
	3		3.1/2.7									
1 / .75	1	208/240	10.6/9.2	4.8/4.2	T314	\$570	D3	2.5	5.75/146	3.66/93	4.74/120	
	3		5.8/5.1									
1.5 / 1.1	1	208/240	13.9/12.0	6.9/6.0	T315	\$677	D3	3.5	5.75/146	4.52/115	5.24/133	
	3		8.0/6.9									
2 / 1.5	1	208/240	14.8/12.9	7.8/6.8	T316	\$749	D3	4.5	5.75/146	4.52/115	6.74/171	
	3		9.1/7.9									
3 / 2.2	1	208/240	19.7/17.1	11.0/9.6	T317	\$910	D3	4.8	5.75/146	4.52/115	6.74/161	96
	3		12.4/10.8									
5 / 3.7	1	208/240	29/26	17.5/15.2	T318★	\$1,247	D3	7.6	7.75/197	5.78/147	7.18/182	96
	3		19.6/17.1									

★ Stock Model

Three Phase Input / Three Phase Output

HP / kW	INPUT VOLTAGE	INPUT AMPS	OUTPUT AMPS	CAT. NO.	LIST PRICE	MULT. SYMB.	APPROX. WGHT. LBS.	HEIGHT	WIDTH	DEPTH	FOOT NOTES
								IN / MM	IN / MM	IN / MM	
1 / 0.75	208/240	5.8/5.1	4.8/4.2	T324★	\$525	D3	2.5	5.75/146	3.66/93	4.74/120	
1.5 / 1.1	208/240	8.0/6.9	6.9/6.0	T325★	\$618	D3	3	5.75/146	3.66/93	5.74/146	
2 / 1.5	208/240	9.1/7.9	7.8/6.8	T326★	\$681	D3	3.1	5.75/146	3.66/93	5.74/146	96
3 / 2.2	208/240	12.4/10.8	11.0/9.6	T327★	\$812	D3	3.2	5.75/146	3.66/93	5.74/146	96
5 / 3.7	208/240	19.6/17.1	17.5/15.2	T328★	\$1,045	D3	4.6	5.75/146	4.52/115	6.74/171	96
7.5 / 5.5	208/240	28.0/25.0	25.0/22.0	T329★	\$1,427	D3	7.3	7.75/197	5.78/147	7.18/182	96
10 / 7.5	208/240	34.0/32.0	30.0/28.0	T330★	\$1,705	D3	7.5	7.75/197	5.78/147	7.18/182	96
15 / 11	208/240	54.0/48.0	48.0/42.0	T331★	\$2,209	D3	13	9.75/248	7.68/195	8.00/203	96
20 / 15	208/240	65.0/61.0	58.0/54.0	T333	\$2,710	D3	13.5	9.75/248	7.68/195	8.00/203	96

★ Stock Model

Continued on next page.

Footnotes:

96 Drive has cooling fan

REGAL-BELOIT SpinMaster® Plus AC Adjustable Speed Drives

Volts/Hertz Constant Torque, Micro Inverter

Three Phase Input / Three Phase Output

HP / kW	INPUT VOLTAGE	INPUT AMPS	OUTPUT AMPS	CAT. NO.	LIST PRICE	MULT. SYMB.	APPROX. WGHT. LBS.	HEIGHT	WIDTH	DEPTH	FOOT NOTES
								IN / MM	IN / MM	IN / MM	
.5 / .37	480	1.4	1.1	T332★	\$591	D3	1.9	5.75/146	3.66/93	3.94/100	
1 / .75	480	2.5	2.1	T334★	\$637	D3	2.4	5.75/146	3.66/93	4.74/120	
1.5 / 1.1	480	3.6	3.0	T335★	\$696	D3	2.9	5.75/146	3.66/93	5.74/146	
2 / 1.5	480	4.0	3.4	T336★	\$768	D3	3.1	5.75/146	3.66/93	5.74/146	
3 / 2.2	480	5.4	4.8	T337★	\$858	D3	3.2	5.75/146	3.66/93	5.74/146	96
5 / 3.7	480	8.6	7.6	T338★	\$1,094	D3	4.6	5.75/146	4.52/115	6.74/171	96
7.5 / 5.5	480	12.4	11.0	T339★	\$1,427	D3	7.2	7.75/197	5.78/147	7.18/182	96
10 / 7.5	480	15.8	14.0	T340★	\$1,705	D3	7.5	7.75/197	5.78/147	7.18/182	96
15 / 11	480	24.0	21.0	T341★	\$2,166	D3	13.3	9.75/248	7.68/195	8.00/203	96
20 / 15	480	31.0	27.0	T342★	\$2,652	D3	13.5	9.75/248	7.68/195	8.00/203	96
25 / 18.5	480	38.0	34.0	T343★	\$3,156	D3	13.8	9.75/248	7.68/195	8.00/203	96
30 / 22.4	480	45.0	40.0	T344	\$3,669	D3	14.5	9.75/248	7.68/195	8.00/203	96
1 / 0.75	575	2.0	1.7	T354	\$681	D3	2.4	5.75/146	3.66/93	4.74/120	
2 / 1.5	575	3.5	3.0	T356	\$816	D3	3.1	5.75/146	3.66/93	5.74/146	
3 / 2.2	575	4.7	4.2	T357	\$969	D3	4.1	5.75/146	4.52/115	6.74/171	
5 / 3.7	575	7.4	6.6	T358	\$1,185	D3	4.7	5.75/146	4.52/115	6.74/171	96
7.5 / 5.5	575	11.2	9.9	T359	\$1,539	D3	7.1	7.75/197	5.78/147	7.18/182	96
10 / 7.5	575	13.7	12.2	T360	\$1,824	D3	7.4	7.75/197	5.78/147	7.18/182	96
15 / 11	575	22.0	19.0	T361	\$2,389	D3	13.3	9.75/248	7.68/195	8.00/203	96
20 / 15	575	27.0	24.0	T362	\$2,922	D3	13.5	9.75/248	7.68/195	8.00/203	96
25 / 18.5	575	31.0	27.0	T363	\$3,456	D3	13.8	9.75/248	7.68/195	8.00/203	96

★ Stock Model

Footnotes:

96 Drive has cooling fan

REGAL-BELOIT SpinMaster® VMax AC Adjustable Speed Drives

Sensorless Vector Constant Torque, Micro Inverter



REGAL-BELOIT
SpinMaster® VMax

Applications: Constant torque or constant horsepower applications. Typical applications include conveyors, packaging machinery, machine tool, printing equipment, and specialty equipment.

- Features:**
- Current limit to 200% with frequency foldback
 - Full output torque at 1Hz
 - Auto Tuning
 - Independent accel and decel adjustment
 - Adjustable DC injection braking
 - Programmable inputs/outputs
 - UL Listed and UL Certified for Canada under File No. E197830
 - IP20 enclosure
 - Unlimited lead length with microMAX™, Black Max® or Blue Max®, AC motor
 - 2 year warranty

Single or Three Phase Input / Three Phase Output

HP / kW	INPUT PHASE	INPUT VOLTAGE	INPUT AMPS	OUTPUT AMPS	CAT. NO.	LIST PRICE	MULT. SYMB.	APPROX. WGHT. LBS.	HEIGHT	WIDTH	DEPTH	FOOT NOTES
									IN / MM	IN / MM	IN / MM	
.5 / .37	1	208/240	5.4/4.7	2.5/2.2	T2112★	\$532	D3	2	5.75/146	3.64/93	3.94/100	
	3		3.1/2.7									
1 / .75	1	208/240	10.6/9.2	4.8/4.2	T2114★	\$599	D3	2.5	5.75/146	3.64/93	4.74/120	
	3		5.8/5.1									
1.5 / 1.1	1	208/240	13.9/12.0	6.9/6.0	T2115★	\$711	D3	3.5	5.75/146	4.52/115	5.24/133	
	3		8.0/6.9									
2 / 1.5	1	208/240	14.8/12.9	7.8/6.8	T2116★	\$786	D3	4.5	5.75/146	4.52/115	6.74/171	
	3		9.1/7.9									
3 / 2.2	1	208/240	19.7/17.1	11.0/9.6	T2117★	\$956	D3	5	5.75/146	4.52/115	6.74/161	96
	3		12.4/10.8									

★ Stock Model

Three Phase Input / Three Phase Output

HP / kW	INPUT VOLTAGE	INPUT AMPS	OUTPUT AMPS	CAT. NO.	LIST PRICE	MULT. SYMB.	APPROX. WGHT. LBS.	HEIGHT	WIDTH	DEPTH	FOOT NOTES
								IN / MM	IN / MM	IN / MM	
1 / 0.75	208/240	5.8/5.1	4.8/4.2	T2214★	\$551	D3	2.5	5.75/146	3.66/93	4.74/120	
1.5 / 1.1	208/240	8.0/6.9	6.9/6.0	T2215★	\$649	D3	3	5.75/146	3.66/93	5.74/146	
2 / 1.5	208/240	9.1/7.9	7.8/6.8	T2216★	\$715	D3	3.1	5.75/146	4.52/115	6.74/171	96
3 / 2.2	208/240	12.4/10.8	11.0/9.6	T2217★	\$853	D3	3.2	5.75/146	4.52/115	6.74/171	96
5 / 3.7	208/240	19.6/17.1	17.5/15.2	T2218★	\$1,097	D3	4.6	5.75/146	4.52/115	6.74/171	96
7.5 / 5.5	208/240	28.0/25.0	25.0/22.0	T2219★	\$1,498	D3	7.3	7.75/197	5.78/147	7.18/182	96
10 / 7.5	208/240	34.0/32.0	30.0/28.0	T2220★	\$1,790	D3	7.5	7.75/197	5.78/147	7.18/182	96
.5 / 0.37	480	1.4	1.1	T2412★	\$621	D3	1.9	5.75/146	3.66/93	4.74/120	
1 / 0.75	480	2.5	2.1	T2414★	\$669	D3	2.4	5.75/146	3.66/93	4.74/120	
1.5 / 1.1	480	3.6	3.0	T2415★	\$731	D3	2.9	5.75/146	3.66/93	5.74/146	
2 / 1.5	480	4.0	3.4	T2416★	\$806	D3	3.1	5.75/146	3.66/93	5.74/146	96
3 / 2.2	480	5.4	4.8	T2417★	\$901	D3	3.2	5.75/146	3.66/93	5.74/146	96
5 / 3.7	480	8.8	7.6	T2418★	\$1,149	D3	4.6	5.75/146	4.52/115	6.74/171	96
7.5 / 5.5	480	12.4	11.0	T2419★	\$1,498	D3	7.2	7.75/197	5.78/147	7.18/182	96
10 / 7.5	480	15.8	14.0	T2420★	\$1,790	D3	7.5	7.75/197	5.78/147	7.18/182	96
1 / 0.75	575	2.0	1.7	T2514★	\$715	D3	2.4	5.75/146	4.52/115	5.24/133	
2 / 1.5	575	3.5	3.0	T2516★	\$857	D3	3.1	5.75/146	4.52/115	6.74/171	
3 / 2.2	575	4.7	4.2	T2517★	\$1,017	D3	4.1	5.75/146	4.52/115	6.74/171	96
5 / 3.7	575	7.4	6.6	T2518★	\$1,244	D3	4.7	5.75/146	4.52/115	6.74/171	96
7.5 / 5.5	575	11.2	9.9	T2519★	\$1,616	D3	7.1	7.75/197	5.76/147	7.18/182	96
10 / 7.5	575	13.7	12.2	T2520★	\$1,915	D3	7.4	7.75/197	5.76/147	7.18/182	96

★ Stock Model

Footnotes:

96 Drive has cooling fan

REGAL-BELOIT SpinMaster®, SpinMaster® Plus and SpinMaster® VMax AC Adjustable Speed Drives

Product Feature Directory

FEATURE DESCRIPTION	SpinMaster®	SpinMaster® Plus	SpinMaster® VMAX
GENERAL DESIGN FEATURES			
RATINGS & SPECIFICATIONS			
INPUT VOLTAGE / HP RANGE 1Ø 20 Vac (+10%,-15%) 1Ø or 3 Ø 208/240 Vac 3 Ø 400/480 Vac 3 Ø 480/590 Vac	0.33 - 1.5 Hp (0.25 - 1.1 kW) 0.33 - 15 Hp (0.25 - 11 kW) 0.5 - 15 Hp (0.37 - 11 kW) N/A	N/A 0.25 - 20Hp (0.18 - 15kW) 0.5 - 30 Hp (0.37 - 22 kW) 1 - 25Hp (0.75 - 18.5kW)	N/A 0.5 - 10 Hp (0.37 - 7.5 kW) 0.5 - 10 Hp (0.37 - 7.5 kW) 0.5 - 10 Hp (0.37 - 7.5 kW)
OUTPUT FREQUENCY	0 - 240 Hz	0 - 240 Hz (1000 Hz option)	0 - 240 Hz
CARRIER FREQUENCY	4kHz to 10kHz (2kHz steps)	4kHz to 10kHz (2kHz steps)	2kHz, 4kHz, & 8kHz
OVERLOAD CAPACITY (60 SECONDS)	150%	150%	150%
TORQUE RATING	CONSTANT / 10:1	CONSTANT / 10:1	CONSTANT / 2000:1
DRIVE TYPE	V/Hz	V/Hz	VECTOR (sensorless)
AMBIENT TEMPERATURE	0 - 40°C	0 - 50°C	0 - 50°C
ENCLOSURE TYPES			
IP20 (CHASSIS)	STANDARD	STANDARD	STANDARD
COOLING	CONVECTION or HEAT SINK FAN	CONVECTION or HEAT SINK FAN	CONVECTION or HEAT SINK FAN
PERFORMANCE FEATURES			
PI SETPOINT CONTROL	N/A	OPTION	N/A
SLIP COMPENSATION	STANDARD	STANDARD	STANDARD
REVERSE ROTATION	STANDARD	STANDARD	STANDARD
DC INJECTION BRAKING UP TO 30% VOLTAGE	UP TO 3600 SECONDS	UP TO 3600 SECONDS	UP TO 999.9 SECONDS
2nd ADJUSTABLE ACCEL/DECEL	STANDARD	STANDARD	STANDARD
2nd STOP COMMAND (e.g. FAST STOP)	STANDARD	STANDARD	STANDARD
RE-START INTO SPINNING MOTOR	STANDARD	STANDARD	STANDARD
BIPOLAR SPEED REFERENCE	N/A	N/A	STANDARD
INPUT/OUTPUT INTERFACE AND OTHER FEATURES			
SPEED REFERENCE INPUTS			
KEYPAD	STANDARD	STANDARD	STANDARD
POTENTIOMETER	STANDARD	STANDARD	STANDARD
4 - 20mA	STANDARD	STANDARD	STANDARD
0 - 10 VDC	STANDARD	STANDARD	STANDARD
MOTOR OPERATED POT (MOP)	STANDARD	STANDARD	STANDARD
PRESET SPEEDS	7	7	7
ANALOG OUTPUTS			
0 - 10 VDC: SPEED or LOAD	N/A	STANDARD	STANDARD
2 - 10 VDC: SPEED or LOAD*	N/A	STANDARD	STANDARD
DIGITAL OUTPUTS			
PROGRAMMABLE STATUS INDICATIONS (e.g. RUN, FAULT, AT SPEED, etc.)	STANDARD	STANDARD	STANDARD
RELAY OUTPUTS	1 (Form A)	N/A	N/A
OPEN-COLLECTOR OUTPUTS	1	2	2
12 VDC POWER SUPPLY FOR AUX. RELAY	STANDARD	STANDARD	STANDARD
KEYPAD & DISPLAY FUNCTIONS			
DISPLAY TYPE	3 DIGIT LED	3 DIGIT LED	3 DIGIT LED
FREQUENCY (SPEED) DISPLAY	STANDARD	STANDARD	STANDARD
MOTOR LOAD DISPLAY	STANDARD	STANDARD	STANDARD
MOTOR VOLTAGE DISPLAY	STANDARD	STANDARD	STANDARD
DC BUS VOLTAGE DISPLAY	STANDARD	STANDARD	STANDARD
SERIAL COMMUNICATIONS			
RS - 232	N/A	N/A	N/A
RS - 485	N/A	STANDARD	STANDARD
MODBUS PROTOCOL	N/A	STANDARD	STANDARD
CONTROL I/O	11 ISOLATED TERMINALS	18 ISOLATED TERMINALS	18 ISOLATED TERMINALS
REMOTE KEYPAD (NEMA 4X)	OPTION	OPTION	OPTION
DYNAMIC BRAKING	OPTION	OPTION	OPTION
EPM PROGRAMMER COMPATIBLE	STANDARD	STANDARD	STANDARD

* 2 - 10 VDC signals can be converted to 4 - 20 mA by adding series resistance such that the total circuit resistance is 500 ohms.

Items in **BOLD BLUE** indicate key product differences.


REGAL-BELOIT SpinMaster®, SpinMaster® Plus, and SpinMaster® VMax AC Adjustable Speed Drives

Micro Inverter Accessories / Options



Electronic Programming Unit

Electronic Programming Unit allows off-line setup and replication of the drive's plug-in electronic programming module. Keypad input and alphanumeric display employ programming. RS-232 serial port allows downloading of configuration files from personal computer.



Remote Keypad

Remote keypad kit includes 8 foot connecting cable and gasket. When mounted in the proper enclosure, will provide up to NEMA 4X protection. Remote keypads are not interchangeable between drives.

CAT. NO.	DESCRIPTION	LIST PRICE	MULT. SYMB.	APPROX. WGT. LBS.
T915★	EPM programmer	\$729	D3	2

★ Stock Model

CAT. NO.	DESCRIPTION	LIST PRICE	MULT. SYMB.	APPROX. WGT. LBS.
T920★	Remote keypad SpinMaster®	\$152	D3	2
T921★	Remote keypad SpinMaster® Plus	\$187	D3	2
T922★	Remote keypad SpinMaster® VMax	\$208	D3	2

★ Stock Model



DIN Rail Mounting Kits

Steel plates and fasteners for mounting AC drives on standard 35 mm DIN rails for panel building. Set of 6.

CAT. NO.	DESCRIPTION	LIST PRICE	MULT. SYMB.	APPROX. WGT. LBS.
T900★	DIN rail mounting kits for 3.66" width drives and dynamic braking modules	\$132	D3	3
T901★	DIN rail mounting kits for 3.66" or 4.52" width drives and dynamic braking modules	\$166	D3	3
T902★	DIN rail mounting kits for 5.78" width drives and dynamic braking modules	\$198	D3	3

★ Stock Model



EPM Bulk Pack

Plug-in electronic programming modules (EPM) allows off-line setup and replication of program using electronic programming unit. Set of 10.

CAT. NO.	DESCRIPTION	LIST PRICE	MULT. SYMB.	APPROX. WGT. LBS.
T916★	EPM bulk pack	\$142	D3	1

★ Stock Model

AC Drive Options

Add the suffix Letter to the SpinMaster® Plus Catalog#. (Available on the SpinMaster® Plus series as a build-up **ONLY**)

DESCRIPTION	PART # SUFFIX ADD TO SMP CAT NO.	LIST PRICE ADDER
PI Set-point Control Function	P	\$70
High Frequency Output (1000 Hz)	V	\$70


Continued on next page.

REGAL-BELOIT SpinMaster®, SpinMaster® Plus, and SpinMaster® VMax AC Adjustable Speed Drives

Micro Inverter Accessories / Options

Dynamic Braking Module

Dynamic braking modules through 10 HP, includes brake resistors and the control electronics in a convenient package. Modules can be panel or DIN rail mounted.



HP	CAT. NO.	VOLTAGE	LIST PRICE	MULT. SYMB.	APPROX. WGT. LBS.
.25 - .50	T931★	208/240	\$233	D3	2
1 - 1.5	T933★	208/240	\$272	D3	3
2 - 3	T935★	208/240	\$370	D3	4
5	T936★	208/240	\$482	D3	5
7.5	T937	208/240	\$609	D3	6
10	T938	208/240	\$735	D3	8
.25 - .50	T941★	480	\$233	D3	2
1 - 1.5	T943★	480	\$272	D3	3
2 - 3	T945★	480	\$370	D3	4
5	T946★	480	\$482	D3	5
7.5	T947	480	\$609	D3	6
10	T948	480	\$735	D3	8
1 - 1.5	T953★	575	\$272	D3	3
2 - 3	T955★	575	\$370	D3	4
5	T956★	575	\$482	D3	5
7.5	T957	575	\$609	D3	6
10	T958	575	\$735	D3	8

★ Stock Model

Dynamic Braking Modules*

HP	CAT. NO.	VOLTAGE	LIST PRICE	MULT. SYMB.	APPROX. WGT. LBS.
15 - 20	T939	208/240	\$314	D3	10
15 - 30	T949	480	\$314	D3	10
15 - 25	T959	575	\$314	D3	10

*Dynamic braking resistors are sold and mounted separately.

Dynamic Braking Resistors**

HP	CAT. NO.	VOLTAGE	LIST PRICE	MULT. SYMB.	APPROX. WGT. LBS.
15 - 20	T969	208/240	\$345	D3	1
15 - 20	T969	480	\$345	D3	1
15 - 20	T970	575	\$345	D3	1
25 - 30	T971	480	\$583	D3	1
25 - 30	T972	575	\$583	D3	1

**Dynamic braking resistors are provided with mounting brackets.

Dynamic Braking Module Sizes

HP	HEIGHT	WIDTH	DEPTH
	IN/MM	IN/MM	IN/MM
.25 - 1.5	4.6/117	3.1/79	3.1/79
2 - 3	4.6/117	3.1/79	4.3/109
5	4.6/117	3.1/79	5.6/142
7.5 - 10	4.6/117	4.2/107	6.7/170
15 - 30	4.6/117	3.1/79	3.1/79

REGAL-BELOIT SpinMaster® Micro AC Adjustable Speed Drives

Constant Torque, NEMA 1 Inverter



REGAL-BELOIT
SpinMaster®

Applications: Constant torque or constant horsepower applications. Typical applications include conveyors, packaging machinery, machine tool, printing equipment, and specialty equipment.

- Features:**
- NEMA 1 enclosure with epoxy finish
 - Current limit to 180% with frequency foldback
 - Adjustable carrier frequency
 - Independent accel and decel times
 - Adjustable DC injection braking
 - Serial Communication interface
 - Programmable inputs/outputs
 - UL Listed and UL Certified for Canada under File No. E197830
 - 2 year warranty

Single Phase Input / Three Phase Output

HP / kW	INPUT VOLTAGE	INPUT AMPS	OUTPUT AMPS 200 / 230 VAC	CAT. NO.	LIST PRICE	MULT. SYMB.	APPROX. WGT. LBS.	HEIGHT	WIDTH	DEPTH	FOOT NOTES
								IN / MM	IN / MM	IN / MM	
0.25 / 0.19	120/240	6.0/3.0	1.4	T1110★	\$757	D3	5	7.50/190	4.70/119	3.33/85	
0.50 / 0.38	120/240	9.2/4.6	2.2	T1112★	\$914	D3	7	7.50/190	6.12/3.63	3.63/92	
1 / 0.75	120/240	16.2/8.1	4.0	T1114★	\$921	D3	7	7.50/190	6.12/3.63	4.22/107	
1.5 / 1.1	120/240	21/10.4	5.2	T1115★	\$1,020	D3	7	7.50/190	6.12/3.63	4.22/107	
2 / 1.5	240	14.9	6.8	T1116★	\$973	D3	9	7.50/190	6.12/3.63	5.12/130	
3 / 2.2	240	21.0	9.6	T1117★	\$1,072	D3	9	7.50/190	6.12/3.63	5.12/130	

★ Stock Model

Three Phase Input / Three Phase Output

HP / kW	INPUT VOLTAGE	INPUT AMPS	OUTPUT AMPS	CAT. NO.	LIST PRICE	MULT. SYMB.	APPROX. WGT. LBS.	HEIGHT	WIDTH	DEPTH	FOOT NOTES
								IN / MM	IN / MM	IN / MM	
0.50 / 0.38	208/240	3.1/2.7	2.5/2.2	T1212★	\$801	D3	6	7.50/190	4.70/119	3.63/92	
1 / 0.75	208/240	5.5/4.8	4.6/4.0	T1214★	\$842	D3	6	7.50/190	4.70/119	4.33/110	
1.5 / 1.1	208/240	7.1/6.2	6.0/5.2	T1215★	\$882	D3	6	7.50/190	4.70/119	4.33/110	
2 / 1.5	208/240	9.3/8.1	7.8/6.8	T1216★	\$943	D3	9	7.50/190	6.12/3.63	5.12/130	
3 / 2.2	208/240	12.9/11.3	11.0/9.6	T1217★	\$1,014	D3	9	7.50/190	6.12/3.63	5.12/130	
5 / 3.7	208/240	20.4/17.7	17.5/15.2	T1218★	\$1,198	D3	11	7.88/200	6.12/3.63	5.94/151	
7.5 / 5.5	208/240	29.9/26.0	25.3/22.0	T1219★	\$1,731	D3	13	9.38/238	7.86/200	6.84/174	96
10 / 7.5	208/240	36.8/32.0	32.2/28.0	T1220★	\$2,295	D3	15	11.25/286	7.86/200	6.84/174	96
15 / 11	208/240	55.2/48.0	48.3/42.0	T1221	\$3,028	D3	19	12.75/324	7.86/200	6.84/174	96
20 / 15	208/240	70.0/61.0	62.0/54.0	T1222★	\$4,110	D3	21	12.75/324	10.26/261	7.74/197	96
25 / 18.5	208/240	89.0/77.0	78.0/68.0	T1223	\$4,977	D3	38	15.75/400	10.26/261	8.35/212	96
30 / 22	208/240	104/90.0	92.0/80.0	T1224	\$5,973	D3	44	15.75/400	10.26/261	8.35/212	96
1 / 0.75	480	2.4	2.0	T1414★	\$1,011	D3	6	7.50/190	4.70/119	3.63/92	
2 / 1.5	480	4.1	3.4	T1416★	\$1,109	D3	7	7.50/190	6.12/3.63	4.22/107	
3 / 2.2	480	5.7	4.8	T1417★	\$1,198	D3	9	7.50/190	6.12/3.63	5.12/130	
5 / 3.7	480	8.9	7.6	T1418★	\$1,347	D3	9	7.50/190	6.12/3.63	5.12/130	
7.5 / 5.5	480	12.8	11.0	T1419★	\$1,831	D3	11	9.38/238	7.86/200	6.25/159	
10 / 7.5	480	15.9	14.0	T1420★	\$2,487	D3	13	9.38/238	7.86/200	6.84/174	96
15 / 11	480	24.0	21.0	T1421★	\$3,195	D3	15	11.25/286	7.86/200	6.84/174	96
20 / 15	480	31.0	27.0	T1422★	\$4,240	D3	17	12.75/324	7.86/200	6.84/174	96
25 / 18.5	480	38.0	34.0	T1423	\$4,999	D3	21	12.75/324	10.26/261	7.74/197	96
30 / 22	480	45.0	40.0	T1424★	\$5,443	D3	21	12.75/324	10.26/261	7.74/197	96
40 / 30	480	59.0	52.0	T1425	\$6,273	D3	35	15.75/400	10.26/261	8.35/212	96
50 / 37.5	480	74.0	65.0	T1426	\$7,647	D3	44	19.75/502	10.26/261	8.55/217	96
60 / 44	480	87.0	77.0	T1427	\$8,400	D3	44	19.75/502	10.26/261	8.55/217	96

★ Stock Model

Footnotes:

96 Drive has cooling fan

Continued on next page.

REGAL-BELOIT SpinMaster® Micro AC Adjustable Speed Drives

Constant Torque, NEMA 1 Inverter

Three Phase Input / Three Phase Output

HP / kW	INPUT VOLTAGE	INPUT AMPS	OUTPUT AMPS	CAT. NO.	LIST PRICE	MULT. SYMB.	APPROX. WGT. LBS.	HEIGHT	WIDTH	DEPTH	FOOT NOTES
								IN / MM	IN / MM	IN / MM	
1 / 0.75	575	1.9	1.6	T1514★	\$1,120	D3	6	7.50/190	4.70/119	3.63/92	
2 / 1.5	575	3.3	2.7	T1516★	\$1,238	D3	7	7.50/190	6.12/3.63	4.22/107	
3 / 2.2	575	4.6	3.9	T1517★	\$1,369	D3	9	7.50/190	6.12/3.63	5.12/130	
5 / 3.7	575	7.1	6.1	T1518★	\$1,491	D3	9	7.88/200	7.86/200	5.94/151	
7.5 / 5.5	575	10.5	9.0	T1519	\$1,824	D3	11	9.38/238	7.86/200	6.25/159	
10 / 7.5	575	12.5	11.0	T1520	\$2,779	D3	13	9.38/238	7.86/200	7.40/188	96
15 / 11	575	19.3	17.0	T1521	\$3,670	D3	17	12.75/324	7.86/200	6.84/174	96
20 / 15	575	25.0	22.0	T1522	\$4,661	D3	19	12.75/324	7.86/200	7.40/188	96
25 / 18.5	575	31.0	27.0	T1523	\$5,505	D3	21	12.75/324	10.26/261	7.74/197	96
30 / 22	575	36.0	32.0	T1524	\$6,021	D3	22	12.75/324	10.26/261	8.25/210	96
40 / 30	575	47.0	41.0	T1525	\$6,837	D3	38	15.75/400	10.26/261	8.35/212	96
50 / 37.5	575	59.0	52.0	T1526	\$8,295	D3	45	19.75/502	10.26/261	8.55/217	96
60 / 44	575	71.0	62.0	T1527	\$9,279	D3	51	19.75/502	10.26/261	8.55/217	96

★ Stock Model

Footnotes:

96 Drive has cooling fan

REGAL-BELOIT SpinMaster® PowerWash™ AC Adjustable Speed Drives

Constant Torque, Washdown NEMA 4 and NEMA 12, Inverter



REGAL-BELOIT
SpinMaster®

Applications: Constant torque applications. Typical applications include machinery found in food processing, dairies, slaughter houses, beverage plants, car washes, and other high humidity or wet environments.

- Features:**
- **NEMA 4:** Dust and water-tight
 - **NEMA 12:** With cooling fan
 - Epoxy finished enclosure, fully gasketed dust and water-tight
 - Current limit to 180% with frequency foldback
 - Adjustable carrier frequency
 - Independent accel and decel times
 - Adjustable DC injection braking
 - Serial Communication interface
 - Programmable inputs/outputs
 - UL Listed and UL Certified for Canada under File No. E197830
 - 2 year warranty

Single Phase Input / Three Phase Output

HP / kW	INPUT VOLTAGE	INPUT AMPS	OUTPUT AMPS 200 / 230 VAC	CAT. NO.	LIST PRICE	MULT. SYMB.	APPROX. WGT. LBS.	HEIGHT	WIDTH	DEPTH	NEMA ENCL.
								IN / MM	IN / MM	IN / MM	
0.25 / 0.19	120 / 240	6.0 / 3.0	1.4	T400	\$1,056	D3	7	7.88 / 200	6.12 / 155	3.63 / 92	4
0.50 / 0.38	120 / 240	9.2 / 4.6	2.2	T402	\$1,154	D3	8	7.88 / 200	7.86 / 200	3.75 / 95	4
1 / 0.75	120 / 240	16.2 / 8.1	4.0	T404	\$1,262	D3	11	7.88 / 200	7.86 / 200	4.90 / 124	4
1.5 / 1.1	120 / 240	21 / 10.4	5.2	T405	\$1,484	D3	11	7.88 / 200	7.86 / 200	4.90 / 124	4
2 / 1.5	240	14.9	6.8	T406	\$1,343	D3	11	7.88 / 200	7.86 / 200	4.90 / 124	4
3 / 2.2	240	21.0	9.6	T407	\$1,423	D3	13	7.88 / 200	7.86 / 200	5.90 / 150	4

Three Phase Input / Three Phase Output

HP / kW	INPUT VOLTAGE	INPUT AMPS	OUTPUT AMPS	CAT. NO.	LIST PRICE	MULT. SYMB.	APPROX. WGT. LBS.	HEIGHT	WIDTH	DEPTH	NEMA ENCL.
								IN / MM	IN / MM	IN / MM	
0.50 / 0.38	208 / 240	3.1 / 2.7	2.5 / 2.2	T422 ★	\$1,136	D3	8	7.88 / 200	6.12 / 155	4.35 / 110	4
1 / 0.75	208 / 240	5.5 / 4.8	4.6 / 4.0	T424 ★	\$1,233	D3	8	7.88 / 200	6.12 / 155	4.35 / 110	4
1.5 / 1.1	208 / 240	7.1 / 6.2	6.0 / 5.2	T425 ★	\$1,250	D3	9	7.88 / 200	6.12 / 155	5.25 / 133	4
2 / 1.5	208 / 240	9.3 / 8.1	7.8 / 6.8	T426 ★	\$1,322	D3	11	7.88 / 200	7.86 / 200	4.90 / 124	4
3 / 2.2	208 / 240	12.9 / 11.3	11.0 / 9.6	T427 ★	\$1,429	D3	12	7.88 / 200	7.86 / 200	4.90 / 124	4
5 / 3.7	208 / 240	20.4 / 17.7	17.5 / 15.2	T428 ★	\$1,763	D3	26	9.75 / 247	10.26 / 261	7.20 / 183	4
7.5 / 5.5	208 / 240	29.9 / 26.0	25.3 / 22.0	T429	\$2,445	D3	26	11.75 / 298	10.26 / 261	8.35 / 212	4
10 / 7.5	208 / 240	36.8 / 32.0	32.2 / 28.0	T430	\$3,085	D3	31	13.75 / 349	10.26 / 261	8.35 / 212	4
15 / 11	208 / 240	55.2 / 48.0	48.3 / 42.0	T431	\$3,720	D3	35	15.75 / 400	10.26 / 261	8.35 / 212	4
20 / 15	208 / 240	70.0 / 61.0	62.0 / 54.0	T532	\$4,775	D3	35	15.75 / 400	10.26 / 261	8.35 / 212	12
25 / 18.5	208 / 240	89.0 / 77.0	78.0 / 68.0	T533	\$6,544	D3	45	20.25 / 514	10.26 / 261	8.35 / 212	12
30 / 22	208 / 240	104 / 90.0	92.0 / 80.0	T534	\$6,934	D3	45	20.25 / 514	10.26 / 261	8.35 / 212	12
1 / 0.75	480	2.4	2.0	T434 ★	\$1,390	D3	8	7.88 / 200	6.12 / 155	4.35 / 110	4
2 / 1.5	480	4.1	3.4	T436 ★	\$1,534	D3	11	7.88 / 200	7.86 / 200	4.90 / 124	4
3 / 2.2	480	5.7	4.8	T437 ★	\$1,643	D3	11	7.88 / 200	7.86 / 200	4.90 / 124	4
5 / 3.7	480	8.9	7.6	T438 ★	\$1,817	D3	12	7.88 / 200	7.86 / 200	5.90 / 150	4
7.5 / 5.5	480	12.8	11.0	T439	\$2,303	D3	26	9.75 / 247	10.26 / 261	7.20 / 183	4
10 / 7.5	480	15.9	14.0	T440	\$3,071	D3	26	11.75 / 298	10.26 / 261	8.35 / 212	4
15 / 11	480	24.0	21.0	T441	\$3,825	D3	31	13.75 / 349	10.26 / 261	8.35 / 212	4
20 / 15	480	31.0	27.0	T442	\$4,906	D3	35	15.75 / 400	10.26 / 261	8.35 / 212	4
25 / 18.5	480	38.0	34.0	T543	\$5,664	D3	35	15.75 / 400	10.26 / 261	8.35 / 212	12
30 / 22	480	45.0	40.0	T544	\$6,190	D3	36	15.75 / 400	10.26 / 261	8.35 / 212	12
40 / 30	480	59.0	52.0	T545	\$7,160	D3	45	20.25 / 514	10.26 / 261	8.35 / 212	12
50 / 37.5	480	74.0	65.0	T546	\$8,310	D3	58	21.00 / 533	13.72 / 348	8.35 / 212	12
60 / 44	480	87.0	77.0	T547	\$9,356	D3	80	21.00 / 533	13.72 / 348	8.35 / 212	12

★ Stock Model

REGAL-BELOIT SpinMaster® PowerWash™ AC Adjustable Speed Drives

Constant Torque, Washdown NEMA 4 and NEMA 12, Inverter

Three Phase Input / Three Phase Output

HP / kW	INPUT VOLTAGE	INPUT AMPS	OUTPUT AMPS	CAT. NO.	LIST PRICE	MULT. SYMB.	APPROX. WGT. LBS.	HEIGHT	WIDTH	DEPTH	NEMA ENCL.
								IN / MM	IN / MM	IN / MM	
1 / 0.75	575	1.9	1.6	T444 *	\$1,512	D3	8	7.88 / 200	6.12 / 155	4.35 / 110	4
2 / 1.5	575	3.3	2.7	T446 *	\$1,687	D3	11	7.88 / 200	7.86 / 200	4.90 / 124	4
3 / 2.2	575	4.6	3.9	T447 *	\$1,839	D3	11	7.88 / 200	7.86 / 200	4.90 / 124	4
5 / 3.7	575	7.1	6.1	T448 *	\$1,980	D3	12	7.88 / 200	7.86 / 200	5.90 / 150	4
7.5 / 5.5	575	10.5	9.0	T449	\$2,723	D3	26	9.75 / 247	10.26 / 261	7.20 / 183	4
10 / 7.5	575	12.5	11.0	T450	\$3,571	D3	26	11.75 / 298	10.26 / 261	8.35 / 212	4
15 / 11	575	19.3	17.0	T451	\$4,314	D3	31	13.75 / 349	10.26 / 261	8.35 / 212	4
20 / 15	575	25.0	22.0	T453	\$5,251	D3	35	15.75 / 400	10.26 / 261	8.35 / 212	4
25 / 18.5	575	31.0	27.0	T553	\$6,262	D3	35	15.75 / 400	10.26 / 261	8.35 / 212	12
30 / 22	575	36.0	32.0	T554	\$6,873	D3	36	15.75 / 400	10.26 / 261	8.35 / 212	12
40 / 30	575	47.0	41.0	T555	\$7,957	D3	45	20.25 / 514	10.26 / 261	8.35 / 212	12
50 / 37.5	575	59.0	52.0	T556	\$9,289	D3	58	21.00 / 533	13.72 / 348	8.35 / 212	12
60 / 44	575	71.0	62.0	T557	\$10,391	D3	80	21.00 / 533	13.72 / 348	8.35 / 212	12

* Stock Model

AC DRIVES

REGAL-BELOIT SpinMaster® PowerWash™ AC Adjustable Speed Drives

Constant Torque, Washdown NEMA 4X, Inverter



REGAL-BELOIT
SpinMaster®

Applications: Constant torque applications. Typical applications include machinery found in food processing, dairies, slaughter houses, beverage plants, car washes, and other high humidity or wet environments where a NEMA 4X enclosure is required.

- Features:**
- **NEMA 4X:** Stainless steel enclosure, fully gasketed dust and water-tight
 - Current limit to 180% with frequency foldback
 - Adjustable carrier frequency
 - Independent accel and decel times
 - Adjustable DC injection braking
 - Serial communication interface
 - Programmable inputs/outputs
 - UL Listed and UL Certified for Canada under File No. E197830
 - 2 year warranty

Single Phase Input / Three Phase Output

HP / kW	INPUT VOLTAGE	INPUT AMPS	OUTPUT AMPS 200 / 230 VAC	CAT. NO.	LIST PRICE	MULT. SYMB.	APPROX. WGT. LBS.	HEIGHT	WIDTH	DEPTH
								IN / MM	IN / MM	IN / MM
0.25 / 0.19	120 / 240	6.0 / 3.0	1.4	T410	\$1,305	D3	7	7.88 / 200	6.12 / 155	3.63 / 92
0.50 / 0.38	120 / 240	9.2 / 4.6	2.2	T412	\$1,451	D3	8	7.88 / 200	7.86 / 200	3.75 / 95
1 / 0.75	120 / 240	16.2 / 8.1	4.0	T414	\$1,555	D3	11	7.88 / 200	7.86 / 200	4.90 / 124
1.5 / 1.1	120 / 240	21 / 10.4	5.2	T415	\$1,912	D3	11	7.88 / 200	7.86 / 200	4.90 / 124
2 / 1.5	240	14.9	6.8	T416	\$1,635	D3	11	7.88 / 200	7.86 / 200	4.90 / 124
3 / 2.2	240	21.0	9.6	T417	\$1,715	D3	13	7.88 / 200	7.86 / 200	5.90 / 150

Three Phase Input / Three Phase Output

HP / kW	INPUT VOLTAGE	INPUT AMPS	OUTPUT AMPS	CAT. NO.	LIST PRICE	MULT. SYMB.	APPROX. WGT. LBS.	HEIGHT	WIDTH	DEPTH
								IN / MM	IN / MM	IN / MM
1/2 / 0.38	208 / 240	2.7	2.2	T452	\$1,334	D3	8	7.88 / 200	6.12 / 155	4.35 / 110
1 / 0.75	208 / 240	4.8	4.6 / 4.0	T454	\$1,431	D3	8	7.88 / 200	6.12 / 155	4.35 / 110
1 1/2 / 1.1	208 / 240	6.2	6.0 / 5.2	T455	\$1,498	D3	9	7.88 / 200	6.12 / 155	5.25 / 133
2 / 1.5	208 / 240	8.1	7.8 / 6.8	T456	\$1,588	D3	11	7.88 / 200	7.86 / 200	4.90 / 124
3 / 2.2	208 / 240	11.3	11.0 / 9.6	T457	\$1,668	D3	12	7.88 / 200	7.86 / 200	4.90 / 124
5 / 3.7	208 / 240	17.7	17.5 / 15.2	T458	\$2,323	D3	26	9.75 / 247	10.26 / 261	7.20 / 183
7.5 / 5.5	208 / 240	29.9 / 26.0	25.3 / 22.0	T459	\$2,859	D3	26	11.75 / 298	10.26 / 261	8.35 / 212
10 / 7.5	208 / 240	36.8 / 32.0	32.2 / 28.0	T460	\$3,566	D3	31	13.75 / 349	10.26 / 261	8.35 / 212
15 / 11	208 / 240	55.2 / 48.0	48.3 / 42.0	T461	\$4,358	D3	35	15.75 / 400	10.26 / 261	8.35 / 212
1 / 0.75	480	2.4	2.0	T464	\$1,573	D3	8	7.88 / 200	6.12 / 155	4.35 / 110
2 / 1.5	480	4.1	3.4	T466	\$1,781	D3	12	7.88 / 200	7.86 / 200	4.90 / 124
3 / 2.2	480	5.7	4.8	T467	\$1,912	D3	12	7.88 / 200	7.86 / 200	4.90 / 124
5 / 3.7	480	8.9	7.6	T468	\$2,182	D3	14	7.88 / 200	7.86 / 200	5.90 / 150
7.5 / 5.5	480	12.8	11.0	T469	\$2,959	D3	26	9.75 / 247	10.26 / 261	7.20 / 183
10 / 7.5	480	15.9	14.0	T470	\$3,666	D3	26	11.75 / 298	10.26 / 261	8.35 / 212
15 / 11	480	24.0	21.0	T471	\$4,386	D3	31	13.75 / 349	10.26 / 261	8.35 / 212
20 / 15	480	31.0	27.0	T472	\$5,414	D3	35	15.75 / 400	10.26 / 261	8.35 / 212
1 / 0.75	575	1.9	1.6	T474	\$1,709	D3	8	7.88 / 200	6.12 / 155	4.35 / 110
2 / 1.5	575	3.3	2.7	T476	\$1,908	D3	12	7.88 / 200	7.86 / 200	4.90 / 124
3 / 2.2	575	4.6	3.9	T477	\$2,063	D3	12	7.88 / 200	7.86 / 200	4.90 / 124
5 / 3.7	575	7.1	6.1	T478	\$2,335	D3	14	7.88 / 200	7.86 / 200	5.90 / 150
7.5 / 5.5	575	10.5	9.0	T479	\$3,156	D3	26	9.75 / 247	10.26 / 261	7.20 / 183
10 / 7.5	575	12.5	11.0	T480	\$4,052	D3	26	11.75 / 298	10.26 / 261	8.35 / 212
15 / 11	575	19.3	17.0	T481	\$4,867	D3	31	13.75 / 349	10.26 / 261	8.35 / 212
20 / 15	575	25.0	22.0	T482	\$5,883	D3	40	15.75 / 400	10.26 / 261	8.35 / 212